



# Factory-Match Seam Sealer

## 08323

Technical Data Sheet

June 2020

3M Part No.(s)	3M Part Descriptor(s)
08323	3M™ Factory-Match Seam Sealer

**Product Description** 3M™ Factory-Match Seam Sealer uses two-part urethane technology to provide a tough flexible material for the sealing of joints on primed or painted substrates such as steel or aluminum enclosures. This material provides excellent flexibility and elongation properties along with a medium/high viscosity and produces a slight flow-out after application. 3M™ Factory-Match Seam Sealer may be top coated with paints in 45 minutes under normal temperature and humidity conditions.

- Features**
- Two-Part Urethane Technology
  - 200 mL Dual - Syringe Cartridge
  - Metered Static Mixing

**Typical Physical Properties**

**Note:** The following technical information and data should be considered representative or typical only and should not be used for specification purposes.

<b>Container</b>	200 mL Dual-Syringe Cartridge
<b>Base</b>	Urethane
<b>Density lbs/Gallon (Appx.)</b>	8.5 / 8.7
<b>Color</b>	Black / Amber
<b>Viscosity (CPS) Brookfield Viscometer</b>	1,000 - 3,000 cps
<b>Consistency</b>	Paste
<b>Solvent</b>	N/A
<b>Service Temperature - °F</b>	-20°F to 180°F

# 3M™ Factory-Match Seam Sealer

08323

---

**Product Uses**

A two-part seam sealer suitable for the sealing of seams on primed or painted substrates such as steel or aluminum enclosures. This material provides excellent flexibility and elongation properties along with a medium/high viscosity and produces a slight flow-out after application. 3M™ Factory-Match Seam Sealer may be top coated with paints in 45 minutes under normal conditions.

**Use with the following applicators: PN 08117 (manual), PN 08571(manual), and PN 09930 (pneumatic).**

**3M™ Mix Nozzle: PN 08193 (6/bag), PN 8194 (50/box).**

**For professional use only. Not intended for retail sale.**

---

**Typical Performance Properties**

**The following times have been determined with ambient air temperature and substrate temperature @ 70°F (21°C) and are considered typical values.**

**WORK TIME:**

10 minutes

**MIX NOZZLE DWELL TIME:**

6 minutes

**CURE TIME:**

4 hours

**PAINT TIME:**

45 minutes

**TENSILE STRENGTH:**

2515 PSI

**ELONGATION:**

390%

---

**Directions for Use**

**NOTE:** 3M Best Practice is that all sealers, unless designated specifically for use on bare metal be applied to properly prepared automotive paint or primer.

**SURFACE PREPARATION:**

**NOTE:** Apply only to surfaces primed with a 2K urethane, 2K epoxy primer, or clean, sanded paint. Acid etch primers should never be in direct contact with seam sealer.

1. Scuff primed surface with a Scotch-Brite™ General Purpose Hand Pad (Ultrafine), (PN 07448).
2. Blow off dust with clean, compressed air and wipe with an appropriate VOC compliant surface cleaner for the removal of surface contaminates.

# 3M™ Factory-Match Seam Sealer

08323

---

## Directions for Use (continued)

### PRODUCT PREPARATION:

1. Insert cartridge into applicator gun.
2. Remove retaining collar and plug from end of cartridge. Discard plug & save retaining collar.
3. Extrude a small amount of product until both parts A and B dispense equally.
4. Attach 3M™ Mixing Nozzle (PN 08193) to cartridge and lock in place with retaining collar.
5. Dispense a small amount of material and discard.

### GENERAL REPAIR PROCESS:

Extrude sealer onto surface. Allow to cure a minimum of 15 minutes before beginning the painting process.

**NOTE:** If sealer is cured for more than 24 hours, scuff the sealer prior to any painting steps.

### APPLICATION WARNINGS:

Not to be used in direct contact with acid etch primers.

### STORAGE:

After initial use, leave mix nozzle in place to seal the cartridge.

### CLEAN-UP:

Unmixed material may be cleaned from most surfaces with a VOC compliant product.

---

## Applications

A two-part seam sealer for seams of primed or painted substrates such as steel or aluminum enclosures. This sealer is not recommended for the repair of vessels designed to contain liquids or liquids under pressure and is primarily used in the auto body repair industry but may be suitable for some architectural or industrial applications (user assumes responsibility to test for suitability).

---

## Storage and Handling

### HANDLING

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water. Keep out of the reach of children. Keep container closed when not in use. Avoid breathing of dust created by cutting, sanding, grinding or machining. For industrial or professional use only. Avoid eye contact with dust or airborne particles.

### STORAGE

When stored at the recommended conditions in original, unopened containers, this product has a shelf life of 12 months from the date of manufacture. Store in a dry area at 72°F for optimal shelf life. Store away from acids and other oxidizing agents.

**After use, leave mix nozzle in place to seal the cartridge.**

# 3M™ Factory-Match Seam Sealer

08323

---

## Precautionary Information

Before using this product, please reference Product Label and/or Safety Data Sheet for Health and Safety Information. Note: Laws controlling the acceptable amounts of Volatile Organic Compounds (VOC's) vary by state, and in some cases by locality. For surface preparation and clean-up activities, consult federal, state and local regulations regarding use of products containing VOCs in your area.

---

## Technical Information

The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.

---

## Product Selection Use

Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product in accordance with all applicable instructions and with appropriate safety equipment, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

---

## Warranty, Limited Remedy, and Disclaimer

Unless different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement or repair of the 3M product or refund of the purchase price. Warranty claims must be made within one (1) year from the date of 3M's shipment.

---

## Limitation of Liability

Except for the limited remedy stated above, and except to the extent prohibited by applicable law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.

---

## Disclaimer

3M industrial and occupational products are intended, labeled, and packaged for sale to trained industrial and occupational customers for workplace use. Unless specifically stated otherwise on the applicable product packaging or literature, these products are not intended, labeled, or packaged for sale to or use by consumers (e.g., for home, personal, primary or secondary school, recreational/sporting, or other uses not described in the applicable product packaging or literature), and must be selected and used in compliance with applicable health and safety regulations and standards (e.g., U.S. OSHA, ANSI), as well as all product literature, user instructions, warnings, and other limitations, and the user must take any action required under any recall, field action or other product use notice. Misuse of 3M industrial and occupational products may result in injury, sickness, death, or property damage. For help with product selection and use, consult your on-site safety professional, industrial hygienist, or other subject matter expert. For additional product information, visit [www.3M.com](http://www.3M.com).



### Automotive Aftermarket Division

3M Center, Building 223-6S-07  
St. Paul, MN 55144-1000  
1-877-666-2277 (1-877-MMM-CARS)  
[www.3MCollision.com](http://www.3MCollision.com)

This is the last page

3M and Scotch-Brite are trademarks of 3M Company.  
Printed in U.S.A.  
©3M 2020 P.N. 08323 (6/20)