



Model # 3083

**2.5" DIAL
TIRE INFLATOR
WITH
LOCKING &
DUAL CHUCKS**

SALES AND MARKETING

1230 Santa Anita Avenue, Suite E
South El Monte, CA 91733
Phone: (800) 221-9705
USA Toll Free
Fax: (877) 318-2194
Phone: (626) 228-3170
Fax: (626) 228-3124

372 Old US Highway
52 South
Mount Airy, NC 27030
(800) 221-9705
Phone: (336) 786-6432
Fax: (336) 786-4992

LARGER 2.5" DIAMETER FACE
Gauge is up to 2X the accuracy of the B40.1 ANSI standard with larger 2.5" diameter face for finer resolution and easier to see readings

HOSE SWIVEL

AIR BLEED & RESET BUTTON
Bleed valve button releases pressure from the tire to your desired range or clears display after checking pressure with dual chuck

"M" STYLE FITTING ON TOOL

0-160 PSI RANGE
Allows for high pressures from the compressor without damaging gauge display

"T" STYLE FITTING

6" DUAL CHUCK

LOCKING CHUCK

Model	Pressure Gauge	Port Size	Pressure
3083	2.5"	1/4" NPT	Max. 160 psi
Hose Length	Working Temp	Accuracy	Resolution
15"	-4°F ~ 176°F	+/- 1.5%	2 psi

**DESIGNED TO INFLATE,
DEFLATE AND MEASURE
TIRE PRESSURE**

 **Astro**
E-mail : astrotools@astrotools.com
WEBSITE : www.astrotools.com



SHOP EQUIPMENT

