

## Interchange Chart

| SKU            | Acme  | Amflo | ARO       | Dill  | Dynaquip   | Foster   | Hansen    | Lincoln | Milton | Parker | Schrader | Truflate |
|----------------|-------|-------|-----------|-------|------------|----------|-----------|---------|--------|--------|----------|----------|
| <b>AES-866</b> | A918B | C20   | 210       | 8888  | DY-340     | 210-3003 | 102       | 632004  | 715    | 53     | 3526     | 13-334   |
| <b>AES-868</b> | A916N | CP-20 | 2609      | 8889  | P-2609A    | 210-11   | 1G2       | 630204  | 728    | A3C    | 3530     | 12-334   |
| <b>AES-869</b> | A914N | CP-21 | 2608      | 8891  | P-2608A    | 210-10   | 1G3       | 639104  | 727    | A2C    | 3529     | 12-324   |
| <b>AES-860</b> | A937B | C38   | 23102-200 | 10002 | D340/DM340 | 3003     | 3000-1000 | 862     | 775    | 23     | 5412-12  | 13-234   |
| <b>AES-862</b> | A911N | CP38  | 23902-200 | 10009 | P-340      | 11-3     | 11        | 13331   | 778    | H3C    | 5139-11  | 12-234   |
| <b>AES-863</b> | A910N | CP37  | 23902-210 | 10010 | P-341      | 10-3     | 10        | 13329   | 777    | H2C    | 5138-11  | 12-224   |

## Air Couplers



**Choose AES High Air Flow couplers and connectors for maximum air flow and performance!**



### Universal Air Coupler, Female AES-844

Designed to fit all popular brands of air nipples, such as AMFLO, ARO, MILTON, PARKER, TRU-FLATE and more. Tough brass construction.

- Large 3/8" inside diameter for optimal air flow
- Quick connect push-in locking mechanism
- Fits standard 1/4" and 3/8" fittings

HANG-UP CARD

| Specifications            |
|---------------------------|
| Construction: Brass       |
| Thread Size: 1/4" NPT (F) |



### Universal Air Coupler, Male AES-844-M

Designed to fit all popular brands of air nipples, such as AMFLO, ARO, MILTON, PARKER, TRU-FLATE and more. Tough brass construction.

- Large 3/8" inside diameter for optimal air flow
- Quick connect push-in locking mechanism
- Fits standard 1/4" and 3/8" fittings

HANG-UP CARD

| Specifications            |
|---------------------------|
| Construction: Brass       |
| Thread Size: 1/4" NPT (M) |



### Universal Safety Quick Coupler, Female AES-849

Eliminate dangerous blow-back with the AES-849 Safety Quick Coupler. Featuring a safety sleeve that releases downstream air pressure prior to disconnecting fittings. Automatic push-in coupling mechanism makes connecting air fittings quick and easy. Fits 1/4" AES, ARO, TRU-FLATE, Milton and Lincoln style connectors.

- Eliminates dangerous blow back during disconnects
- Quick connect push-in locking mechanism
- Fits standard 1/4" fittings

HANG-UP CARD

| Specifications            |
|---------------------------|
| Thread Size: 1/4" NPT (F) |



### Quick Air Coupler, Female AES-866

Interchangeable with Milton 715.

- Quick connect push-in locking mechanism
- Corrosion resistant full brass construction

HANG-UP CARD

| Specifications            |
|---------------------------|
| Construction: Brass       |
| Thread Size: 1/4" NPT (F) |



### Universal Air Coupler, Male AES-866-S

Designed for heavy duty use with all air tools. Rust resistant chromium plating. Interchangeable with Milton 715.

- Quick connect push-in locking mechanism
- Rust resistant chromium plating

HANG-UP CARD

| Specifications            |
|---------------------------|
| Construction: Steel       |
| Thread Size: 1/4" NPT (F) |



### Lincoln Air Coupler, Female AES-840

Accepts Lincoln style connectors. Rust resistant chromium plating.

- Fits Lincoln style connectors
- Quick connect push-in locking mechanism
- Fits standard 1/4" fittings

HANG-UP CARD

| Specifications            |
|---------------------------|
| Construction: Steel       |
| Thread Size: 1/4" NPT (F) |



### Quick Air Coupler, Female AES-860

Compact push-in coupler. Interchangeable with Milton 775.

- Quick connect push-in locking mechanism
- Corrosion resistant full brass construction

HANG-UP CARD

| Specifications            |
|---------------------------|
| Construction: Brass       |
| Thread Size: 1/4" NPT (F) |