IMPACT WRENCHES



1285-XL 1/2" COMPOSITE IMPACT WRENCH

- 900 ft-lb maximum torque and 1,100 ft-lb loosening torque
- Hard hitting twin hammer mechanism delivers maximum power
- Grip has been ergonomically designed to perfectly fit the hand-providing unmatched comfort for the user
- Molded buffers protect the tool from side impacts
- Push button forward/reverse buttons for fast and convenient change of direction
- Power management switch provides ultimate control

1150

1/2" COMPOSITE IMPACT WRENCH

- Provides 900 ft-lb maximum torque and 1,295 ft-lb of loosening torque
- Most powerful 1/2" impact in it's class!
- Hard hitting twin hammer mechanism
- Durable composite housing
- Patented ergonomically designed handle
- Patented quiet tuned exhaust (86 dBA)
- Patented easy operation flip lever forward and reverse







1150-BB Black AIRCAT® Boot Fits Models: 1150, 1000-TH and 1000-TH-2

SPECIFICATIONS

| | of Lon Tonitonio | | | 11 - A.S. | B. Bach | A State of the " | AND STREET STREET | | | CARLE ENTRY | | S. 192 |
|---|------------------|---------------------|---------------------------|--------------------------|-----------------------|------------------------|-------------------|----------------|--------------------|----------------------------|---------------------------|--------|
| | Model No. | Free Speed (RPM) | Bolt Capacity (in.) | Square Drive (in.) | Impacts Per Minute | Max. Torque (ft-lb) | Weight (lbs.) | Length (in) | Air Cons. (CFM) | Rec. Hose Size (in.) | Air Inlet NPT (in.) | |
| ą | 1285-XL | 7,500 | 9/16 | 1/2 | 1600 | 900 | 4.6 | 6.66 | 8 | 3/8 | 1/4 | |
| | 1150 | 9,000 | 9/16 | 1/2 | 1400 | 900 | 4.5 | 7.5 | 8 | 3/8 | 1/4 | |