FASTENER SERVICE AUTOMOTIVE SPECIALTY TOOLS





4554

Torque Angle Gauge

 Required when servicing many late model engines that use torque-to-yield fasteners. Measures angle of rotation after pretorque in torque-angle applications.



- The 360° scale is marked in 2° increments and intervals of 10° and 30°; easily zeroed for next application by turning the tool housing.
- Has 1/2" male and female square drives.

Torque Multiplier, 1100 ft-lb

- Drive Input; 1/2", 365 lb-ft Max
- Drive Output; 3/4", 1100 lb-ft Max
- Head Width; 2.9", 3.3:1 Ratio
- Reaction Bar; 13-3/4"
- Includes reaction foot.
- Note; frictional gear loss = 6%



7368

Torque Multiplier, 2200 lb-ft

- Drive Input; 3/4", 730 lb-ft Max
- Drive Output; 1", 2200 lb-ft Max
- Head Width; 3.6", 3.3:1 Ratio
- Reaction Bar; 15-5/8"
- Includes reaction foot.
- Note: frictional gear loss = 6%



7380-E150

Digital Torque Wrench

- Displays torque in real time and at peak when torque is released.
- Torque value accuracy is $\pm 1\%$ clockwise (CW) and counterclockwise (CCW) from 10%-100% of full scale.
- Can be used to measure bearing preload torque values.
- Display starts at 1% to 250% of full scale; has a 5-digit, alpha-numeric LCD, and indicator icons for functions, units and battery.
- Indicators include green, yellow and red LED light, an audible buzzer, and vibration.
- 1/4" Drive, 36 tooth ratchet head. Range 1.5 – 150 In Lb.



5776 Preset Torque Wrench Set

These color coded click torque wrenches are pre-set to the most common lug nut torque settings, making them perfect for tire shops. Highly durable design can hold up to the toughest tire shop demands.

- No need for adjustments
- Durable satin finish
- 1/2" Drive, 36 tooth
- Quick release ratchet head
- Perfect for Wheel / Tire shop
- Accuracy better than ±3% CW Sold Individually:

5776-1

Preset Torque Wrench, 1/2" 65 lb-ft

5776-2

Preset Torque Wrench, 1/2" 80 lb-ft

5776-3

Preset Torque Wrench, 1/2" 100 lb-ft

5776-4

Preset Torque Wrench, 1/2" 120 lb-ft

5776-5

Preset Torque Wrench, 1/2" 140 lb-ft



