

Dual Voltage Two Stage Vacuum Pumps

DUAL VOLTAGE



GAS BALLAST VALVE

LARGE OIL SIGHTGLASS



Universal IEC plug
All units/dual voltage 115V & 230V

Dual voltage design vacuum pump operates on 115 VAC or 230 VAC (50 or 60Hz). Advanced two-stage design pulls deep vacuum fast to 15 microns.

| Model | VP2D | VP3D | VP6D |
|------------------------------|--------------------------------------|----------------------------------|-----------------------------------|
| Free Air Displacement | 1.9 CFM @ 60HZ 45 l/m @ 50Hz | 3.15 CFM @ 60HZ 75 l/m @ 50Hz | 6.25 CFM @ 60HZ 148 l/m @ 50Hz |
| Horse Power RPM (50/60Hz) | 1/4 HP 1440/1720 | 1/3 HP 1440/1720 | 1/2 HP 2880/3440 |
| Ultimate Vacuum | 15 microns | | |
| Inlet Ports (male flare) | 1/4", 3/8" SAE Male & 1/2" ACME Male | | |
| Oil Capacity | 12oz./350 ml | 15oz./450ml | 15oz./450ml |
| Dimensions | 13" x 5.3" x 10" | 13.7" x 5.6" x 10.4" | 13.7" x 5.6" x 10.4" |
| Shipping Weight | 21.66lb/9.8kg | 25.42 lb/11.5kg | 25.42lb/11.5kg |

For Australia: VP2DA, VP3DA, VP6DA all Single Voltage 240VAC/50Hz.

| Model | VP8D | VP10D | VP12D |
|------------------------------|-------------------------------------|-----------------------------------|-----------------------------------|
| Free Air Displacement | 7.9 CFM @ 60HZ 186 l/m @ 50Hz | 10.0 CFM @ 60HZ 236 l/m @ 50Hz | 11.8 CFM @ 60HZ 278 l/m @ 50Hz |
| Horse Power RPM (50/60Hz) | 2/3 HP 2880/3440 | 2/3 HP 2880/3440 | 3/4 HP 2880/3440 |
| Ultimate Vacuum | 15 microns | | |
| Inlet Ports (male flare) | 1/4", 3/8" SAE Male & 1/2" SAE Male | | |
| Oil Capacity | 13.5 oz./400ml | 14 oz./425ml | 15 oz./450ml |
| Dimensions | 15" x 6.2" x 11.2" | | |
| Shipping Weight | 32.95lb/14.5kg | 34.26lb/15.5kg | 36.47lb/16.5kg |

Dual Voltage Single Stage Vacuum Pumps

DUAL VOLTAGE



LARGE OIL SIGHTGLASS



| Model | VP2S | VP3S | VP6S |
|------------------------------|--------------------------------------|----------------------------------|-----------------------------------|
| Free Air Displacement | 1.9 CFM @ 60HZ 45 l/m @ 50Hz | 3.15 CFM @ 60HZ 75 l/m @ 50Hz | 5.85 CFM @ 60HZ 138 l/m @ 50Hz |
| Horse Power RPM (50/60Hz) | 1/5 HP 1440/1720 | 1/4 HP 1440/1720 | 1/3 HP 1440/1720 |
| Ultimate Vacuum | 100 microns | | |
| Inlet Ports (male flare) | 1/4", 3/8" SAE Male & 1/2" ACME Male | | |
| Oil Capacity | 13.5 oz./400 ml | 13 oz./380 ml | 17 oz./500 ml |
| Dimensions | 13" x 5.3" x 10" | 13" x 5.3" x 10" | 13.7" x 5.6" x 10.4" |
| Shipping Weight | 18.11lb/8.2kg | 19.44lb/8.8kg | 24.75lb/11.2kg |

VPXJ220
220 VAC jumper power cord for locations where 110 voltage is not available.



VPXOMP
Oil mist preventer exhaust port.

