

SPARK PLUGS | IGNITION

2375 SPARK PLUG SOCKET

- 5/8" X 6 PT - 6" LONG
Dual 3/8" square & 3/4" hex drive.



5061 5 PC. SPARK PLUG SOCKET SET



Includes:

No.	Size	OAL
1730	5/8" x 12 Pt	6"
2376	16mm	2.5"
2380	5/8" x 6 Pt	10"
2390	9/16" x 6 Pt	10"
2394	14mm x 6 Pt	10"



1730 SPARK PLUG SOCKET - CHRYSLER

- 5/8" X 12 PT - 6" LONG
Thin wall magnetic socket services
2000s Jeep Grand Cherokee
& Commander, Dodge
Dakota, Durango & Ram
1500, Chrysler Aspen
& Mitsubishi Raider.



2380 SPARK PLUG SOCKET

- 5/8" X 6 PT - 10" LONG
Deep-reach w/ recessed
magnet. Services
Dodge Ram 1500 4.7L,
Honda & Toyota. 3/8" drive.



2395 SPARK PLUG SOCKET - BMW

- 5/8" X 6 PT - 14" LONG
Extra-long for hard-to-reach plugs found on 2006-2015 BMW N52,
N53, M54 In-line 6 engines (except turbocharged). Internal magnet,
chrome plated, knurled end & 3/8" drive.



2369 SPARK PLUG SOCKET - FORD

- 9/16" X 6 PT
For Ford Triton V8 & V10 Engines.
2.5" long & 3/8" drive.



2385 SPARK PLUG SOCKET SWIVEL - FORD

- 9/16" X 6 PT - 6" LONG
For Ford Triton V8 & V10 Engines.
3/8" drive w/ plastic holding insert.



2390 SPARK PLUG SOCKET - FORD

- 9/16" X 6 PT - 10" LONG
For Ford Triton V8 & V10 Engines.
Deep reach & 3/8" drive.



2376 SPARK PLUG SOCKET - 14MM X 12 PT

Thin-wall socket for many late model
BMW, Mini, Benz & more. 2.5" long
& 3/8" drive. Comparable to Factory
Tool: 121220.



2394 SPARK PLUG SOCKET - TOYOTA

- 14MM x 6 PT - 10" LONG
Deep-reach. Internal magnet holds spark plug firmly. For Toyota/Lexus/
Scion 1.8L, plus Nissan, Land Rover, Jaguar & more. 3/8" drive.



2030 4 PC. METRIC SWIVEL SPARK PLUG SOCKET SET



Includes:

No.	Size	OAL
1061	14mm x 12 Pt	3.6"
4329	16mm x 12 Pt	3.6"
7654	14mm x 12 Pt	8.7"
7656	16mm x 12 Pt	8.7"

SPARK PLUG SOCKETS - THIN WALL SWIVEL

Required for BMW N54, N55 & N63, Benz, and other
Euro applications. Rubber insert to hold spark plug.
3/8" square drive. 3.6" OAL.

No.	Size
1061	14mm
4329	16mm



SPARK PLUG SOCKETS - LONG SWIVEL EXTENSION

12 Point spark plug sockets w/ 15-20° degree
swivel extension. OAL: 8.7" (22cm).

No.	Size
7654	14mm
7656	16mm



3055 VW/AUDI SPARK PLUG CABLE TOOL

For vehicles w/ steel spark plug boots. Engages ears of boot shield,
saves wires from damage
& saves time (no need to
remove intake manifold). Extra-long shaft & T-handle for pulling power
OAL: 14" (35cm). Comparable to VW Factory Tool #T-10029.



3052 SPARK PLUG WIRE BOOT PLIERS

Removes spark plug wire boots safely.
Insulated handles & jaws. Small
indentations in jaws allow gripping
a bare terminal w/ engine running.



5303 BENZ IGNITION LOCK REMOVER

Removal & replacement of main ignition switch
retaining ring on W129, W140, W164, W169, W171,
W199, W202, W203, W209, W210, W211, W215,
W219, W220, W221, W230, W240, W245, W251
& W414. Compare to Benz Factory Tool
#129 589 00 007 00.



1088 5 PC. VW/AUDI TRIANGLE BOLT SOCKET SET

Fits triangular tamperproof fixings on VW
Audi TDi, Bosch injector & pump seals, or
adjust VW TDi injection pump timing on
1996-2003 TDi injection pumps. Accesses
fuel temperature sensor by removing screws on top pump cover.
Includes sizes: M5 (8mm), M6 (10mm), M8 (12mm), M10 (15mm)
& M12 (16.5mm). 1/2" drive on metal rail. Chrome vanadium.



3280 IGNITION FILE

Long, thin blade for precision
filing of points & other small objects. OAL: 5.25" (13cm).



3018 SPARK PLUG WIRE TESTER

Tests presence of spark w/o risk of shock or damage to
wires. Identifies badly fouled spark plugs. Includes:
48" (122cm) lead, hooded alligator clip
& inductive tester w/ LED.



3020 UNIVERSAL IGNITION SPARK TESTER

Quickly & safely troubleshoots no-starts. See & hear if spark is
present, test intensity or test spark timing w/ conventional ignition.

