




# Fittings



P-H-4069




P-H-4090



P-H-4091

## DeVilbiss Quick Disconnects (Air)


Part Number	Type	Description	Connection Size	Max. Working Pressure	Service Form
P-H-4069	Stem	Air bayonet	1/4" npt(m)	250 psi	n/a
P-H-4090	Body	Air bayonet	1/4" npt(f)	250 psi	n/a
P-H-4091	Body	Air bayonet	1/4" npt(m)	250 psi	n/a




HC-4699



HC-4700



HC-1166




HC-4419




MPV-60-K3

## DeVilbiss Quick Disconnects (High-Flow Air)


Part Number	Type	Description	Connection Size	Max. Working Pressure	Service Form
HC-4699	Body (f)	Hi-flow	1/4" universal (m)	230 psi	SB-12-001
HC-4700	Body (f)	Hi-flow	1/4" npt(f)	230 psi	SB-12-001
HC-1166	Stem (m)	Hi-flow	1/4" npt(m)	230 psi	SB-12-001
HC-4419	Stem (m)	Hi-flow	1/4" nps(f)	230 psi	SB-12-001
MPV-60-K3	Stem (f)	Hi-flow (ball swivel)	1/4" nps(f)	230 psi	n/a




72-1823, 72-1869



72-1927



111-1354



83-2155

## Gun/Outlet Manifolds

Part Number	Max. Working Pressure	No. of Outlets	Outlet Threads	Inlet Swivel Nut	Notes
72-994	200 psi	2	3/8" npt(f)	7/8" -18 nps(f)	Ptld brass
72-1823	250 psi	2	3/8" nps(m)	3/8" nps(f)	Stainless steel
72-1927	250 psi	2	1/4" nps(m)	1/4" nps(f)	Plated brass fittings, plated steel body and swivel nut
72-1869	1000 psi	2	1/4" nps(m)	3/8" nps(f)	Stainless steel
111-1354*	3000 psi	2	1/4" nps(m)	1/4" nps(f)	Used in circulating and heated fluid systems for fluid
83-2155	4000 psi	2	3/8" npt(m)	1" npt(f)	303 Stainless steel body with 4000 psi valves

\*For 2-gun air outlet for AA spray guns, remove the 2 ea. 1/8" npt(m) x 1/4" nps(m) fittings and add 2 ea. 1/8" -1/4" i.d. x 3/8" o.d. tube fittings (54-4975).

N/R = Non-Rated • Ptld brass = Plated brass, chrome • S.S. = Stainless steel  
Galv. = Galvanized steel • Steel ptld = Plated steel, cadmium or zinc • Poly = Polypropylene plastic