



## WATER FLEXEEL® INDUSTRIAL STRENGTH WATER HOSE

We have incorporated the popular characteristics of Flexeel into a new industrial strength water hose. Water Flexeel weighs 50% less than traditional hoses so it is easy to carry and handle. It's also the perfect hose for hose reels because its light weight and elastic properties make winding and unwinding a snap. Water Flexeel is made of reinforced industrial grade polyurethane so it retains its flexibility under all conditions. Water Flexeel is also UV stabilized and crack-resistant so it will last season after season.

### Features:

- Weighs 50% less than traditional hose.
- Drinking water safe.
- Manufactured from industrial-grade polyurethane so it is ideal for home, garden and commercial use.
- Solid brass, crush-proof fittings.
- Retains its flexibility, unlike other hoses which become stiff.
- Integral strain relief with bend restrictor.

I.D.	Length	Color	Model
1/2"	50'	Green	A774H50-G
1/2"	50'	Blue	A774H50-B
1/2"	75'	Green	A774H75-G
1/2"	75'	Blue	A774H75-B
5/8"	50'	Green	A774K50-G
5/8"	50'	Blue	A774K50-B
5/8"	75'	Green	A774K75-G
5/8"	75'	Blue	A774K75-B

Hose I.D.	Hose O.D.	Maximum Water Temperature	Flow Rate	Working Pressure at 70° F
1/2"	.730"	110° F	12.9 gal. / minute	100 PSI
5/8"	.830"	110° F	15.5 gal. / minute	100 PSI



## GENERAL PURPOSE AIR HOSE

### Features:

- EPDM (Ethylene-Propylene Diene Terpolymer) cover, backing and tubing with a single braid polyester rayon cord for additional strength.
- Designed for air applications where contact with petroleum products is minimal.
- Can be used with crimped-on barb fittings or reusable fittings.

I.D.	Length	Fitting	Model
1/4"	25'	1/4" MPT	A720D-25
1/4"	50'	1/4" MPT	A720D-50
1/4"	100'	1/4" MPT	A720D-100
1/4"	600'	No Fittings (reel)*	A720-600
3/8"	25'	1/4" MPT	A724D-25
3/8"	25'	3/8" MPT	A724F-25
3/8"	35'	1/4" MPT	A724D-35
3/8"	35'	3/8" MPT	A724F-35
3/8"	50'	1/4" MPT	A724D-50
3/8"	50'	3/8" MPT	A724F-50
3/8"	100'	1/4" MPT	A724D-100
3/8"	100'	3/8" MPT	A724F-100
3/8"	600'	No Fittings (reel)*	A724-600

Hose I.D.	Hose O.D.	Temperature Range	Working Pressure at 70° F
1/4"	17/32"	- 40° F to 180° F	250 PSI
5/16"	5/8"	- 40° F to 180° F	250 PSI
3/8"	21/32"	- 40° F to 180° F	250 PSI
1/2"	57/64"	- 40° F to 180° F	250 PSI

\*Reel lengths shown are approximate and may vary. Please consult factory for actual length upon placing an order.

See page 31 for replacement fittings.



## THERMOPLASTIC AIR HOSE

### Features:

- Combines prime PVC with special additives, allowing this hose to resist long term deterioration caused by exposure to air line lubricating oils.
- Tough cover protects against scuffs, cuts and abrasions while the rayon spiral synthetic cord assures added strength.
- Use with crimped-on barb fittings or reusable fittings.

I.D.	Length	Fitting	Model
1/4"	25'	1/4" MPT	A730D-25
1/4"	50'	1/4" MPT	A730D-50
1/4"	500'	No Fittings (reel)*	A730-500
3/8"	25'	1/4" MPT	A734D-25
3/8"	25'	3/8" MPT	A734F-25
3/8"	50'	1/4" MPT	A734D-50
3/8"	50'	3/8" MPT	A734F-50
3/8"	500'	No Fittings (reel)*	A734-500
1/2"	25'	1/2" MPT	A736H-25
1/2"	50'	1/2" MPT	A736H-50
1/2"	500'	No Fittings (reel)*	A736-500

Hose I.D.	Hose O.D.	Temperature Range	Working Pressure at 70° F
1/4"	1/2"	-20° F to 150° F	300 PSI
3/8"	41/64"	-20° F to 150° F	300 PSI
1/2"	25/32"	-20° F to 150° F	300 PSI

\*Reel lengths shown are approximate and may vary. Please consult factory for actual length upon placing an order.

See page 31 for replacement fittings.



Glad Hand assembly includes a standard universal quick disconnect air line coupler, which is used between all truck tractors and trailers equipped with air brakes, and a reducer bushing (1/2" to 1/4"). Available in packages of 10.

## CAB-AIR KITS

### Features:

- Auxiliary inflator kit for compressor-equipped trucks.
- Provides low cost tire care for a vehicle, anytime, anywhere.
- Reduces road calls and minimizes down time.
- Increases tire life and improves tire safety.
- Coupler provides a quick change of blow gun and dual foot extension chuck.
- Contents include a 1/4" I.D. Hose, glad hand with reducer bushing (A808), dual foot chuck (A824), safety blow gun (A633), two connectors (A937N4M), coupler (A937B) and 1/4" MPT fitting.

Hose length	Hose Type	Model
25'	Rubber	A713
50'	Polyurethane coil	A715

Components	Model
25' 1/4" I.D. red rubber hose with A937B coupler	A714
50' 1/4" I.D. polyurethane recoil hose with A937B coupler	A716
Glad hand assembly	A808



## FLEXEEL® COMPRESSOR ACCESSORY KIT

### Features:

- Includes everything needed to transfer and control air from the compressor to the air tool: a 3/8" 35' length of Flexeel; a high performance, compact filter/ regulator combo with gauge and coupler and connector; a ball swivel fitting; six ball industrial coupler and Teflon® tape.
- Ideal for contractors, mechanics and maintenance personnel.

Model number: A3708



## BODY SHOP KITS

### Features:

- Comes complete with everything you need between the air tool and the compressor.
- Includes an In-Line blow gun with rubber tip (A634RT-BL), 1/4" ball swivel Industrial Interchange connector (A937N4BS), 1/4" Automatic Universal male coupler (A937B4MU), and a 3/8" Flexeel hose.

Description	Model
Body Shop Kit with 35' Flexeel Hose	A3712
Body Shop Kit with 50' Flexeel Hose	A3713



## PAINT BOOTH KITS

### Features:

- Comes complete with everything you need between the paint gun and the compressor.
- Includes an In-Line blow gun with rubber tip (A634RT-BL), a female high flow ball swivel (A923N4BSF) and a high flow composite coupler (A923MB4M).
- A3711 includes a 3/8" I.D. x 1/4" MPT 35' Flexeel (A750FD35TR); A3714 includes a 3/8" I.D. x 1/4" MPT 35' Rubber hose (A724D-35).

Description	Model
Paint Booth Kit with 35' Flexeel Hose	A3711
Paint Booth Kit with 35' Red Rubber Hose	A3714