



Specifications

Weight (gun only)	500g
Gun Body	Anodized Aluminum
Air Cap	Plated Brass
Air Cap Retaining Ring & Knobs	Black Anodized Aluminum
Fluid Nozzle	Stainless Steel
Fluid Needle	Stainless Steel
Air Inlet Thread	1/4" Universal
Service Bulletin	SB-E-2-995

Top Assembly Part Numbers

Part Number	Description	Air Cap	Nozzle Size	Material Cup	Gauge
905016	GPG Gravity HVLP Gun Kit	GPG2	1.3mm, 1.4mm, 1.5mm	900ml, Aluminum	HAV-501
905012	GPG Gravity HVLP Gun Kit	GPG2	1.3mm, 1.5mm, 1.8mm	900ml, Aluminum	HAV-501
905013	GPG Gravity HVLP Gun Kit	GPG2	1.3mm, 1.5mm, 1.8mm	560ml, Acetal	HAV-501
905014	GPG Gravity HVLP Gun Kit	GPG2	1.8mm, 2.2mm	900ml, Aluminum	-
905015	GPG Gravity High Efficiency Gun Kit	7E7	1.2mm, 1.3mm, 1.4mm	900ml, Aluminum	HAV-501
905019	GPG Gravity High Efficiency Gun Kit	7E7	1.3mm, 1.4mm	-	HAV-555
905020	GPG Gravity High Efficiency Gun Kit	7E7	1.3mm, 1.4mm	900ml, Aluminum	HAV-555
905021	GPG Gravity High Efficiency Gun Kit	7E7	1.2mm, 1.3mm	-	HAV-555
905022	GPG Gravity High Efficiency Gun Kit	7E7	1.2mm, 1.3mm	900ml, Aluminum	HAV-555
905026	GPG Gravity HVLP & High Efficiency Gun Kit	PR10 & PR30	1.4mm, 1.6mm	900ml, Aluminum	-
905027	GPG Gravity HVLP & High Efficiency Gun Kit	PR10 & PR30	1.8mm, 2.0mm	900ml, Aluminum	-
905028	GPG Gravity HVLP & High Efficiency Gun Kit	PR10 & PR30	2.5mm	900ml, Aluminum	-
905036	GPG Gravity HVLP & High Efficiency UV Primer Gun Kit	PR10 & PR30	UV1, UV2	560ml, UV Cup	-

Air Cap Offerings



Air Cap	Atomization Type	Applications	Recommended Inlet Pressures		Max Air Consumption		Fan Pattern Size		Nozzle Sizes
			PSI	BAR	SCFM	SLPM	in	mm	
Multi-purpose									
7E7	High Efficiency	Basecoats, Clearcoats	16-22	1.1-1.5	10.8	305	9.5-10.5	240-265	1.2mm-1.4mm
GPG2	HVLP	Basecoats, Clearcoats	22-26	1.5-1.8	15.9	450	11.5-12.0	290-310	1.2mm-2.2mm
C86	Conventional	Basecoats, Clearcoats	29-44	2.0-3.0	10.6	300	10.5-11.5	270-290	1.4mm-1.8mm
C30	Conventional	Basecoats, Clearcoats	29-58	2.0-4.0	10.8	305	9.5-10.5	240-270	1.4mm-1.8mm
Primers									
PR10	High Efficiency	Primers	26-29	1.8-2.0	12.0	340	10.5-12.0	265-305	1.4mm-2.5mm, UV1, UV2
PR30	HVLP	Primers	17-21	1.2-1.4	16.0	450	11.0-13.0	280-330	1.4mm-2.5mm, UV1, UV2

Refer to autorefinishdevilbiss.com for a complete listing of approved areas and requirements for regulatory compliance.