

Electric Tools

Electric Dynafile® II Abrasive Belt Tool

Model 40610

- Electric Dynafile® II runs coated abrasive and non-woven nylon belts, and is ideal for countless applications on metal, plastic, fiberglass, solid surface, stone, glass, etc.
- Includes 11203 Contact Arm, for abrasive belts 1/2" wide by 18" long.
- Grind with contact wheel or platen pad. Finish and polish using slack of belt.
- Tool accepts over 20 interchangeable contact arms for use with belts 1/4" to 3/4" wide x 18" long.
- Comfortable switch with "lock on" feature.
- Easily accessible brushes for quick replacement.
- Sanding head pivots 360°, for working in previously inaccessible areas.
- Reversible side handle for operator comfort.
- Tool is double-insulated for safety, and includes electric cord, 8 feet in length.



Electric Dynafile® II Versatility Kit

Model 40611

- Includes 40610 Electric Dynafile® II with 11203 Contact Arm, and two additional arms (11202 and 11204). Also includes eight abrasive belts of various grits, and an assortment of platen pads. All items contained in a durable carrying case.

Model Number	Motor RPM	Maximum Watts Out	Abrasive Belt Size Inch (mm)	Voltage	Current Amps	Phase	Frequency	Weight Pound (kg)	Length Inch (mm)	Height Inch (mm)
40610	11,000	680	1/4-3/4 (6-19) W x 18-24 (457-610) L	120 V (AC)	6	1	60 Hz	5 (2.3)	19 (483)	5.5 (140)

Additional Specifications: Maximum 2,520 SFPM (768 SMPM)

Electric Depressed Center Wheel Grinder

Model 40260

- For 4-1/2" diameter grinding wheels and abrasive discs.
- 5/8"-11 spindle thread accepts optional Type 27 Depressed Center Wheels and Abrasive Flap Discs, 4-1/2" diameter with 7/8" center hole.
- Industrial-quality electric motor rated at 6 amps.
- Easily accessible brush holders allow quick brush replacement (recommended every 150 hours).
- Convenient spindle lock offers fast change of accessory.
- Locking power switch for extended use with less fatigue.
- Repositioning side handle for left or right hand operation.
- All ball-bearing and needle-bearing construction ensures longer tool durability.



120 V (AC)

Important: Always use required wheel guard. Never remove wheel guard from tool. Speed of tool must not exceed maximum operating speed of accessory. Never mount bonded grinding wheels. Always wear eye, face and body protection.

Model Number	Maximum Watts Out	Motor RPM	Voltage (AC)	Current Amps	Phase	Frequency	* Weight Pound	Length Inch	Height Inch
40260	680	11,000	120	6	1	60 Hz	4.6	12	4.25

*Weight includes flanges, side handle and wheel guard, with no wheel attached.

DynaPen Filer Kit

- Ideal for intricate deburring on delicate parts.
- Powers files at 14,000 strokes a minute, in short stroke length of .007" (.018 mm).
- Air line swivels 360° for great maneuverability, especially on contoured parts.
- One-touch on/off button, conveniently mounted to air line.
- Tool also accepts optional collet sizes of 1/16" (51780) and 3/32" (51674).

10844 Kit

- Includes 10832 DynaPen with 51673 Collet Insert (3 mm), 51659 Collet Insert (1/8"), 95731 Wrench, 90900 Straight File, 90901 Curved File and 90930 Half-Round File.

Model 10843

- Tool includes 51659 Collet Insert (1/8") only.



**ASK ABOUT
KITS WITH
CHISELS AND
SCRIBE POINTS!**



Model Number	Motor RPM	Stroke Length Inch	Maximum Air Flow SCFM	Air Pressure PSIG	Collet Size	Weight Pound	Length Inch	Diameter Inch	Hose Length Inch
10832	14,000	.007	7	90	3 mm	.57	4.25	.9	56

AutobradeRed® FOR THE VALUE-MINDED PRO

Auto File II Abrasive Belt Tool

Model 18100

3/4" Wide

- Includes 11206 Contact Arm for 3/4" x 18" long coated abrasive and non-woven nylon belts. 1/2" x 18" long belts also fit.
- Excellent multi-purpose tool for grinding sharp metal edges, rusted bolts, welds, etc. Works well on composites, blending, scuffing grooves and contours. Hundreds of uses in every shop!



Additional contact arms available – call for details.

Four-In-One Versatility Kit

18025

1/4" Die Grinder • 3" Cut-Off Tool
Belt Sander • 3" Disc Sander

- Quick and convenient, easy to change accessories. A must for all shops.
- Includes: 18100 basic tool, .5 hp gearless 20,000 RPM motor, front exhaust, 7° offset composite handle with safety-lock throttle; 50010 Collet; 50292 Cut-Off Guard; 50269 Flange; 51347 3" Backing Pad (3/8"-24); 15352 Drive Wheel; 40014 Belt Housing Assembly; 11206 Contact Arm Assembly; 94300 Dynaswivel®; wrenches for accessory changes; sample abrasive belt and 3" abrasive disc; deluxe storage/carrying case.



Model Number	Motor hp	Motor RPM	Sound Level	Maximum Air Flow CFM/SCFM	Air Inlet Thread	Hose Size Inch	Air Pressure PSIG	Weight Pound	Length Inch	Height Inch
18100	.5	20,000	79 dB(A)	3/22	1/4" NPT	3/8	90	2.8	15	5