

Dynaswivel® Air Line Connectors

Never Fight an Air Hose Again!

- Dynaswivel® is a “universal-joint” that connects portable air tools to an air line.
- It improves tool maneuverability, minimizes operator fatigue and extends hose life.
- Patented; works great on air tools or paint guns.
- Choose from the most popular original Dynaswivel® style:
 - SWIVELS 360° AT TWO LOCATIONS which allows air hose to drop straight to the floor, no matter how the tool is held.
- OR, choose from the “single-pivot” style:
 - Right angle, “single-pivot” swivels 360° at one location. Permits 360° maneuverability of tool, while air hose extends horizontally.



1/8" NPT Model

95852

- 1/4" NPT and 1/8" NPT; fits small air tool.
- Air flow: up to 25 SCFM.
- Weight: 0.19 lb.
- Heavy duty aluminum.



1/4" NPT Model

95460

- Air flow: up to 25 SCFM.
- Heavy duty aluminum.



1/4" NPT, Composite Model

94300


- Air flow: up to 33 SCFM.
- Non-marring lightweight composite construction.
- Allows greater air flow than the “original” model (see 95460).



1/4" NPT, Flow Control Model

95734

- Air flow: up to 25 SCFM.
- Built-in dial allows for air flow control.
- Heavy duty aluminum.



1/4" NPT, Flow Control, Composite Model

94407

- Air flow: up to 46 SCFM.
- Built-in dial allows for air flow control.



1/4", 3/8" & 1/2" NPT, Single-Pivot

- Heavy duty aluminum.

95590

1/4" NPT

- Air flow: up to 25 SCFM.

95591

3/8" NPT

- Air flow: 26 to 45 SCFM.

95592

1/2" NPT

- Air flow: 46 to 65 SCFM.



3/8", 1/2" & 3/4" NPT Models

- Heavy duty aluminum.

95461

3/8" NPT

- Air flow: 26 to 45 SCFM.

95462

1/2" NPT

- Air flow: 46 to 65 SCFM.



95690

3/4" NPT

- Air flow: above 65 SCFM.

Ball-Swivel Plug

97016

- Offers 53° conical range of motion for added tool maneuverability and operator comfort.
- A natural fit with Dynabrade palm-style Random Orbital Sanders!
- Ported plug design allows air flow up to 74 SCFM.
- Maximum air pressure of 90 PSIG.



Important: 150 PSI maximum on all models. Do not use on percussion tools or in areas of high mechanical abuse.

Note: Do not exceed recommended torque value of 20 ft. lbs.

Point-of-Purchase Air Line Accessories

Pre-Packaged Accessories for Showroom and Will Call Areas!

Lightweight 8mm I.D. Air Line Assembly

- Air line is 66% lighter than conventional hoses.
- High flexibility and narrow bending prevents choking.
- Includes one male and one female fitting.

76018 5 ft. Length

76019 2 ft. Length

76018



Dynaswivel® Air Line Connector

Never Fight an Air Hose Again!

- Dynaswivel® rotates 360° at two locations allowing air hose to drop straight to the floor, no matter how the tool is held.
- 1/4" NPT.

94300 Non-Marring Composite Construction

95460 Aluminum Construction

94300



96177

Dynaswivel® Store Counter Display Pack

96177

- Ten 94300 1/4" NPT Dynaswivel® Air Line Connectors in a refillable display box.
- Convenient way to buy!

Coupler and Plug Sets

76004 Push-Button Quick Coupler and Plug Set

- Lightweight 1.4 oz, non-marring composite material.
- Heavy-duty construction.
- 1/4" Female Coupler to 1/4" Male Plug.

76005 Pull-Back Steel and Brass Coupler/Plug Set

- Durable nickel-plated steel and brass construction.
- Pull back on sleeve of coupler for quick disconnect of tool from air line.
- 1/4" Female Coupler to 1/4" Male Plug.



76004



76005

DynaJet In-Line Blow Guns

- Purges air lines of water and contaminants before starting air tool.
- Clean off work pieces after grinding and sanding.
- Meets O.S.H.A. requirements which limits air pressure to 30 PSIG.

76003 DynaJet In-Line Blow Gun with Safety Tip

76002 Standard DynaJet In-Line Blow Gun



76003



76002