

Reducing Nipples

Male-male reducing nipple – steel



| Part no. | Ø M1 | Ø M2 | Quantity |
|----------|------|------|----------|
| 36020 | 1/4" | 1/8" | 5 |
| 36011 | 1/4" | 1/4" | 5 |
| 36021 | 3/8" | 1/4" | 5 |
| 36012 | 3/8" | 3/8" | 5 |
| 36031 | 1/2" | 1/4" | 5 |
| 36022 | 1/2" | 3/8" | 5 |
| 36013 | 1/2" | 1/2" | 5 |
| 36023 | 3/4" | 1/2" | 5 |
| 36014 | 3/4" | 3/4" | 5 |
| 36024 | 1" | 3/4" | 5 |
| 36015 | 1" | 1" | 5 |

Male-female reducing nipple – steel



| Part no. | Ø M | Ø F | Quantity |
|----------|------|------|----------|
| 36040 | 1/4" | 1/8" | 5 |
| 36050 | 3/8" | 1/8" | 5 |
| 36041 | 3/8" | 1/4" | 5 |
| 36051 | 1/2" | 1/4" | 5 |
| 36042 | 1/2" | 3/8" | 5 |
| 36052 | 3/4" | 3/8" | 5 |
| 36043 | 3/4" | 1/2" | 5 |

Female-male reducing nipple – steel



| Part no. | Ø F | Ø M | Quantity |
|----------|------|------|----------|
| 36060 | 1/4" | 1/8" | 5 |
| 36061 | 3/8" | 1/4" | 5 |
| 36062 | 1/2" | 3/8" | 5 |
| 36063 | 3/4" | 1/2" | 5 |

Female-female reducing nipple – steel



| Part no. | Ø F1 | Ø F2 | Quantity |
|----------|------|------|----------|
| 36080 | 1/4" | 1/8" | 5 |
| 36231 | 1/4" | 1/4" | 5 |
| 36081 | 3/8" | 1/4" | 5 |
| 36232 | 3/8" | 3/8" | 5 |
| 36082 | 1/2" | 3/8" | 5 |
| 36233 | 1/2" | 1/2" | 5 |
| 36083 | 3/4" | 1/2" | 5 |

BSPP = BSP parallel female thread.
BSPT = BSP taper male thread.

Male Ends

Steel



| Part no. | Ø M | Ø H | Quantity |
|----------|------|-----|----------|
| 35006 | 1/4" | 6 | 1 |
| 35007 | 1/4" | 7 | 5 |
| 35008 | 1/4" | 8 | 1 |
| 35010 | 1/4" | 10 | 5 |
| 35012 | 1/4" | 12 | 5 |
| 35013 | 1/4" | 13 | 1 |
| 35107 | 3/8" | 7 | 5 |
| 35108 | 3/8" | 8 | 5 |
| 35110F | 3/8" | 10 | 5 |
| 35113 | 3/8" | 13 | 1 |
| 36208 | 1/2" | 8 | 1 |
| 36211 | 1/2" | 11 | 1 |
| 36213 | 1/2" | 13 | 1 |
| 36221 | 1/2" | 16 | 5 |
| 36222 | 1/2" | 19 | 5 |

Parkerised steel



| Part no. | Ø M | Ø H | Quantity |
|--------------------|------|-----|----------|
| BSPT Thread | | | |
| R-78 | 1/4" | 7 | 5 |
| R-108 | 1/4" | 10 | 5 |
| R-138 | 1/4" | 13 | 5 |
| R-1012 | 3/8" | 10 | 5 |
| R-1312 | 3/8" | 13 | 5 |
| R-1615 | 1/2" | 16 | 5 |
| R-1920 | 3/4" | 19 | 5 |
| R-2526 | 1" | 25 | 5 |
| NPT Thread | | | |
| RB-108 | 1/4" | 10 | 5 |
| RB-1312 | 3/8" | 13 | 5 |
| RB-1615 | 1/2" | 16 | 5 |
| RB-1920 | 3/4" | 19 | 5 |

Tool Regulator

Steel



| Part no. | |
|----------|-----------------------|
| 326-250 | 1/4" NPTF x 1/4" NPTM |

Swivel-It™ Universal Joints

Bi-directional 360° rotation, increases operator comfort and productivity.



| Part no. | | Maximum flow (l/s) |
|--|----------|--------------------|
| Aluminium and Steel / Adjustable Flow | | |
| ASA-1/4 | 1/4" NPT | 11.8 |
| Composite Material and Steel | | |
| ASC-1/4 | 1/4" NPT | 15.5 |
| Aluminium and Steel | | |
| AS-3/8 | 3/8" NPT | 21.2 |
| AS-1/2 | 1/2" NPT | 28.3 |

Air Control Needle Valves

Composite material.
Female threads.
Maximum operating pressure: 13.8 bar.
Operating temperature 0-90°C.



| Part no. | |
|------------|-------------|
| 104104-N02 | 1/4" NPT(F) |
| 104104-N03 | 3/8" NPT(F) |
| 104104-N04 | 1/2" NPT(F) |
| 104104-N06 | 3/4" NPT(F) |