

Air Finishing Tools



4151-HL
150 mm (6"), orbit 5 mm (3/16")



- 0.15 kW (0.20 HP)
- 12,000 rpm
- Only 0.86 kg
- Composite Housing
- Auto-Balancer
- Power regulator

Also available

- 4152-HL**
150 mm (6"), orbit 2.5 mm (3/32")
- 4151-HL-2**
150 mm (6"), orbit 5 mm (3/16")

| Ref. | CCN | mm | mm | mm | kWatt | rpm | kg | mm | in | mm | l/s | l/s | dB(A) | m/s ² /K ⁽¹⁾ |
|-----------|----------|-----|------|------------|-------|--------|------|-----|---------|----|-----|------|-------|------------------------------------|
| 4151-HL | 1371624 | 150 | 5.00 | 5/16" - 24 | 0.15 | 12,000 | 0.86 | 190 | 1/4 NPT | 8 | 3.7 | 7.20 | 81.6 | 7.5/1.6 |
| 4151-HL-2 | 22041198 | 150 | 5.00 | 5/16" - 24 | 0.15 | 12,000 | 1.12 | 252 | 1/4 NPT | 8 | 3.7 | 7.20 | 81.6 | 6.2/1.0 |
| 4152-HL | 80134356 | 150 | 2.50 | 5/16" - 24 | 0.15 | 12,000 | 0.86 | 190 | 1/4 NPT | 8 | 3.7 | 7.20 | 81.6 | 8.2/1.7 |

⁽¹⁾ ISO28927 – 3-axis measurement: vibration level/measurement uncertainty.

Air Finishing tools | Air Sanders and Polishers

3103XPA
Sander - Tool only



- 50 mm (2") and 75 mm (3")
- 0.15 kW (0.2 HP)
- 15,000 rpm
- Only 0.50 kg and 135 mm
- Composite housing
- 2-position power regulator

Available in kits
3103KA Kit
CCN: 47520769001



Includes 14-piece 2" (50mm) and 3" (75mm) sanding discs and pads

3128XPA
RO Sander - Tool only



- 75 mm (3")
- Orbit 5 mm (3/16")
- 0.15 kW (0.2 HP)
- 15,000 rpm
- Only 0.60 kg and 145 mm
- Composite housing
- 2-position power regulator

Available in kits
3128KA Kit
CCN: 47520770001



Includes 71-piece hook and loop discs and pad:
- 180, 220, 320 and 800 grits aluminum oxide
- backing pad

3129XPA
Polisher - Tool only



- 75 mm (3")
- 0.22 kW (0.30 HP)
- 6,400 rpm
- Only 0.60 kg and 155 mm
- Composite housing
- 2-position power regulator

Available in kits
3129KA Kit
CCN: 47520771001



Includes four-piece hook and loop pads with foams

| Ref. | CCN | mm | mm | kWatt | rpm | kg | mm | in | mm | l/s | l/s | dB(A) | m/s ² /K ⁽¹⁾ |
|---------|-------------|-----------|------|-------|--------|------|-----|---------|----|-----|------|-------|------------------------------------|
| 3103XPA | 47520748001 | 50 and 75 | - | 0.15 | 15,000 | 0.50 | 135 | 1/4 NPT | 10 | 9.0 | 0.00 | 78.6 | 4.1/0.8 |
| 3128XPA | 47520749001 | 75 | 5.00 | 0.15 | 15,000 | 0.60 | 145 | 1/4 NPT | 10 | 8.6 | 0.00 | 80.9 | 5.2/1.1 |
| 3129XPA | 47520750001 | 75 | - | 0.22 | 6,400 | 0.60 | 155 | 1/4 NPT | 10 | 9.4 | 0.00 | 81.5 | 2.7/0.7 |

⁽¹⁾ ISO28927 – 3-axis measurement: vibration level/measurement uncertainty.