

**For use with: Gasoline, Diesel, Kerosene,
Bio-Diesel, Transmission Fluid**

FC-25GC & FC-25DC



25 GALLON U.L. LISTED STEEL GAS CADDY

Designed for the professional automotive service facility. Tested and approved to UL requirements for leakage, rupture, stability, abuse and endurance. Meets OSHA approved standards - with safety the number one priority.

Features include:

- 25-gallon capacity steel tank
- UL Listed and complies with OSHA guidelines
- UL Listed cast iron pump
- 10" steel wheels
- Fill level gauge
- Fire-screened vent and filler neck
- Wide footprint for stability
- 8' PVC suction/discharge hose with internal steel grounding wire
- Tank ground wire & clamp
- Decal set for contents identification
- Two-way filter kit available



HANDLING
FUEL



UL Listed Pump

This heavy-duty, UL Listed cast iron rotary pump with carbon vanes and Viton seals offers a two-way operation for siphoning or dispensing fuel. One gallon is delivered for every 12 revolutions on the pump handle.



Also Available in Yellow for Diesel Only

SPECIFICATIONS:	FC-25GC & FC-25DC
CAPACITY	25-GALLONS
MATERIAL	14-GAUGE STEEL
PUMP	TWO-WAY, UL LISTED CAST IRON ROTARY
WHEEL SIZE	10" HEAVY-DUTY STEEL
DIMENSIONS	21"W x 13"L x 46"H
WEIGHT	95 LBS.