

STEEL ^{GAS} CADDIES

WITH MANUAL OR AIR OPERATED PUMP

Pumps available on the PRO30 Gas Caddies

FC-P30-UL



UL Listed Two-Way Rotary Pump

This heavy-duty UL listed pump features carbon vanes and Viton seals. The 2-way operation allows for either siphoning or dispensing fuel. One gallon is delivered for every 12 turns of the pump handle.

FC-P30A-UL



UL Listed Air Diaphragm Pump

Designed for efficiency and productivity. Fuel is pumped to and from the vehicle by an air operated pump. Shop air is connected to the air throttle control on the top of the tank resulting in quick and quiet service.

SPECIFICATIONS:	FC-P30-UL	FC-P30A-UL
GALLONS	30-GALLON	30-GALLON
MATERIAL	STEEL	STEEL
PUMP	TWO-WAY MANUAL	UL LISTED AIR OPERATED
WHEEL SIZE - FRONT	5" LOCKING SWIVEL CASTERS	5" LOCKING SWIVEL CASTERS
WHEEL SIZE - REAR	12" HEAVY-DUTY FIXED	12" HEAVY-DUTY FIXED
FILTER	10 MICRON	10 MICRON
DIMENSIONS	24" W X 30" L X 41" H	24" W X 30" L X 41" H
WEIGHT	165 LBS.	165 LBS.

Common features of both models include:



4-Way Valve

An integral 4-way valve clearly directs the flow of fuel to and from the vehicle.



Vent and Level Gauge

The level gauge provides a quick look at the tank fluid level while the vent prevents excess build-up of fumes.



Integral Filter System

To protect vehicle fuel pumps from being contaminated the P30-UL models are equipped with an in-line system that filters the fuel in both directions. A 10 micron filter is included. Replacement filters are available in 1, 10 and 30 microns.



Fill Spout

Fuel can be added to the caddy tank using the fill spout.

HANDLING FUEL