

Essential Industrial Safety Products



At Justrite, we partner with customers to better understand, anticipate and systematically address the safety challenges you face every day. Our extensive portfolio allows us to think holistically about your organization's vulnerabilities and deliver enterprise-wide compliance.

Justrite products and expertise help your organization to:

- Reduce fire risks
- Prevent environmental contamination
- Provide emergency relief to injured personnel
- Avoid injuries & accidents
- Avoid fines associated with non-compliance
- Stay in compliance to changing regulations
- Fulfill insurance carrier recommendations
- Improve housekeeping & operational efficiencies

Approval and Compliance Key

FM	Tested and approved by FM Approvals
UL/ULC	Underwriters Laboratories listed in the U.S. and Canada
ULCLAS	Tested and Approved by UL; Classified to ANSI Z358.1
TÜV	TÜV Technical Inspection Association certified
GS	Geprüfte Sicherheit – safety tested and GS certified by MPA Dresden
CE	Conformité Européenne – European conformity mark that is the manufacturer's declaration that a product meets applicable EC directives
N	Complies with National Fire Protection Association (NFPA) Flammable and Combustible Liquids Code 30
O	Complies with Occupational Safety and Health Administration (OSHA) Regulations
I	Complies with the International Fire Code (IFC)
A	Complies with NFPA 1 Fire Code - 2012 Edition
A9	Complies with NFPA 1 Fire Code - 2009 Edition
H	Complies with NFPA 400 Hazardous Material Code
AN	Meets or exceed American National Standards Institute (ANSI) Z358.1
EN	Complies with European standards EN 14470-1 and EN 14727
ENS	Complies with European standard for showers, EN15154
C	Compressed Gas Association (CGA) P1 Standard for Safe Handling of Compressed Gases in Containers
G	Complies with NFPA 55 Compressed Gases and Cryogenic Fluids Code
U	U.S. Geological Survey High Hazards Zone Requirements
E	Complies with Environmental Protection Agency (EPA) Regulations
S	Supports EPA Spill Prevention, Control and Countermeasures Rule (SPCC)
V	Validated by the EPA Environmental Technology Verification Program



Type I Safety Cans

Protect workers and reduce fire risks by transferring, storing and dispensing flammable liquids in OSHA-approved, single-spout Type I safety cans

- Self-closing, leakproof lid protects vapors from escaping and guards against spills
- Positive-pressure relief cap automatically vents can to guard against rupture or explosion
- Stainless steel flame arrestor dissipates heat to stop flashback ignition
- Guaranteed 100% leakproof construction
- Large label ID zone on swing-handle cans provides writing space to identify contents
- Trigger-release handle on cans up to 1-quart (1-L)
- Swinging handles on cans 1-gallon or larger help carry heavier loads
- Tough powder-coat finish resists chemicals.



Swinging, full-fisted rounded handle eases carrying.

Type I Safety Can Funnel

- Polypropylene funnel for sizes 1-gallon (4-L) and larger
- Two positions: folds down for filling, stays up when pouring
- Big bowl protects against splashes



Convenient hinged design allows you to fill the can without removing the funnel.



Description and Capacity	Dimensions OD x H	Approv/Lstg Regulation	Red Can Model	Red Can with Funnel* Model
Trigger Handle Type I Safety Cans				
1 pint (0.5 L) steel safety can	4.812 x 6.75 in (122 x 172 mm)	FM, UL/ULC, TÜV	10001	—
1 quart (1 L) steel safety can	4.812 x 8.25 in (122 x 210 mm)		10101	
1 gallon (4 L) steel safety can	7.25 x 11.5 in (184 x 292 mm)	FM, UL/ULC	10301	
Swinging Handle Type I Safety Cans				
1 gallon (4 L) steel safety can	9.5 x 11 in (241 x 279 mm)	FM, UL/ULC, TÜV	7110100	7110110
2 gallon (7.5 L) steel safety can	9.5 x 13.75 in (241 x 349 mm)		7120100	7120110
2.5 gallon (9.5 L) steel safety can	11.75 x 11.5 in (298 x 292 mm)		7125100	7125110
5 gallon (19 L) steel safety can	11.75 x 16.875 in (298 x 429 mm)		7150100	7150110
Polypropylene funnel for 1 gallon (4L) and larger	0.5 x 11.25 in (13 x 286 mm)	—	11202Y	—
Bolt-on funnel with galvanized hose for 1 gallon (4L) and larger	1 x 14 in (25 x 356 mm)		11089	

* Approvals apply to safety can only, not funnel.