

Essential Industrial Safety Products



At Justrite, we partner with customers to better understand, anticipate and systematically address the safety challenges you face every day. Our extensive portfolio allows us to think holistically about your organization's vulnerabilities and deliver enterprise-wide compliance.

Justrite products and expertise help your organization to:

- Reduce fire risks
- Prevent environmental contamination
- Provide emergency relief to injured personnel
- Avoid injuries & accidents
- Avoid fines associated with non-compliance
- Stay in compliance to changing regulations
- Fulfill insurance carrier recommendations
- Improve housekeeping & operational efficiencies

Approval and Compliance Key

FM	Tested and approved by FM Approvals
UL/ULC	Underwriters Laboratories listed in the U.S. and Canada
ULCLAS	Tested and Approved by UL; Classified to ANSI Z358.1
TÜV	TÜV Technical Inspection Association certified
GS	Geprüfte Sicherheit – safety tested and GS certified by MPA Dresden
CE	Conformité Européenne – European conformity mark that is the manufacturer's declaration that a product meets applicable EC directives
N	Complies with National Fire Protection Association (NFPA) Flammable and Combustible Liquids Code 30
O	Complies with Occupational Safety and Health Administration (OSHA) Regulations
I	Complies with the International Fire Code (IFC)
A	Complies with NFPA 1 Fire Code - 2012 Edition
A9	Complies with NFPA 1 Fire Code - 2009 Edition
H	Complies with NFPA 400 Hazardous Material Code
AN	Meets or exceed American National Standards Institute (ANSI) Z358.1
EN	Complies with European standards EN 14470-1 and EN 14727
ENS	Complies with European standard for showers, EN15154
C	Compressed Gas Association (CGA) P1 Standard for Safe Handling of Compressed Gases in Containers
G	Complies with NFPA 55 Compressed Gases and Cryogenic Fluids Code
U	U.S. Geological Survey High Hazards Zone Requirements
E	Complies with Environmental Protection Agency (EPA) Regulations
S	Supports EPA Spill Prevention, Control and Countermeasures Rule (SPCC)
V	Validated by the EPA Environmental Technology Verification Program



Oily Waste Cans

Dispose of oil-soaked rags and prevent fires caused by stray sparks or spontaneous combustion

- Lid stays closed when not in use to isolate contents from fire sources and limit available oxygen
- Round construction and elevated base allow circulation of air around can to disperse heat and reduce moisture build-up and rusting
- Durable steel construction with a powder-coat finish provides chemical resistance
- Swinging carry handle for portability
- Warning label with pictographs reduces miscommunication
- FM-approved; meets OSHA requirements



Foot pedal provides hands-free opening. When released, cover self-closes to reduce oxygen source and prevent a fire from starting.



Description and Nominal Gallon Capacity	OD x H	Approv/Lstg Regulation	Red Model	
			Foot-Operated	Hand-Operated*
0.45 gallon (2 L) oily waste can	7 x 10.5 in (178 x 267 mm)	FM, NESAM, EPA	—	09400
2 gallon (8 L) oily waste can	9.625 x 9.125 in (244 x 232 mm)	FM	—	09200
6 gallon (20 L) oily waste can	11.875 x 15.875 in (302 x 403 mm)	FM, UL, TÜV	09100	09110
10 gallon (34 L) oily waste can	13.938 x 18.25 in (354 x 464 mm)		09300	09310
14 gallon (52 L) oily waste can	16.063 x 20.25 in (408 x 514 mm)		09500	09510
21 gallon (80 L) oily waste can	18.375 x 23.438 in (467 x 595 mm)		09700	09710

*Hand-operated models do not have TÜV certification.