

Essential Industrial Safety Products



At Justrite, we partner with customers to better understand, anticipate and systematically address the safety challenges you face every day. Our extensive portfolio allows us to think holistically about your organization's vulnerabilities and deliver enterprise-wide compliance.

Justrite products and expertise help your organization to:

- Reduce fire risks
- Prevent environmental contamination
- Provide emergency relief to injured personnel
- Avoid injuries & accidents
- Avoid fines associated with non-compliance
- Stay in compliance to changing regulations
- Fulfill insurance carrier recommendations
- Improve housekeeping & operational efficiencies

Approval and Compliance Key

FM	Tested and approved by FM Approvals
UL/ULC	Underwriters Laboratories listed in the U.S. and Canada
ULCLAS	Tested and Approved by UL; Classified to ANSI Z358.1
TÜV	TÜV Technical Inspection Association certified
GS	Geprüfte Sicherheit – safety tested and GS certified by MPA Dresden
CE	Conformité Européenne – European conformity mark that is the manufacturer's declaration that a product meets applicable EC directives
N	Complies with National Fire Protection Association (NFPA) Flammable and Combustible Liquids Code 30
O	Complies with Occupational Safety and Health Administration (OSHA) Regulations
I	Complies with the International Fire Code (IFC)
A	Complies with NFPA 1 Fire Code - 2012 Edition
A9	Complies with NFPA 1 Fire Code - 2009 Edition
H	Complies with NFPA 400 Hazardous Material Code
AN	Meets or exceed American National Standards Institute (ANSI) Z358.1
EN	Complies with European standards EN 14470-1 and EN 14727
ENS	Complies with European standard for showers, EN15154
C	Compressed Gas Association (CGA) P1 Standard for Safe Handling of Compressed Gases in Containers
G	Complies with NFPA 55 Compressed Gases and Cryogenic Fluids Code
U	U.S. Geological Survey High Hazards Zone Requirements
E	Complies with Environmental Protection Agency (EPA) Regulations
S	Supports EPA Spill Prevention, Control and Countermeasures Rule (SPCC)
V	Validated by the EPA Environmental Technology Verification Program



Sure-Grip® EX Classic Safety Cabinets

Protect workers, reduce fire risks, and improve productivity by storing flammable fuels and chemicals in OSHA- and NFPA-compliant safety cabinets

- Independently fire tested and approved by FM Approvals
- 18-gauge (1-mm) thick double-wall, welded steel with 1-1/2-in (38-mm) of insulating air space.
- Adjustable, patented SpillsSlope® galvanized steel shelves direct spills to back and bottom of 2-in (51-mm) leakproof sump
- 3-point stainless steel bullet latching system
- Self-closing models feature a fusible link that holds doors open—in fire conditions it melts at 165 F (74 C) for automatic closure. Concealed mechanism offers obstruction-free access to contents.
- U-Loc™ handle with two keys—accepts optional padlock
- Trilingual warning with Haz-Alert™ reflective labels
- Includes dual vents with flame arresters, adjustable leveling feet, and grounding connector



Complies with OSHA and provides 10 minutes of evacuation time.



Capacity Gal/L	Doors and Style	H x W x D	Shelves	Approv/Lstg Regulation	Model	CA Prop 65
30/114	2 door, manual	44 x 43 x 18 in	1	FM, N, O, A	893000	
	2 door, self-close	1118 x 1092 x 457 mm		FM, N, O, A, I	893020	⚠
45/170	2 door, manual	65 x 43 x 18 in	2	FM, N, O, A	894500	
	2 door, self-close	1651 x 1092 x 457 mm		FM, N, O, A, I	894520	⚠
60/227	2 door, manual	65 x 34 x 34 in		FM, N, O, A	896000	
	2 door, self-close	1651 x 864 x 864 mm		FM, N, O, A, I	896020	⚠
90/341*	2 door, manual	65 x 43 x 34 in	FM, N, O, A	899000		
	2 door, self-close	1651 x 1092 x 864 mm	FM, N, O, A, I	899020	⚠	

*OSHA 29CFR 1910.106(d)(3) states that not more than 60 gallons (227 L) of Category 1, 2, or 3 flammable liquids, nor more than 120 gallons (454 L) of Category 4 flammable liquids may be stored in a safety cabinet.

Accessories	Fits Cabinet Styles	W x D	Model
SpillsSlope® steel shelf	30 & 45 gallon (114 & 170 L) - 43 in W (1092 mm)	39.375 x 14 in (1000 x 356 mm)	29937
	30 gallon (114 L) - 36 in W (914 mm)	32.375 x 20 in (822 x 508 mm)	29942
	60 gallon (227 L) - 34 in W (864 mm)	30.375 x 29 in (771 x 737 mm)	29944
	90 gallon (341 L) - 43 in W (1092 mm)	39.375 x 29 in (1000 x 737 mm)	29945

⚠ WARNING: This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.