

## GENERAL PURPOSE

- Magnetic insert firmly holds the fastener in the socket for easy installation/removal
- Prevents fasteners from dropping into restricted areas where they can be difficult to locate and/or retrieve
- Magnetic insert can be left in or removed for use in other sockets

### 520 9 PC. MAGNETIC SOCKET INSERTS (SAE)



- Includes nine pieces: 3/8", 7/16", 1/2", 9/16", 5/8", 11/16", 3/4", 13/16", and 7/8"

### 850 UNIVERSAL SEAL PULLER KIT



- Pin creates a pivot point on the surface of the seal, thus distributing the force evenly over a larger surface area (when compared to competitive puller designs)
- Greater surface area on hook helps prevent seal puller from piercing through the seal
- Works with 3/8" square drive ratchet or braker bar

### 521 10 PC. MAGNETIC SOCKET INSERTS (METRIC)



- Includes nine pieces: 10, 11, 12, 13, 14, 15, 16, 17, 18 and 19mm

### 852 2-PIECE PRYBAR HEAD SET



- Teeth allow for a better grip and approximately 70% less movement on the prying surface
- 3/8" and 1/2" square drive connections provide various orientations in limited access locations

### 522 19 PC. MAGNETIC SOCKET INSERTS (SAE & METRIC)



- Includes nineteen pieces: SAE and Metric sets combined

### 950 11 PC. GASKET HOLE PUNCH SET



- Designed to cut holes and internal radii in gaskets and other soft material (i.e., rubber, lead foil, linoleum, felt fiber)
- Contains long driving mandrel
- Ten punch sizes: 1/4", 5/16", 3/8", 7/16", 1/2", 9/16", 5/8", 3/4", 7/8", 1"

## PULLEY

Removes and installs power steering pump pulleys on most major domestic vehicle platforms including early GM, Chrysler, Ford and GM belt-driven vacuum pumps and pressed-on water pump pulleys on GM 4 and 6 cylinders

### 5238 MASTER POWER STEERING PULLEY REMOVER AND INSTALLER SET



### 5239A (CLAMSHELL) 5239B (CASE) POWER STEERING PUMP/ALTERNATOR PULLEY REMOVER/INSTALLER



## SERRATED BIT WRENCHES

- Use to install and remove 12-point (triple-square) metric socket-head screws
- Turn with a socket or wrench

Part No.	12-POINT				DRIVE	
	6MM	8MM	10MM	12MM	5/16"	1/2"
676-6	•				•	
676-8		•			•	
676-10			•			•
676-12				•		•



## MISCELLANEOUS

### 413 FORD SEATBELT PRETENTIONER RELEASE TOOL



- Allows for the disconnection of Ford Interceptor, Taurus & Lincoln MKS seat belt pretensioner system
- Simplifies disconnection of seatbelt release mechanism

### 436A EXHAUST HANGER REMOVAL PLIERS



- For removal of rubber exhaust system hangers, (i.e. tailpipe, exhaust pipe and muffler)
- Self-locating forcing pin
- Cushioned slip-resistant handles at a 25° offset for easy access in restricted areas

### 504 GLOW PLUG HARNESS TOOL




- Prevents damage to harness and connector rail
- Removes and installs glow plug connectors
- Applications Include 2004 and newer
  - 6.0 Liter Diesel
  - E-series
  - Low Cab Forward
  - F250-F350 Super Duty

### 525 TILT STEERING PIVOT PIN REMOVER



- Removes pivot pins from Chrysler, Ford, and GM steering columns
- Fits all telescoping steering columns (1969 to present)

### 538 FORD FUEL FILTER CAP TOOL



- 36mm hex, combined with 6 notches allows this tool to do the work of two
- Blue anodized aluminum
- 3/8" drive

### 548 MAXXFORCE FUEL LINE RELEASE TOOL



- Fuel line disconnect for International MaxxForce series 11 & 13 engines
- Heat treated to minimize fork deflection

### 563 FORD 1/2" FUEL LINE & VAPOR REMOVAL CONNECTION TOOL



- Removal of Ford type 1&2 quick release connectors
- Removal of Super Duty truck Fuel supply line quick connectors
- Found on majority of 2005 to current Ford Motor Co. vehicles

### 568 FORD 3/8" FUEL LINE & VAPOR REMOVAL CONNECTION TOOL



- Removal of Ford type 1&2 quick release connectors
- Removal of passenger car and light truck 5/16" & 3/8" Fuel supply & Vapor line quick connectors
- Found on majority of 2005 to current Ford Motor Co. vehicles

### 635A UNIVERSAL OIL FILTER WRENCH



- Designed to fit oil filters for all domestic and foreign compact, mid- and standard sized automobiles
- Self-adjusting wrench will fit all filters 2-1/2" through 3-13/16" in diameter
- Works with a 3/8" square drive socket wrench

### 708 CAMSHAFT SPROCKET HOLDING TOOL



- Pivoting design allows fit in most cam and injection pump gear sizes
- Dented grooves on holding pins gives user a sure hold
- Use as a counter holder when loosening or tightening sprocket retainer bolts

### 3509 STEEL WHEEL LOCK-PLATE REMOVER/INSTALLER



- Features puller yoke to fit late model GM cars with (S.I.R.) air bags
- Narrow yoke prevents damage to the lock plate
- Hex screw supplied will lock down telescoping steering columns while removing lock plate
- Zinc and black oxide for corrosion resistance