

Retractable Air Hose Reels with Levelwind™ Technology



Featuring Levelwind™ – Flexzilla’s unique winding system that automatically layers hose back and forth across the reel ensuring that the hose is coiled smoothly, easily...every time – and includes Flexzilla® air hose and lead-in hose.



L8305FZ

FEATURES:

- **Latching Mode Switch** - Choose from latching hose every 3 ft. for extended use or switch to free run for immediate automatic rewinding
- **Seven Position Locking Bracket** - These reels can swivel freely on a mounting bracket up to 135° or can be locked into place using the locking brace. Up to seven different locking angles can be utilized (L8300-W)
- **Adjustable Hose Stopper** - Increase or decrease the length of the hose that remains when hose is fully retracted
- **Extra Large Swivel** - A 3/4 in. swivel reduces flow restrictions and allows for maximum flow
- **Free Standing Base** - Portable - Use freestanding or mounted on wall or ceiling. Flat base allows reel to rest on the ground
- **Built-In Handle** - For carrying ease
- **Durable Construction** - Made from durable UV stabilized polypropylene
- **Hose Material** - Flexible Hybrid Polymer
- **Lead-in Hose Included** - 5 ft.

ASSEMBLED IN USA
of US and global components

Retractable Air Hose Reels with Levelwind™ Technology

| Part No. | Hose I.D. | Hose Length | Working Pressure @ 70°F | Temperature Range (F°) | Lead-in Hose Connection | Reel Inlet | Hose Outlet | Weight | Retail Packaging | Assembled in USA |
|----------|-----------|-------------|-------------------------|------------------------|-----------------------------------|--------------------------|--------------|---------|------------------|------------------|
| L8305FZ | 3/8 in. | 50 ft. | 300 psi | -40° to 140° | 3/4 in. Female GHT x 1/4 in. MNPT | 3/4 in. – 1 1/2 Male GHT | 1/4 in. MNPT | 25 lbs. | ● | ● |
| L8306FZ | 3/8 in. | 75 ft. | 300 psi | -40° to 140° | 3/4 in. Female GHT x 1/4 in. MNPT | 3/4 in. – 1 1/2 Male GHT | 1/4 in. MNPT | 30 lbs. | ● | ● |
| L8335FZ | 1/2 in. | 50 ft. | 300 psi | -40° to 140° | 3/4 in. Female GHT x 3/8 in. MNPT | 3/4 in. – 1 1/2 Male GHT | 3/8 in. MNPT | 29 lbs. | ● | ● |

Mounting Brackets



L8300-W



L8300-B

L8300-W FEATURES:

- Includes a seven position locking bracket
- Reel can swivel freely on mounting bracket up to 135° or can be locked into place using the locking brace
- Mounting options: wall or overhead ceiling

L8300-B FEATURES:

- Includes a seven position locking bracket
- Reel can swivel freely on mounting bracket up to 360° or can be locked into place using the locking brace
- Mounting options: high wall or bench