

# Grease couplers

## Hydraulic couplers – standard

- 6 000 psi (408 bar) maximum operating pressure.
- For all hydraulic type grease fittings.
- Small outside diameter permits easy contact with recessed fittings.
- Built-in ball check prevents leak and lubricant backup.
- Inlet 1/8 in. NPT (f).
- Bulk model 245978

## Hydraulic coupler displays

### Model 5852

- One hydraulic coupler in a resealable clamshell.
- 3-jaw design

### Model 5852-2

- Two hydraulic couplers in the same clamshell as model 5852.

### Model 5852-5

- Contains five couplers; reduces cost per unit.

### Model 5852-54 counter display

- Contains 54 couplers in a displayable box; best value.

### Model 5845 heavy-duty

- 7 500 psi (517 bar) maximum operating pressure.
- 1 1/16 in. hex
- Inlet 1/8 in. NPT (f)
- Bulk model 245976

### Model 5848 adapter

- 7 500 psi (517 bar) maximum operating pressure.
- Built-in swivel allows full 360° circle.
- Locks in any one of eight 45° positions.
- Adjustable coupler section permits contact with fittings in reverse positions.
- Angle body has 1/8 in. NPT (f) inlet permits addition of pipe extension when required.

### Model G300 standard grease coupler

For use with most hand-operated grease guns and equipment. 1/8 in. NPT 4-jaw design.

## Special access grease couplers

### Model 5883 90° grease coupler

- Provides access to difficult to reach fittings.
- Allows for easy lubrication in tight areas.

## Button-head couplers and adapters

### Model 80933

4 000 psi (276 bar) maximum operating pressure. For pull-on, push-on or hook-on service. Use with large 7/8 in. (22 mm) diameter button-head fittings. 7/16 in.-27 (f) thread.

### Model 81458

Same as model 80933 except for 5/8 in. (16 mm) diameter button-head fittings.

### Model 10460

5 000 psi (345 bar) maximum operating pressure. For adapting standard or large button-head couplers to hose with 1/8 in. NPT connections. 1/8 in. NPT (f) x 7/16 in.-27 (m) thread. Use gasket model 31138, not included.


### Model 10536

4 500 psi (310 bar) maximum operating pressure. For adapting standard or large button-head couplers to hose with 3/8 in. NPT connections. 3/8 in. NPT (f) x 7/16 in.-27 (m) thread. Use gasket model 31138, not included.



Hydraulic coupler displays

Model 5852



Model 5845



Model 5848



Model G300



Model 5883



Model 81458



Model 10536

