

# Portable Mancooler® - 115V

## Belt Drive Models



### 2 Year Warranty - Engineered for Superior Performance

#### FEATURES ON ALL BELT DRIVE MANCOOLERS®

- Guards & Barrel Are Epoxy Coated

#### MC42OS

- 115V, 1 Phase, 2 Speed, ODP, 1 HP Motor
- Epoxy Coated Steel Spiral, Vibration Isolated Mounted Guards
- 20 Gauge Roll Form, Epoxy Coated Housing
- Steel Hubbed Wheels with Locking Casters
- Compliant with OSHA Requirements
- SJT 10' Cord with Three Prong Plug
- Full Width Handle with Cord Wrap
- Four Bladed Aluminum Propeller
- Quiet - Db: High 75, Low 67
- Motor Out of Air Stream
- 2 Speed Rocker Switch
- Fully Assembled



EDP No.	Catalog No.	Prop Dia.	Fan Style	HP	Cabinet Size	CFM		RPM		Ship Wt.
						High	Low	High	Low	
60002	MC42OS	42"	Portable	1	46"	17100	9558	430	285	130



### 2 Year Warranty

#### EMC42D

- 115V, ½ HP, 2 Speed, 1 Phase, ODP, Ball Bearing Motor, Rocker Switch
- Epoxy Coated Steel Spiral, Resilient Mounted Guards
- 20 Gauge Roll Form Epoxy Coated Housing
- 10' Three Conductor SJT Type Cord
- Compliant with OSHA Requirements
- 45" Diameter Barrel with 15" Width
- Full Width Easy Grip Handle
- Aluminum 3 Blade Prop
- Fully Assembled
- 8" Steel Wheels



EDP No.	Catalog No.	Prop Dia.	Fan Style	HP	Cabinet Size	CFM		RPM		Ship Wt.
						High	Low	High	Low	
60007	EMC42D	42"	Portable	½	46"	14000	8000	540	400	120
05242	Blade Ass'y - EMC42D	42"	Replacement Propeller	---	---	---	---	---	---	7



### 2 Year Warranty

#### MC42 / MC48 Swivel Mounts

- 115V, 1 Phase, 1 Speed, ODP, ¾ HP (42") & 1 PH (48") Motor
- 12' Three Conductor SJT Type Cord and Switch
- Four Bladed Epoxy Coated Steel Propeller
- 4" Steel Wheels with Rubber Tires
- Pull Handle with Cord Wrap
- Tilttable 30°, Locks in Place



EDP No.	Catalog No.	Prop Dia.	HP	Cabinet Size	CFM	RPM	Ship Wt.
60025	MC42B	42"	¾ (2 Speed)	42½"	16180	380	135
60026	MC48B	48"	1 (1 Speed)	48½"	17730	385	160

