


CHARGING ADAPTERS, REPLACEMENT GASKETS, DEPRESSORS

90° ADAPTERS



		REPLACEMENT	GASKET/O-RING	DEPRESSOR
A	90333-R	Shut-off valve 1/4" MFL x 1/4" FFL	90336	-
B	90314*	1/4" MFL x 1/4" FFL	42010	42014
B	90340*	1/4" MFL x 1/8" FFL (high side) Ford 1977-1980	90341	90368
B	90354*	1/4" MFL x 3/16" FFL (high side) GM 1976 & later	90369	90368

45° ADAPTERS




C	90924	1/4" MFL x 1/4" FFL	42010	42014
C	90927*	1/4" MFL x 3/16" FFL (high-side)	90369	90368

STRAIGHT ADAPTERS



D	82272*	R134a 1/2" ACME-F x 13 mm R134a (low side)	85511	-
E	82335	R134a shut-off valve 1/2" ACME-M x 1/2" ACME-F	90336	-
E	90335-R	Shut-off valve 1/4" MFL x 1/4" FFL	90336	-
E	90337	Shut-off valve 1/4" MFL x 3/16" FFL	90331	-
F	82634*	1/4" FFL x 1/2" ACME-M	90331	-
F	82634-M	1/4" FFL x 1/2" ACME-M without valve core	90331	-
G	82734	14 mm-M x 1/4" MFL	83341	-
H	90358*	1/4" MFL x 3/16" FFL (high side)	42010	42014
I	90274	1/4" MFL x 1/4" FFL swivel	42010	42014
I	90332**	1/4" MFL x 1/4" FFL anti-blowback fitting	42010	42014
I	90357	1/4" MFL x 3/16" FFL (high side) swivel	90369	90368
I	91084*	1/4" MFL x 3/16" FFL (high side) swivel adapter GM 1976 & Later, Ford 1981 & later	90369	90368
J	90338*	GM 1991 & later service adapter	90339	-
K	90637	3/4" NPSF x 1/4" MFL refrigeration tank adapter	90638	-
L	90633	1/4" MFL x 1/4" MFL union	-	-
L	82633	1/2" ACME-M x 1/2" ACME-M union	-	-
M	83634-M	1/4 FL-F x 1/2 ACME LH-M fitting for R1234yf systems without check valve	90331	-

FLEX ADAPTERS



N	90355*	1/4" MFL x 3/16" FFL (high side) GM 1976 & later, Ford 1981 & later	90369	90368
N	90356*	1/4" MFL x 1/4" FFL	42010	42014
N	90373*	1/4" MFL x 1/8" FFL (high side) Ford 1977-1980	90341	90368
O	90410	Convert 1/4 SAE hose into 5/16 SAE, swivel connection	82010	-

ACCESS SERVICE TOOLS



P	90296*	1/4" MFL x 1/8" NPT	-	-
P	80296*	1/2" ACME-M x 1/8" NPT	-	-

* Includes access valve core (0377-001) – (90-110 PSI opening) / ** Includes check valve core (0332-002) – (8-12 PSI opening)