

COMPONENTS and ACCESSORIES

Compressed Air Regulators Diaphragm

Model No.	Description	Pipe Size	Nominal Air Flow	Maximum Pressure	Temperature Range	Outlet Range
RG-4049	Mini Reg	1/4 NPT	25 CFM	250 PSI	40-120 F	2-125 PSI
RG-4520	Regulator	1/2 NPT	100 CFM	300 PSI	40-120 F	2-125 PSI
M-200	Controller	1/2 NPT	215 CFM	300 PSI	40-120 F	2-125 PSI
M-830	S.A.M.S.	3/4 NPT	250 CFM	300 PSI	40-120 F	2-125 PSI
MHT-7300	High-Tech Regulator	1/2 NPT	30 CFM	125 PSI	40-120 F	2-125 PSI



Compressed Air Tank Drains

Model No.	Pipe Size	Drain Time	Cycle Time	Maximum Pressure	Temperature Range	Electrical
RF-2011	1/4 NPT	1-30 Sec.	1-60 Min.	200 PSI	35-165 F	115VAC

Model No.	Type	Pipe Size	Maximum Pressure	Temperature Range
AD-1000	Automatic Float Drain	1/2 NPT	120 PSI	40-120 F



Air Hose

Motor Guard now offers the Magna-Flex Spray Booth Hose for high-quality refinishing. Specifically designed for HVLP spray booth applications and constructed of premium hybrid polymer with a reinforced core, the Model MF-35 hose is durable, lightweight and non-kinking. 1/4" brass full-flow (HVLP) fittings at each end allow for maximum airflow while the 35 foot length is ideal for use in the spray booth. A durable, yet flexible inner core allow the hose to lay flat while it resists breaking down under repeat use and flexing.

Model No.	Description	Hose Length	Hose Size	Nominal Air Flow	Maximum Pressure	Temperature Range
MF-35	Premium Spray Booth Hose	35'	3/8"	30 CFM	300 PSI	40-120 F



Accessories

Motor Guard D-20 Blow Gun with Filter

Model No.	Description	Pipe Size	Nominal Air Flow	Maximum Pressure	Temperature Range	Filtration Rating
D-20	Blow Gun/Filter	1/4 NPT	30 CFM	125 PSI	40-120 F	.01 Micron

Replacement Desiccant

Silica gel desiccant beads with color change indicator. Beads go from blue to pink when changing is needed. Low dust.

Model No.	Description
M-4095-Q	Quart
M-4095-Q6	Six-Pack of Quarts
M-4095-G	Gallon

