

SEAL & BEARING DRIVER SET

Now you can have the proper-size driver for nearly any automotive seal, bearing, or bushing installation job. These sets include discs and handles, spacers and drivers.

- Discs range from 1/2" to 4-1/2" in diameter, in 1/16" increments.

- 27793** Starter set. Includes a handle and discs (5/8" to 2" diameter) specially selected to provide the driver sizes usually needed in automotive service. Includes plastic storage box.
- 27794** Basic set. Includes two handle sizes and 41 discs, ranging from 1/2" to 3" diameter along with plastic storage box and insert.
- 27795** Big-job set for servicing large components. Includes a handle and 24 discs, ranging from 3-1/16" to 4-1/2" diameter.
- 27796** Intermediate set. Includes a handle and 25 discs, ranging from 2" to 3-1/2" diameter.
- 27797** Master set. Includes three handle sizes and 65 discs, ranging from 1/2" to 4-1/2" diameter.
- 27810** Tool organizer board for holding all components in No. 27797 master set.



27810




Starter Set 27793

Tool No.	Description	Tool No.	Description	Tool No.	Description
10012*	Cap Screw	27508	Disc, 1-9/16" dia.	27534	Disc, 3-3/16" dia.
10020*	Cap Screw	27509*	Disc, 1-5/8" dia.	27535	Disc, 3-1/4" dia.
10854*	Cap Screw	27510	Disc, 1-11/16" dia.	27536	Disc, 3-5/16" dia.
10855*	Cap Screw	27511*	Disc, 1-3/4" dia.	27537	Disc, 3-3/8" dia.
12001*	Cap Screw	27512	Disc, 1-13/16" dia.	27538	Disc, 3-7/16" dia.
27487*	Small Handle	27513*	Disc, 1-7/8" dia.	27539	Disc, 3-1/2" dia.
27488	Medium Handle	27514	Disc, 1-15/16" dia.	27540	Disc, 3-9/16" dia.
27489	Large Handle	27515*	Disc, 2" dia.	27541	Disc, 3-5/8" dia.
27490	Extension Tube	27516	Disc, 2-1/16" dia.	27542	Disc, 3-11/16" dia.
27491	Disc, 1/2" dia.	27517	Disc, 2-1/8" dia.	27543	Disc, 3-3/4" dia.
27492	Disc, 9/16" dia.	27518	Disc, 2-3/16" dia.	27544	Disc, 3-13/16" dia.
27493*	Disc, 5/8" dia.	27519	Disc, 2-1/4" dia.	27545	Disc, 3-7/8" dia.
27494	Disc, 11/16" dia.	27520	Disc, 2-5/16" dia.	27546	Disc, 3-15/16" dia.
27495*	Disc, 3/4" dia.	27521	Disc, 2-3/8" dia.	27547	Disc, 4" dia.
27496	Disc, 13/16" dia.	27522	Disc, 2-7/16" dia.	27548	Disc, 4-1/16" dia.
27497*	Disc, 7/8" dia.	27523	Disc, 2-1/2" dia.	27549	Disc, 4-1/8" dia.
27498	Disc, 15/16" dia.	27524	Disc, 2-9/16" dia.	27550	Disc, 4-3/16" dia.
27499*	Disc, 1" dia.	27525	Disc, 2-5/8" dia.	27551	Disc, 4-1/4" dia.
27500	Disc, 1-1/16" dia.	27526	Disc, 2-11/16" dia.	27552	Disc, 4-5/16" dia.
27501*	Disc, 1-1/8" dia.	27527	Disc, 2-3/4" dia.	27553	Disc, 4-3/8" dia.
27502	Disc, 1-3/16" dia.	27528	Disc, 2-13/16" dia.	27554	Disc, 4-7/16" dia.
27503*	Disc, 1-1/4" dia.	27529	Disc, 2-7/8" dia.	27555	Disc, 4-1/2" dia.
27504	Disc, 1-5/16" dia.	27530	Disc, 2-15/16" dia.	7350*	Allen Wrench
27505*	Disc, 1-3/8" dia.	27531	Disc, 3" dia.		
27506	Disc, 1-7/16" dia.	27532	Disc, 3-1/16" dia.		
27507*	Disc, 1-1/2" dia.	27533	Disc, 3-1/8" dia.		

NOTE: All discs are 1/2" thick. *Included in set No. 27793.

5550
Spectrum Solar 10W LED Work Light with UV Top Light



5550 Specifications

10W LED Work light with UV Top Light
LI-ION Rechargeable Battery – 3.6V 2250 mA, AC/DC
Charger Input AC 100 ~ 240V; 50/60Hz; DC12V ~ 24V
Power Output: 5.0V 1000 mA
Charger Time: 3.5 ~ 4.0 hours
Active Time: 2.5 hours
Storage Temperature: -4°F to 158°F; -20°C to 70°C
Operating Temperature: 23°F to 122°F; -5° to 50°C
PS: LED Sector: 170°
At 50 cm: 350 LUX (750 LM)
Waterproof Grade IP65

5551
Spectrum Trio 9W LED Work Light with 3W LED Top Light



5551 Specifications

9W LED Work light with 3W LED Top Light
LI-ION Rechargeable Battery – 3.6V 2250 mA, AC/DC
Charger Input AC 100 ~ 240V; 50/60Hz; DC12V ~ 24V
Power Output: 5.0V 1000 mA
Charger Time: 3.5 ~ 4.0 hours
Active Time: 3.0 hours
Storage Temperature: -4°F to 158°F; -20°C to 70°C
Operating Temperature: 23°F to 122°F; -5° to 50°C
PS: LED Sector: 25°
At 50 cm: 4000 LUX
Waterproof Grade IP65

5552
Spectrum 30+4 30 Pc. LED Work Light with 4 Pc. LED Top Light



5552 Specifications

30 Piece LED Work light with 4 Piece LED Top Light
LI-ION Rechargeable Battery – 3.6V 2250 mA, AC/DC
Charger Input AC 100 ~ 240V; 50/60Hz; DC12V ~ 24V
Power Output: 5.0V 1000 mA
Charger Time: 3.5 ~ 4.0 hours
Active Time: 4.0 to 5.0 hours
Storage Temperature: -4°F to 158°F; -20°C to 70°C
Operating Temperature: 23°F to 122°F; -5° to 50°C
PS: LED Sector: 15°
At 50 cm: 2250 LUX
Waterproof Grade IP65

- AC/DC Rechargeable
- Li-Ion battery
- Magnetic base
- Bright LEDs - 50,000 hour life
- Adjustable 60° angle
- Slip resistant textured body
- Impact & Waterproof Grade IP65
- Limited Lifetime Warranty

