

T. Acceptable Manufacturers and models

1. Prime manufacturers: Specifications are based on the equipment identified herein by manufacturers name and model to establish acceptable standards of quality, performance, features and construction.

Lincoln Industrial; St. Louis, MO.

PMV Series Pumps

2.6 LUBRICATION TOOLS

A. Features and Construction for Manual Grease Guns

1. Lever Gun to be of rigid construction with metal cartridge holder wall thickness of .045".
2. Develop 8,000 psig of pressure
3. Ball check seat with grade 25 or better.
4. Cast Iron Head Construction
5. Case hardened piston to depth of .010".
6. Must have follower flip over or universal seal to accommodate either bulk filling or standard grease cartridge.

B. Acceptable manufacturers and models.

1. Prime manufacturers: Specifications are based on the equipment identified herein by manufacturers name and model to establish acceptable standards of quality, performance, features and construction.

Lincoln Industrial; St. Louis, MO.

Lincoln Models 1142, 1148, 1147, 1151, 1132, 1133, 1134, 1013, 1145, 1035, 1037

SKF Industrial Sales – Lubrication

5148 North Hanley Road, St. Louis, MO 63134
USA Tel 31 314-679-4200 Fax +1 314-679-4359
lincolnindustrial.com skf.com/lubrication