

### Low-capacity drains

Low-capacity drains are available in 8 gallon (30 liter) or 18 gallon (68 liter) models with high-density polyethylene reservoirs. They have a portable upright configuration commonly used for collecting fluids under lift-mounted vehicles. Both models include an integrated oil filter drain shelf and funnel designed to include an added raised area to act as a splashguard. Both can be used with an optional cam-lock drainage kit for use with standard cam lock diaphragm pump systems.

## Model 3518 18 gallon (68 liter) low-capacity drain

Complete drain kit including 18 gallon (68 liter) polythylene reservoir, drain bowl, drain spigot and a standard bung port and is adjustable from 40 to 77 in. (101 to 195 cm).

# Model 3508 8 gallon (30 liter) low-capacity drain

Complete drain kit including 8 gallon (30 liter) polythylene reservoir, drain bowl and is adjustable from 36 to 65 in. (91 to 165 cm).

#### **Features**

- Available in two sizes
- Durable, polyethylene reservoir construction
- Splashguard to catch overspray
- Integrated oil filter drain shelf
- Multiple reservoir evacuation options
- Long-lasting casters for ease of movement



### Low-capacity drain technical data

| Model                           | 3518                                     | 3508                                     |
|---------------------------------|--|--|
| Capacity                        | 18 gal. (6 <i>8 liter)</i>               | 8 gal. ( <i>30 liter</i> )               |
| Bowl diameter                   | 17.5 in. (444.5 <i>mm</i> )              | 17.5 in. (444.5 mm)                      |
| Reservoir included              | Yes                                      | Yes                                      |
| Wheels (qty. 4) – swivel caster | 2.5 in. (63.5 mm)                        | 2.5 in. (63.5 mm)                        |
| Minimum height                  | 40 in. (1 016 mm)                        | 36 in. (914 mm)                          |
| Maximum height                  | 77 in. (1 956 mm)                        | 65 in. (1 651 mm)                        |
| Size tank                       | 16 × 15 × 22 in.<br>(406 × 381 × 559 mm) | 13 × 14 × 16 in.<br>(330 × 356 × 406 mm) |





#### Optional accessories

| Model                      | Name   | Description  | Compatible models                      |
|----------------------------|--|--|--|
| 820036<br>820039<br>820015 | Tool caddy<br>Cam lock drain kit<br>Drain pan                                      | Optional, sold separately<br>Optional, sold separately<br>Optional, sold separately. | 3608, 3618<br>3608, 3618<br>3608, 3618 |
| 820016<br>1340<br>G402     | 37.5 × 24.625 in.<br>(9 <i>53 × 625 mm</i> ) drain pan<br>Hand pump<br>Rotary pump | Optional, sold separately Optional, sold separately Optional, sold separately        | 3608, 3618<br>3618<br>3618             |
|                            |  |  |  |





LINCOLN 146 SKF