

PT-500 Instructions

Hand-Held Automatic Ignition Butane Powered PRO-TORCH™

Specifications:

PT-500 PRO-TORCH™	
Dimensions	H-177 mm(7.0inch) L-120 mm(4.73inch) Grip Dia-45 mm(1.78inch) Base-65 mm(2.56inch)
Weight (w / o fuel)	460 g (empty)
Fuel	Butane
Hours of nonstop Burning	200 Minutes (min. setting)
Flame Temperature	1350°C (blue flame)

Features:


- State of the art Waterproof Piezo Electronic Ignition system.
- Large Fuel Tank for 200 minutes use on each filling.
- Powerful High Output Wind-Resistant flame.
- Ergonomic designed comfortable grip
- Angled nozzle to properly direct flame
- Easily refilled with any brand of butane gas.
- Flame adjustment for the most demanding applications.

Instructions:

- A. Prior to initial use, fill torch with butane fuel as described below
- B. To fill gas tank, turn unit upside down and firmly push the butane can nozzle into the filling valve (fig. **C**).
The tank should be filled in approximately ten seconds.
Please allow a few minutes after filling for the gas to stabilize.
- C. To ignite the torch:
 1. Rotate the gas control knob Counterclockwise (left) till hear the gas flow sound.
 2. Depress the igniter button (fig. **B**) to ignite.
 3. The flame size can then be adjusted by rotating the gas control knob (fig. **A**) in either direction.
 4. The flame temperature may be adjusted by rotating the Air Control Ring.
- D. To shut off the torch, simply rotate the gas control knob fully clockwise (right).

Warning:

- Do not touch flame guard while in use or until sufficient time has passed for cooling.
- Do not immerse heated parts or items in water, allow to cool naturally.
- Use only butane gas in the torch. Do not use propane gas or any other types of fluids.
- Do not store in a temperature exceeding 40°C/ 104°F.
- Keep away from eyes at all times.
- Keep this unit out of the reach of children.
- The flame of the torch is nearly invisible in bright light or sunlight.
- Make sure that gas flow is turned off when not in use.



MADE IN TAIWAN