

THE E-FLOOD & E-SPOT SERIES ARE ABOUT  
**DELIVERING**  
**THE RIGHT LIGHT**  
**EXACTLY WHERE**  
**YOU NEED IT.**

**E-SPOT® LITEBOX®**  
**E-SPOT® FIREBOX®**

Three LEDs spotlight an area with focused bright light so you can search or inspect from a distance. Its beam has more of a hotspot than the E-Flood, providing more concentrated, brighter light. Its swivel head makes it easy to inspect high bays, ceilings, and out-of-the-way places. IPX4 rated for water-resistance. Optimized electronics provide regulated intensity. Unbreakable, scratch-resistant lens.

**E-SPOT LITEBOX / E-SPOT FIREBOX**

**BATTERY:** Zero-maintenance, sealed lead acid

**SIZE:** 11.5" x 5.1" x 7"  
 (29.2 x 13 x 17.8 cm)

**WEIGHT:** 7.9 lbs (3.58 kg)

**COLOR:** Orange, Yellow or Beige (Power Failure model only)

**E-SPOT LITEBOX**

- 45851 120V AC/12V DC, shoulder strap and mounting rack – Orange
- 45871 120V AC/12V DC, shoulder strap and mounting rack – Yellow
- 45855 Vehicle Mount System with 12V DC, shoulder strap – Orange
- 45875 Vehicle Mount System with 12V DC, shoulder strap – Yellow
- 45857 Power Failure System, shoulder strap and mounting rack – Orange
- 45867 Power Failure System, shoulder strap and mounting rack – Beige
- 45856 without Charger - with shoulder strap – Orange
- 45866 without Charger - Power Failure with shoulder strap – Beige
- 45876 without Charger - with shoulder strap – Yellow

**E-SPOT FIREBOX**

- 45861 120V AC/12V DC, dual rear LEDs, strap, mounting rack – Orange
- 45865 Vehicle Mount System w/DC, dual rear LEDs, shoulder strap – Orange
- 45882 without Charger incl. shoulder strap – dual rear LEDs – Orange

	HIGH	LOW
<b>LUMENS:</b>	540	330
<b>CANDELA:</b>	55,000	32,000
<b>DISTANCE:</b>	469m	358m
<b>RUN TIME:</b>	7h	15h

**NFPA**

Rack meets requirements of NFPA 1901-14.1.10.2 (2016) mounted in any position



Power Failure System  
 Power failure circuitry automatically illuminates the light when the power goes off.



E-Spot FireBox includes dual safety blue rear LEDs.