

## 20 TON AIR/HYDRAULIC FLOOR JACK

A standard duty truck jack for the budget conscious user who still wants the quality of a Sunex product to handle truck and trailer shop work, bus work, and roadside service calls.

- Conveniently lifts up to 20 tons with air/hydraulic powered pump
- Narrow chassis design fits easily between tandem wheels
- Hand grip can be used to store in vertical position
- 5" diameter composite wheels make maneuverability easy
- Wiper seals protect hydraulic system from contaminants
- Overload and bypass safety valves prevent the jack from being used beyond its rated capacity and ram overextension
- Integrated filter protects air motor



6623

MODEL #	CAPACITY (TONS)	LOW HEIGHT (IN.)	RAM TRAVEL (IN.)	EXT. SCREW ADJ. (IN.)	MAX. HEIGHT W/ EXT. TUBES (IN.)	OVERALL LENGTH (IN.)	OVERALL WIDTH (IN.)	WHEEL DIA. (IN.)	SADDLE DIA. (IN.)	HANDLE LENGTH (IN.)	SHIPPING WT. (LBS.)
6623	20 @ 100 PSI	8.67	3.94	2.78	23.35	17.8	8.9	5	1.75	45	53

## 22 TON AIR/HYDRAULIC JACK

Designed for heavy duty truck and trailer shop use, rail and bus work, and portable for roadside service calls.

- Narrow chassis design fits easily between tandem wheels
- Chassis base is contoured so wheels make contact with ground when jack is not under load and raises them off the ground when under load to prevent damage
- 8" diameter pneumatic wheels make maneuverability easy
- Wiper seals protect hydraulic system from contaminants
- Overload and bypass safety valves prevent the jack from being used beyond its rated capacity and ram overextension
- Self-retracting ram



6622

MODEL #	CAPACITY (TONS)	LOW HEIGHT (IN.)	RAM TRAVEL (IN.)	EXT. SCREW ADJ. (IN.)	MAX. HEIGHT W/ EXT. TUBES (IN.)	OVERALL LENGTH (IN.)	OVERALL WIDTH (IN.)	WHEEL DIA. (IN.)	SADDLE DIA. (IN.)	HANDLE LENGTH (IN.)	SHIPPING WT. (LBS.)
6622	22 @ 100 PSI	9	4.5	3.25	21	21	13	8	1.75	42.2	117