

CARTRIDGES

OV

For use with:
Certain organic vapours



G01

AG

For use with:
Chlorine, hydrogen chloride, and sulphur dioxide or chlorine dioxide or hydrogen sulphide (escape only)



G02

OV/AG

For use with:
Certain organic vapours, chlorine, hydrogen chloride, and sulphur dioxide, hydrogen sulphide (escape only) and hydrogen fluoride



G03

AM/MA

For use with:
Ammonia and methylamine



G04

FORMALDEHYDE

For use with:
Formaldehyde (and certain organic vapours)



G05

MULTI-GAS

For use with:
Certain organic vapours, chlorine, hydrogen chloride, chlorine dioxide, hydrogen sulphide (escape only), ammonia/ methylamine, formaldehyde and hydrogen fluoride



G08

OV/P100

For use with:
Same as G01 except with an attached P100 particulate filter



G71

AG/P100

For use with:
Same as G02 except with an attached P100 particulate filter



G72

OV/AG/P100

For use with:
Same as G03 except with an attached P100 particulate filter



G73

AM/MA/P100

For use with:
Same as G04 except with an attached P100 particulate filter



G74

FM/P100

For use with:
Same as G05 except with an attached P100 particulate filter



G75

MULTI-GAS/P100

For use with:
Same as G08 except with an attached P100 particulate filter



G78

Gerson Signature™ Select™ Reusable Half-Mask Respirator
9100 TPE Facepiece *Small*
9200 TPE Facepiece *Medium*
9300 TPE Facepiece *Large*



Gerson 9900 Series One-Size-Fits-All Full Face Respirator



Gerson Professional Series™ Reusable Half-Mask Respirator
9250 Silicone Facepiece *Medium*
9350 Silicone Facepiece *Large*



GERSON®
Value, Quality & Performance
508.947.4000 • www.gersonco.com

WARNING: This Applications Guide provides only general information regarding possible uses, and is not a recommendation of suitability for use in a particular environment. It is necessary to assess the work environment and the type of and concentrations of hazardous substances that may exist in the workplace in order to determine the appropriate protective equipment and the length of time that any respirator can be used within a particular environment. Some substances have OSHA-specific requirements for respiratory protection. All users of safety products must undergo thorough training, and all warnings and instructions provided with the products must be read and understood prior to use. Before use, the user must first determine that the respirator properly fits. A fit test must be performed in accordance with 29CFR 1910.134. These products do not supply Oxygen. User must maintain at least 19.5% Oxygen in the workplace. Do not use in or around sandblasting.
ProductSelectionGuide111615revA