

Scotch© High Performance Masking Tape 3434

Humid weather? Choose a tape that's up for the tack.

Working in hot and humid conditions can be tricky. Choose a high-performance tape with good solvent and water resistance properties that can be used in environments up to 110°C (230°F). Engineered as one of the highestadhesion 3M masking tapes, this smooth crepe paper tape conforms well to difficult or irregular surfaces without tearing. With all the benefits you need for the most demanding applications, this tape can take the heat – so you don't have to.



High temperature resistance up to 230°F



High adhesion in humid environments



Sticks easily with excellent holding power



Performs well with solvent and waterborne paint systems

Product Name	SKU #	Part #	Size	Rolls / Case
Scotch® High Performance Masking Tape 3434	7100037748	07895	3/4 in. x 55 yds. (18 mm x 50 m)	48
	7100037749	07897	1 in. x 55 yds. (24 mm x 50 m)	36
	7100037750	07898	1-1/2 in. x 55 yds. (36 mm x 50 m)	24
	7100037744	07899	2 in. x 55 yds. (48 mm x 50 m)	20

Automotive Aftermarket Division 3M Center Building 223-06S-07 St. Paul, MN 55144-1000 1-877-666-2277 Warranty and Limited Remedy: 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER EXPRESS OR INPLIED WARRANTIES OR CONDITIONS, INCLUDING ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. If a 3M product does not conform to this warranty, the sole and exclusive remedy is, at 3M's option, replacement or repair of the 3M product or refund of the purchase price. Limitation of Liability: Except for the limited remedy above, and except to the extent prohibited by applicable law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential, regardless of the legal or equitable theory asserted. For industrial/occupational use only. Not for consumer sale or use. For health and safety information please refer to product tables and Safety Data Sheets. 60-4405-0211-4