



Norton SuperFlexible Film is best used when:

- Denibbing (1200/1500)
- Blending
- Paint prep
- Bumper scuffing
- · Primer blocking and scuffing
- Sanding edge panels
- · Light scuffing on base coat
- · Sanding primer surfacer
- Sanding door jambs
- Paint Finishing

Can be used wet or dry!

Using dry will allow the technician to see while sanding. Wipe frequently to extend the life of the abrasive product.

Using wet will reduce loading while extending the life of the product.



Primer Sanding

- Sanding primer surfacer and e-coat surfaces (P400)
- Sanding e-coat, primer surfacer and clear coat surfaces (P600)



Blending

Sanding primer surfacer and scuffing clear coat for blends (P800)



Paint Finishing

- Sanding clear coat to remove aggressive dirt nibs and texture from the surface (P1200)
- Sanding clear coat to remove dirt nibs and texture from the surface (P1500)

Hook & Loop Cut Sheets

PART #	GRIT	COLOR	PKG/CS QTY		
6-11/16" x 5-1/8" - Perforated					
666233 90555	1500	Rose	25/100		
666233 90554	1200	Amber	25/100		
666233 90552	800	Citrine	25/100		
666233 90551	600	Turquoise	25/100		
666233 90550	400	Sapphire	25/100		

Hook & Loop Disc

PART #	GRIT	COLOR	PKG/CS QTY
6" Discs			
666233 90559	3000	Meteorite	25/100
666233 90558	2500	Aquamarine	25/100
666233 90557	2000	Jade	25/100
666233 90556	1500	Rose	25/100



OUALITY THAT PAYS™

www.facebook.com/NortonAbrasivesNA | www.youtube.com/NortonAbrasives | www.nortonabrasives.com

CUSTOMER SERVICE:

1 (800) 456-8444 1 (800) 263-6565 USA Toll Free: CAN Toll Free: 1 (888) 383-2249 Toll Free Fax:

FORM #8920 REV. 06/21

© Saint-Gobain June 2021.

Norton, "Quality that Pays", Refinish Solutions Group and "Reshaping Your World" are trademarks of Saint-Gobain Abrasives. All other trademarks are the property of their respective owners.







