

SECTION 1: Identification

1.1. Product identifier

Product form : Mixture
 Trade name : REVvive by RSG High Build Primer - Gray
 Product group : Aerosol
 Other means of identification : UPC - 66623391007

1.2. Recommended use and restrictions on use

Recommended use : For professional use only

1.3. Supplier

Canada

Saint-Gobain Canada, Inc.
 28 Albert Street, W.
 N0J 1S0 Plattsville, ON
 T 519-684-7441
www.Nortonabrasives.com

United States

Saint-Gobain Abrasives Inc
 1 New Bond Street
 01615 Worcester, MA
 T 800-551-4413
www.Nortonabrasives.com

1.4. Emergency telephone number

Emergency number : 508-795-5000. For emergencies in Canada, call CHEMTREC: 800-424-9300

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Classification (GHS-CA)

Flammable aerosol Category 1	H222
Serious eye damage/eye irritation Category 2	H319
Carcinogenicity Category 2	H351
Specific target organ toxicity (single exposure) Category 3	H336
Hazardous to the aquatic environment - Chronic Hazard Category 3	H412

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS-CA labeling

Hazard pictograms (GHS-CA) :



Signal word (GHS-CA) : Danger

Hazard statements (GHS-CA) : H222 - Extremely flammable aerosol
 H319 - Causes serious eye irritation
 H336 - May cause drowsiness or dizziness
 H351 - Suspected of causing cancer
 H412 - Harmful to aquatic life with long lasting effects

Precautionary statements (GHS-CA) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P251 - Do not pierce or burn, even after use.
 P261 - Avoid breathing fume, spray, vapors.
 P280 - Wear eye protection, protective clothing, protective gloves.
 P305 - IF IN EYES: Rinse first with plenty of water and if necessary take medical advice
 P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
 P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS-CA)

No data available

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

REVvive by RSG High Build Primer- Gray

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	%	Classification (GHS-CA)
ethyl methyl ketone	ethyl methyl ketone 2-butanone / 2-oxobutane / 3-butanone / acetone, methyl- / AI3-07540 / butan-2-one / butanone / Caswell NO 569 / ethyl methyl ketone / EXXON methylethyl ketone / FEMA N°. 2170 / ketone, ethyl methyl- / meetco / MEK (= methyl ethyl ketone) / methyl 2-propanone / methyl acetone	(CAS-No.) 78-93-3	30 - 40	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
methyl acetate	methyl acetate acetate of methyl / acetic acid methyl ester / acetic acid, methyl ester / devoton / ethyl ester of monoacetyl acid / methyl acetate / methyl acetate, anhydrous / methyl acetic ester / methyl ester acetic acid / methyl ethanoate / tereton	(CAS-No.) 79-20-9	7 - 10	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336

REVvive by RSG High Build Primer- Gray

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Name	Chemical name / Synonyms	Product identifier	%	Classification (GHS-CA)
titanium(IV) oxide	1700 WHITE / A051 / A072 / A351 / AC 1 / AC 11 / AC 5 / A-FIL CREAM / AJANTOX / AJANTOX AGP / AJANTOX GR / AJANTOX RUTILE / AN10 / ASD / ASTM D476 / ASTM D76 / atlas white titanium dioxide / AUSTIOX / AUSTIOX ADM / AUSTIOX AE / AUSTIOX AFN3 / AUSTIOX AHR / AUSTIOX ALF / AUSTIOX ALF2 / AUSTIOX APP / AUSTIOX APP2 / AUSTIOX GRANULAR / AUSTIOX RCR / AUSTIOX RCR10 / AUSTIOX RCR2 / AUSTIOX RCR3 / AUSTIOX RCR6 / AUSTIOX RCR60 / AUSTIOX RFC / AUSTIOX RFC2 / AUSTIOX RFC5 / AUSTIOX RHD / AUSTIOX RHD2 / AUSTIOX RHD3 / AUSTIOX RHD4 / AUSTIOX RHD6 / AUSTIOX RMC / AUSTIOX RSM / AUSTIOX RSM2 / AUSTIOX RSM3 / AUSTIOX RTC2 / AUSTIOX RTC30 / AUSTIOX RTC4 / AUSTIOX RTC4U / AUSTIOX RTC50 / AUSTIOX RTC90 / AUSTIOX RXL / AUSTIOX RXW / BAYER titan / BAYER titan A / BAYER titan A2 / BAYER titan AC5522 / BAYER titan AC5581 / BAYER titan AE / BAYER titan AN2 / BAYER titan AN3 / BAYER titan RCK20 / BAYER titan RCL10 / BAYER titan RCL20 / BAYER titan RD / BAYER titan RFD1 / BAYER titan RFD2 / BAYER titan RFDI / BAYER titan R-FK 21 / BAYER titan RFKD / BAYER titan RKB2 / BAYER titan RKB3 / BAYER titan RKB4 / BAYER titan RKBD / BAYER titan RPL1 / BAYER titan RU2 / BAYER titan RUF / BAYER titan T / BAYERITIAN / BAYTITAN / BETA-RUTILE / BROOKITE / C.I. 77891 / C.I. pigment white 6 / CABOT / CALCOTONE WHITE T / COSMETIC WHITE C47-5175 / COSMETIC WHITE C47-9623 / DETI-ANA / DETI-RU / E171 / ET 10 / FA50 / FA55W / FA65 / FA80 / FE150 / FE160 / FINN titan / FINN titan AG / FINN titan AN / FINN titan AP / FINN titan RD / FINN titan RD2 / FINN titan RDD / FINN titan RDDX / FINN titan RDE2 / FINN titan RDI / FINN titan RF / FINN titan RF2 / FINN titan RF2new / FINN titan RF4 / FINN titan RR / FINN titan RR2 / FINN titan RR2S / FINN titan RR3 / FINN titan RRL / FINN titan RU / FLAMENCO / FR22 / FR30 / FR31 / FR41 / FRUF84 / FUJI titan / FUJI titan TA100 / FUJI titan TA200 / FUJI titan TA210 / FUJI titan TA300 / FUJI titan TA400 / FUJI titan TA500 / FUJI titan TE / FUJI titan TP13 / FUJI titan TP2 / FUJI titan TP3 / FUJI titan TR700 / FUJI titan TR780 / FUJI titan TR840 / FURUKAWA / HOMBITAN / HOMBITAN KA / HOMBITAN LOCR / HOMBITAN LOCRK / HOMBITAN LOCRS / HOMBITAN LW / HOMBITAN LWS / HOMBITAN LWSU / HOMBITAN R101 / HOMBITAN R10106 / HOMBITAN R101D / HOMBITAN R110 / HOMBITAN R210 / HOMBITAN R301 / HOMBITAN R301D / HOMBITAN R320 / HOMBITAN R505 / HOMBITAN R506 / HOMBITAN R510 / HOMBITAN R511 / HOMBITAN R610 / HOMBITAN R610D / HOMBITAN R610K / HOMBITAN R610L / HOMBITAN R611 / HOMBITAN R611D / HOMBITAN R710 / HOMBITAN RCL22 / HOMBITAN RCL66 / HOMBITAN SA10 / HOMBITAN SR12 / HOMBITAN SR16 / HORSE HEAD / HORSE HEAD A-410 / HORSE HEAD A-420 / HORSE HEAD A430 / HORSE HEAD A430C / HORSE HEAD A430FG / HORSE HEAD	(CAS-No.) 13463-67-7	5 - 7	Carc. 2, H351
08-21-2018				3/19

REVvive by RSG High Build Primer- Gray

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Name	Chemical name / Synonyms	Product identifier	%	Classification (GHS-CA)
talc	<p>agalite / agi talc,BC / alpine talc USP,BC127 / alpine talc USP,BC141 / alpine talc USP,BC662 / asbestine / B 13 / B 13,mineral / B 9(=talc) / beaver white 200 / beaver white 325 / blueline 200,talc / C.I. 77718 / ceramitalc / ceramitalc 10-A / ceramitalc HDT / ceramitalc no 1 / chematalc 10M,Incemin AG / cimflex 606 / circron MP / CP 10-40 / CP 38-33 / crown talc w83 / crown talc Z / crystalite CRS 6002 / CT 8 (mineral) / cubic master / desertalc 57 / desertall 57 / E 3410 / emtal 500 / emtal 549 / emtal 596 / emtal 599 / EX-IT / fibrene C400 / finntalc C10 / finntalc M05 / finntalc M15 / finntalc P40 / finntalc PF / french chalk / FW-XO / grade steamic OOS / hydrated magnesium silicate / hydrous magnesium silicate / IT extra / LMR 100 / LO micron talc 1 / LO micron talc BC1621 / LO micron talc USP, BC2755 / luzenac 10MOOS / luzenac 1445 / luzenac 20MOOS / luzenac A7 / luzenac M20 / luzenac OXO / luzenac SE MICRO / luzenac steam OOS / luzenac steamic OOS / magnesium silicate (3:4) / magnesium silicate, hydrate / magnesiumsilicate, hydrous / metro / metro talc 4604 / metro talc 4608 / metro talc 4609 / micro ACE K1 / micro ACE L1 / micron white 5000A / micron white 5000P / micron white 5000S / microtalc IT extra / mistron 139 / mistron 2SC / mistron frost P / mistron RCS / mistron star / mistron super frost / mistron vapor / mistron vapor RP6 / MP 12-50 / MP 25-38 / MP 40-27 / MP 45-26 / MP50-30 U16558lc / MST / mussolinite / naintsch A-7 / naintsch A-7C / nicron / nicron 100 compact,talc / nicron 100pwr,talc / nicron JS322,talc / no 907 metro talc / non-asbestiform talc / nonfibrous talc / nyal / nyal 100 / nyal 100HR / nyal 200 / nyal 300 / nyal 300H / nyal 400 / nyal 99 / OOS / OXO / P 3 / P 3, mineral / PK-C / PK-N / polytal 4641 / polytal 4725 / purtalc USP / SCLEROSOL / secupur antibloc / secupur nucleating / sierra C-400 / sierra mistron vapor compact,talc / sierra supreme USP,talc / silica acid, magnesium salt (4:3) / silica, talc, non asbestos / silicate:talc, containing no asbestos / silverline 200,talc / snowgoose / steamic OOS / steaplast 8502 / steawhite / sterline 400 / supreme / supreme dense / supreme, talc / talc / talc (Mg3H2(SiO3)4) / talc (powder), containing no asbestos fibers / talc lubricant / talc U.S.P. / talc, (industrial) / talc, non-asbestiform and less than 1% crystalline silica / talc, not containing asbestiform fibres / talc, not contaminated with more than 1% crystalline silica,asbestos fibres or asbestiform fibres / talc, powder / talcan PK-P / talcron CP44-31 / talcum / TDMCG-95, talc / tital 10, INCEMIN AG / tital 15 / tremolitic talc / trimagnesium tetrasilicate / TY 80 / WESTMIN-EF66</p>	(CAS-No.) 14807-96-6	5 - 7	Carc. 2, H351
cyclohexane	<p>cyclohexane benzene hexahydride / benzene, hexahydro- / cyclohexane / formula No 96100 / hexahydrobenzene / hexamethylene / hexanaphthene</p>	(CAS-No.) 110-82-7	1.5 - 3	<p>Flam. Liq. 2, H225 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Acute 1, H400 Aquatic Chronic 1, H410</p>

REVvive by RSG High Build Primer- Gray

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Name	Chemical name / Synonyms	Product identifier	%	Classification (GHS-CA)
acetone	2-propanon / 2-propanone / acetone / acetone NF / acetone oil / AI3-01238 / Caswell No.004 / chevron acetone / dimethyl formaldehyde / dimethyl ketone / dimethylketal / Dimethylketon / DMK (=dimethyl ketone) / FEMA No 3326 / ketone propane / KTI acetone / methyl acetyl / pyroacetic acid / pyroacetic ether / pyroacetic spirit / STEC 4908105	(CAS-No.) 67-64-1	1 - 1.5	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336

REVvive by RSG High Build Primer- Gray

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Name	Chemical name / Synonyms	Product identifier	%	Classification (GHS-CA)
carbon black	10 B / 200303 / 3500 B / 40 B / acetylen black / acetylene black / acticarbon AC 35 / AD 200 / AD 200(carbon) / AM black / amorphous carbon / aquafine AF black E 2B / aquafine black E ZB / aro / aroflow / arogen / aromex / arotone / arovel / arrow / asahi 35 / asahi 60 / asahi 70 / asahi 80 / asahithermal / ASM(carbon) / ATG 60 / ATG 70 / atlantic / ATR 077 / austin black / austin black 325 / AX 3023 / BK 6 / BK 6(carbon black) / black FW / black pearls / black pearls 1000 / black pearls 1000A80 / black pearls 1100 / black pearls 1300 / black pearls 2000 / black pearls 700 / black pearls 800 / black pearls 880 / black pearls 900 / black pearls I / C.I. 77266 / C.I. pigment black 6 / C.I. pigment black 7 / cabot 330 / cabot 607 / calblack N 220 / cancarb / carbalac 2 / carbodis / carbodis 100 / carbodis 80 / carbolac / carbolac 1 / carbomet / CARBON BLACK / carbon black BV and V / carbon black corax N330 / carbon black EB501 / carbon black monarch 81 / carbon black pearls / carbon black pigment / carbon black, acetylene / carbon black, channel / carbon black, furnace / carbon black, lamp / carbon black, thermal / carbon, amorphous / CC 40-220 / CD-7037 / channel black / charcoal black / chesacarb / chesacarb E / chesacarb EC / chesacarb K 2 / chezasorb / CK3 / CK4 / CK4(carbon black) / clagon RBDA / collocarb / colour black FW 1 / columbia carbon / CONDUCTEX / CONDUCTEX 40-220 / CONDUCTEX 7055 / CONDUCTEX 900 / CONDUCTEX 950 / CONDUCTEX 975 / CONDUCTEX GC 40-220 / CONDUCTEX N 472 / CONDUCTEX SC / continental(=carbon black) / continex / CONTINEX N 330 / CONTINEX N 356 / corac P / corax / corax 234 / corax 3HS CSX 147 / corax A / corax L / corax L 29 / corax L 6 / corax N220 / corax N539 / corax N650 / corax N683 / corax N765 / corax P / croflex / crolac / CSX 150A / CSX 150A2 / CSX 174 / CSX 200A / CSX 99 / CSX191 / CSX230 / CSX242 / DEGUSSA black FW / DEGUSSA(=carbon black) / dermmapol black G / DG 100 / diablack 2350 / diablack 3500B / diablack 52 / diablack A / diablack E / diablack G / diablack H / diablack MA 100 / diablack MA 8 / diablack MA 8B / diablack SH / disperse black SD 9020 / dixie(=carbon black) / dixiecell / dixiedensed / dixitherm / DMG 105a durex O / durex O beads / durex(carbon black) / E carbon black / eagle germantown / EDO / EDO(carbon black) / eldic EC 8013 / ELF / ELF 78 / elfex 475 / ELF-O / elftex / elftex 115 / elftex 12 / elftex 120 / elftex 125 / elftex 150 / elftex 160 / elftex 180 / elftex 280 / elftex 285 / elftex 415 / elftex 430 / elftex 435 / elftex 460 / elftex 465 / elftex 470 / elftex 475 / elftex 480 / elftex 485 / elftex 490 / elftex 495 / elftex 5 / elftex 570 / elftex 670 / elftex 675 / elftex 8 / elftex TP / elftex-E280 / emacol NS black 4901 / EPC / EPC(carbon black) / essex / excelsior / EXP / EXP 1 / EXP 2 / EXP(carbon black) / explosion / explosion acetylene black / explosion black / F 122 / farbruss / farbruss FW 1 / farbruss S 160 / fecto / flame black / flamruss / furnace black / fural / fural 500 / furnex / furnex N 765 / FW 200 / FW 200(carbon) / G 2 / G2(carbon black) / gas black / gas-furnace black / gastex /	(CAS-No.) 1333-86-4	0.1 - 0.5	Carc. 2, H351
08-21-2018	EN (English US)			6/19

REVvive by RSG High Build Primer- Gray

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Call a poison center/doctor/physician if you feel unwell.
First-aid measures general	: IF exposed or concerned: Get medical advice/attention.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects	: May cause drowsiness or dizziness.
Symptoms/effects after eye contact	: Eye irritation.

4.3. Immediate medical attention and special treatment, if necessary

Other medical advice or treatment	: Treat symptomatically.
-----------------------------------	--------------------------

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam.
------------------------------	----------------------------------

5.2. Unsuitable extinguishing media

No additional information available

5.3. Specific hazards arising from the hazardous product

Fire hazard	: Extremely flammable aerosol.
Explosion hazard	: Pressurized container: may burst if heated.

5.4. Special protective equipment and precautions for fire-fighters

Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
--------------------------------	--

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

No additional information available

6.2. Methods and materials for containment and cleaning up

For containment	: Contain released product, pump into suitable containers. Collect spillage.
Methods for cleaning up	: Notify authorities if product enters sewers or public waters. Mechanically recover the product.
Other information	: Dispose of materials or solid residues at an authorized site.

6.3. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection"

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Use only outdoors or in a well-ventilated area. Avoid breathing vapors, spray, fume. Avoid contact with skin and eyes.
Hygiene measures	: Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	: Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F. Store in a well-ventilated place. Keep container tightly closed. Keep cool.
Storage temperature	: < 25 °C
Special rules on packaging	: Keep only in original container.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

REVvive by RSG High Build Primer- Gray

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

ethyl methyl ketone (78-93-3)		
USA - ACGIH	ACGIH TWA (ppm)	200 ppm
USA - ACGIH	ACGIH STEL (ppm)	300 ppm
USA - ACGIH	Remark (ACGIH)	URT irr; CNS & PNS impair
USA - ACGIH	Regulatory reference	ACGIH 2018
USA - OSHA	OSHA PEL (TWA) (mg/m ³)	590 mg/m ³
USA - OSHA	OSHA PEL (TWA) (ppm)	200 ppm
USA - OSHA	Regulatory reference (US-OSHA)	OSHA
Alberta	OEL STEL (ppm)	300 ppm
Alberta	OEL TWA (ppm)	200 ppm
Alberta	Notations and remarks	URT irr; CNS & PNS impair
British Columbia	OEL STEL (ppm)	300 ppm
British Columbia	OEL TWA (ppm)	200 ppm
British Columbia	Notations and remarks	URT irr; CNS & PNS impair
Manitoba	OEL STEL (ppm)	300 ppm
Manitoba	OEL TWA (ppm)	200 ppm
Manitoba	Notations and remarks	URT irr; CNS & PNS impair
New Brunswick	OEL STEL (ppm)	300 ppm
New Brunswick	OEL TWA (ppm)	200 ppm
New Brunswick	Notations and remarks	URT irr; CNS & PNS impair
New Foundland & Labrador	OEL STEL (ppm)	300 ppm
New Foundland & Labrador	OEL TWA (ppm)	200 ppm
New Foundland & Labrador	Notations and remarks	URT irr; CNS & PNS impair
Nova Scotia	OEL STEL (ppm)	300 ppm
Nova Scotia	OEL TWA (ppm)	200 ppm
Nova Scotia	Notations and remarks	URT irr; CNS & PNS impair
Nunavut	OEL STEL (ppm)	300 ppm
Nunavut	OEL TWA (ppm)	200 ppm
Nunavut	Notations and remarks	URT irr; CNS & PNS impair
Northwest Territories	OEL STEL (ppm)	300 ppm
Northwest Territories	OEL TWA (ppm)	200 ppm
Northwest Territories	Notations and remarks	URT irr; CNS & PNS impair
Prince Edward Island	OEL STEL (ppm)	300 ppm
Prince Edward Island	OEL TWA (ppm)	200 ppm
Prince Edward Island	Notations and remarks	URT irr; CNS & PNS impair
Saskatchewan	OEL STEL (ppm)	300 ppm
Saskatchewan	OEL TWA (ppm)	200 ppm
titanium(IV) oxide (13463-67-7)		
USA - ACGIH	ACGIH TWA (mg/m ³)	10 mg/m ³
USA - ACGIH	Remark (ACGIH)	LRT irr; A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans: The agent is carcinogenic in experimental animals at a relatively high dose, by route(s) of administration, at site(s), of histologic type(s), or by mechanism(s) that may not be relevant to worker exposure. Available epidemiologic studies do not confirm an increased risk of cancer in exposed humans. Available evidence does not suggest that the agent is likely to cause cancer in humans except under uncommon or unlikely routes or levels of exposure)
USA - ACGIH	Regulatory reference	ACGIH 2018
USA - OSHA	OSHA PEL (TWA) (mg/m ³)	15 mg/m ³

REVvive by RSG High Build Primer- Gray

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

titanium(IV) oxide (13463-67-7)		
USA - OSHA	Regulatory reference (US-OSHA)	OSHA
Alberta	OEL TWA (mg/m ³)	10 mg/m ³
Alberta	Notations and remarks	LRT irr
British Columbia	OEL TWA (mg/m ³)	10 mg/m ³
British Columbia	Notations and remarks	LRT irr
Manitoba	OEL TWA (mg/m ³)	10 mg/m ³
Manitoba	Notations and remarks	LRT irr
New Brunswick	OEL TWA (mg/m ³)	10 mg/m ³
New Brunswick	Notations and remarks	LRT irr
New Foundland & Labrador	OEL TWA (mg/m ³)	10 mg/m ³
New Foundland & Labrador	Notations and remarks	LRT irr
Nova Scotia	OEL TWA (mg/m ³)	10 mg/m ³
Nova Scotia	Notations and remarks	LRT irr
Nunavut	OEL TWA (mg/m ³)	10 mg/m ³
Nunavut	Notations and remarks	LRT irr
Northwest Territories	OEL TWA (mg/m ³)	10 mg/m ³
Northwest Territories	Notations and remarks	LRT irr
Prince Edward Island	OEL TWA (mg/m ³)	10 mg/m ³
Prince Edward Island	Notations and remarks	LRT irr
Saskatchewan	OEL STEL (mg/m ³)	20 mg/m ³
Saskatchewan	OEL TWA (mg/m ³)	10 mg/m ³
carbon black (1333-86-4)		
USA - ACGIH	ACGIH TWA (mg/m ³)	3 mg/m ³ (Inhalable fraction)
USA - ACGIH	Remark (ACGIH)	Bronchitis
USA - ACGIH	Regulatory reference	ACGIH 2018
USA - OSHA	OSHA PEL (TWA) (mg/m ³)	3.5 mg/m ³
USA - OSHA	Regulatory reference (US-OSHA)	OSHA
Alberta	OEL TWA (mg/m ³)	3 mg/m ³
Alberta	Notations and remarks	Bronchitis
British Columbia	OEL TWA (mg/m ³)	3 mg/m ³
British Columbia	Notations and remarks	Bronchitis
Manitoba	OEL TWA (mg/m ³)	3 mg/m ³
Manitoba	Notations and remarks	Bronchitis
New Brunswick	OEL TWA (mg/m ³)	3 mg/m ³
New Brunswick	Notations and remarks	Bronchitis
New Foundland & Labrador	OEL TWA (mg/m ³)	3 mg/m ³
New Foundland & Labrador	Notations and remarks	Bronchitis
Nova Scotia	OEL TWA (mg/m ³)	3 mg/m ³
Nova Scotia	Notations and remarks	Bronchitis
Nunavut	OEL TWA (mg/m ³)	3 mg/m ³
Nunavut	Notations and remarks	Bronchitis
Northwest Territories	OEL TWA (mg/m ³)	3 mg/m ³
Northwest Territories	Notations and remarks	Bronchitis
Prince Edward Island	OEL TWA (mg/m ³)	3 mg/m ³
Prince Edward Island	Notations and remarks	Bronchitis
Saskatchewan	OEL STEL (mg/m ³)	7 mg/m ³
Saskatchewan	OEL TWA (mg/m ³)	3.5 mg/m ³

REVvive by RSG High Build Primer- Gray

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

talc (14807-96-6)		
USA - ACGIH	ACGIH TWA (mg/m ³)	2 mg/m ³ (Respirable fraction. The value is for particulate matter containing no asbestos and < 1% crystalline silica) 0.1 fibers/cm ³ (Respirable fibers: length > 5 µm; aspect ratio ≥ 3:1, as determined by the membrane filter method at 400-450X magnification (4-mm objective), using phase-contrast illumination)
USA - ACGIH	Regulatory reference	ACGIH 2018
USA - OSHA	OSHA PEL (TWA) (ppm)	20 mppcf
USA - OSHA	Remark (OSHA)	Table Z-3. CAS No. source: eCFR Table Z-1.
USA - OSHA	Regulatory reference (US-OSHA)	OSHA Annotated Table Z-3 Mineral Dusts
Alberta	OEL TWA (mg/m ³)	2 mg/m ³
British Columbia	OEL TWA (mg/m ³)	2 mg/m ³
Manitoba	OEL TWA (mg/m ³)	2 mg/m ³
New Brunswick	OEL TWA (mg/m ³)	2 mg/m ³
New Foundland & Labrador	OEL TWA (mg/m ³)	2 mg/m ³
Nova Scotia	OEL TWA (mg/m ³)	2 mg/m ³
Nunavut	OEL TWA (mg/m ³)	2 mg/m ³
Northwest Territories	OEL TWA (mg/m ³)	2 mg/m ³
Prince Edward Island	OEL TWA (mg/m ³)	2 mg/m ³
Saskatchewan	OEL TWA (mg/m ³)	2 mg/m ³
acetone (67-64-1)		
USA - ACGIH	ACGIH TWA (ppm)	250 ppm
USA - ACGIH	ACGIH STEL (ppm)	500 ppm
USA - ACGIH	Remark (ACGIH)	eye irr; CNS impair; BEI
USA - ACGIH	Regulatory reference	ACGIH 2018
USA - OSHA	OSHA PEL (TWA) (mg/m ³)	2400 mg/m ³
USA - OSHA	OSHA PEL (TWA) (ppm)	1000 ppm
USA - OSHA	Regulatory reference (US-OSHA)	OSHA
Alberta	OEL STEL (ppm)	500 ppm
Alberta	OEL TWA (ppm)	250 ppm
Alberta	Notations and remarks	eye irr; CNS impair; BEI
British Columbia	OEL STEL (ppm)	500 ppm
British Columbia	OEL TWA (ppm)	250 ppm
British Columbia	Notations and remarks	eye irr; CNS impair; BEI
Manitoba	OEL STEL (ppm)	500 ppm
Manitoba	OEL TWA (ppm)	250 ppm
Manitoba	Notations and remarks	eye irr; CNS impair; BEI
New Brunswick	OEL STEL (ppm)	500 ppm
New Brunswick	OEL TWA (ppm)	250 ppm
New Brunswick	Notations and remarks	eye irr; CNS impair; BEI
New Foundland & Labrador	OEL STEL (ppm)	500 ppm
New Foundland & Labrador	OEL TWA (ppm)	250 ppm
New Foundland & Labrador	Notations and remarks	eye irr; CNS impair; BEI
Nova Scotia	OEL STEL (ppm)	500 ppm
Nova Scotia	OEL TWA (ppm)	250 ppm
Nova Scotia	Notations and remarks	eye irr; CNS impair; BEI
Nunavut	OEL STEL (ppm)	500 ppm
Nunavut	OEL TWA (ppm)	250 ppm
Nunavut	Notations and remarks	eye irr; CNS impair; BEI

REVvive by RSG High Build Primer- Gray

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

acetone (67-64-1)		
Northwest Territories	OEL STEL (ppm)	500 ppm
Northwest Territories	OEL TWA (ppm)	250 ppm
Northwest Territories	Notations and remarks	eye irr; CNS impair; BEI
Prince Edward Island	OEL STEL (ppm)	500 ppm
Prince Edward Island	OEL TWA (ppm)	250 ppm
Prince Edward Island	Notations and remarks	eye irr; CNS impair; BEI
Saskatchewan	OEL STEL (ppm)	750 ppm
Saskatchewan	OEL TWA (ppm)	500 ppm
methyl acetate (79-20-9)		
USA - ACGIH	ACGIH TWA (ppm)	200 ppm
USA - ACGIH	ACGIH STEL (ppm)	250 ppm
USA - ACGIH	Remark (ACGIH)	eye & URT irr
USA - ACGIH	Regulatory reference	ACGIH 2018
USA - OSHA	OSHA PEL (TWA) (mg/m ³)	610 mg/m ³
USA - OSHA	OSHA PEL (TWA) (ppm)	200 ppm
USA - OSHA	Regulatory reference (US-OSHA)	OSHA
Alberta	OEL STEL (ppm)	250 ppm
Alberta	OEL TWA (ppm)	200 ppm
Alberta	Notations and remarks	eye & URT irr
British Columbia	OEL STEL (ppm)	250 ppm
British Columbia	OEL TWA (ppm)	200 ppm
British Columbia	Notations and remarks	eye & URT irr
Manitoba	OEL STEL (ppm)	250 ppm
Manitoba	OEL TWA (ppm)	200 ppm
Manitoba	Notations and remarks	eye & URT irr
New Brunswick	OEL STEL (ppm)	250 ppm
New Brunswick	OEL TWA (ppm)	200 ppm
New Brunswick	Notations and remarks	eye & URT irr
New Foundland & Labrador	OEL STEL (ppm)	250 ppm
New Foundland & Labrador	OEL TWA (ppm)	200 ppm
New Foundland & Labrador	Notations and remarks	eye & URT irr
Nova Scotia	OEL STEL (ppm)	250 ppm
Nova Scotia	OEL TWA (ppm)	200 ppm
Nova Scotia	Notations and remarks	eye & URT irr
Nunavut	OEL STEL (ppm)	250 ppm
Nunavut	OEL TWA (ppm)	200 ppm
Nunavut	Notations and remarks	eye & URT irr
Northwest Territories	OEL STEL (ppm)	250 ppm
Northwest Territories	OEL TWA (ppm)	200 ppm
Northwest Territories	Notations and remarks	eye & URT irr
Prince Edward Island	OEL STEL (ppm)	250 ppm
Prince Edward Island	OEL TWA (ppm)	200 ppm
Prince Edward Island	Notations and remarks	eye & URT irr
Saskatchewan	OEL STEL (ppm)	250 ppm
Saskatchewan	OEL TWA (ppm)	200 ppm
cyclohexane (110-82-7)		
USA - ACGIH	ACGIH TWA (ppm)	100 ppm
USA - ACGIH	Remark (ACGIH)	CNS impair

REVvive by RSG High Build Primer- Gray

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

cyclohexane (110-82-7)		
USA - ACGIH	Regulatory reference	ACGIH 2018
USA - OSHA	OSHA PEL (TWA) (mg/m ³)	1050 mg/m ³
USA - OSHA	OSHA PEL (TWA) (ppm)	300 ppm
USA - OSHA	Regulatory reference (US-OSHA)	OSHA
Saskatchewan	OEL STEL (ppm)	150 ppm
Saskatchewan	OEL TWA (ppm)	100 ppm

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Personal protective equipment:

Gloves. Protective clothing. Safety glasses.

Materials for protective clothing:

Impermeable clothing

Hand protection:

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Personal protective equipment symbol(s):



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Aerosol.
Color	: Gray
Odor	: There may be no odour warning properties, odour is subjective and inadequate to warn of overexposure. Mixture contains one or more component(s) which have the following odour: Odourless Commercial/unpurified substance: unpleasant odour Sweet odour Acetone odour Fruity odour Mild odour Ether-like odour Pleasant odour Aromatic odour Peppermint odour Petroleum-like odour Commercial/unpurified substance: irritating/pungent odour
Odor threshold	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Relative evaporation rate (ether=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Extremely flammable aerosol
Vapor pressure	: No data available
Vapor pressure at 50 °C	: No data available

REVvive by RSG High Build Primer- Gray

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Relative density	: No data available
Specific gravity / density	: 0.777 g/cm ³
Solubility	: insoluble in water. soluble in most organic solvents.
Log Pow	: No data available
Explosive properties	: Pressurized container: may burst if heated.
Explosion limits	: No data available

9.2. Other information

VOC content	: 608 g/l
MIR	: 0.95

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	: Extremely flammable aerosol. Pressurized container: may burst if heated.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reactions known under normal conditions of use.
Conditions to avoid	: Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.
Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

ethyl methyl ketone (78-93-3)	
LD50 oral rat	2193 mg/kg body weight (Equivalent or similar to OECD 423, Rat, Male/female, Read-across, Oral)
LD50 dermal rabbit	> 10 ml/kg (Equivalent or similar to OECD 402, 24 h, Rabbit, Male, Experimental value, Dermal)
ATE CA (oral)	2193 mg/kg body weight
titanium(IV) oxide (13463-67-7)	
LD50 oral rat	> 5000 mg/kg body weight (OECD 425: Acute Oral Toxicity: Up-and-Down Procedure, Rat, Female, Experimental value, Oral, 14 day(s))
LC50 inhalation rat (mg/l)	> 6.82 mg/l (Other, 4 h, Rat, Male, Experimental value, Inhalation (dust), 14 day(s))
carbon black (1333-86-4)	
LD50 oral rat	> 8000 mg/kg (Equivalent or similar to OECD 401, Rat, Male/female, Experimental value, Oral)
LD50 dermal rabbit	> 3000 mg/kg (Rabbit, Literature study, Dermal)
LC50 inhalation rat (mg/l)	> 4.6 mg/l air (4 h, Rat, Experimental value, Inhalation)
acetone (67-64-1)	
LD50 oral rat	5800 mg/kg (Equivalent or similar to OECD 401, Rat, Female, Experimental value, Oral)
LD50 dermal rabbit	20000 mg/kg (Equivalent or similar to OECD 402, Rabbit, Male, Experimental value, Dermal)
LC50 inhalation rat (mg/l)	76 mg/l (Other, 4 h, Rat, Female, Experimental value, Inhalation (vapours))
ATE CA (oral)	5800 mg/kg body weight
ATE CA (dermal)	20000 mg/kg body weight
ATE CA (vapours)	76 mg/l/4h
ATE CA (dust,mist)	76 mg/l/4h
methyl acetate (79-20-9)	
LD50 oral rat	6482 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male, Experimental value, Oral)
LD50 dermal rat	> 2000 mg/kg body weight (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male/female, Experimental value, Dermal)
ATE CA (oral)	6482 mg/kg body weight
cyclohexane (110-82-7)	
LD50 oral rat	> 5000 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male/female, Experimental value, Oral)
LD50 dermal rabbit	> 2000 mg/kg body weight (Equivalent or similar to OECD 402, Rabbit, Male/female, Experimental value, Dermal)

REVvive by RSG High Build Primer- Gray

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

cyclohexane (110-82-7)	
LC50 inhalation rat (mg/l)	> 32.88 mg/l air (Equivalent or similar to OECD 403, 4 h, Rat, Male/female, Experimental value)
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Suspected of causing cancer.
Reproductive toxicity	: Not classified

Specific target organ toxicity – single exposure : May cause drowsiness or dizziness.

ethyl methyl ketone (78-93-3)	
Specific target organ toxicity – single exposure	May cause drowsiness or dizziness.
acetone (67-64-1)	
Specific target organ toxicity – single exposure	May cause drowsiness or dizziness.
methyl acetate (79-20-9)	
Specific target organ toxicity – single exposure	May cause drowsiness or dizziness.
cyclohexane (110-82-7)	
Specific target organ toxicity – single exposure	May cause drowsiness or dizziness.

: Not classified

Specific target organ toxicity – repeated exposure

Aspiration hazard : Not classified

REVvive by RSG High Build Primer- Gray	
Vaporizer	Aerosol

Symptoms/effects : May cause drowsiness or dizziness.

Symptoms/effects after eye contact : Eye irritation.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Harmful to aquatic life with long lasting effects.

Aquatic acute : Not classified

Aquatic chronic : Harmful to aquatic life with long lasting effects.

ethyl methyl ketone (78-93-3)	
LC50 fish 1	2993 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Pimephales promelas, Static system, Fresh water, Experimental value, GLP)
EC50 Daphnia 1	308 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)
ErC50 (algae)	1972 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, GLP)
Log Pow	0.3 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 40 °C)
Log Koc	1.53 (log Koc, Calculated value)

titanium(IV) oxide (13463-67-7)	
LC50 fish 1	> 100 mg/l (Equivalent or similar to OECD 203, 96 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value, Nominal concentration)
ErC50 (algae)	61 mg/l (EPA 600/9-78-018, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Nominal concentration)

carbon black (1333-86-4)	
LC50 fish 1	> 1000 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Brachydanio rerio, Literature study)
EC50 Daphnia 1	> 5600 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 24 h, Daphnia magna, Static system, Fresh water, Experimental value)

REVvive by RSG High Build Primer- Gray

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

carbon black (1333-86-4)	
EC50 72h algae [mg/l] 1	> 10000 mg/l (OECD 201: Alga, Growth Inhibition Test, Scenedesmus subspicatus, Static system, Fresh water, Experimental value)
talca (14807-96-6)	
LC50 fish 1	> 100 g/l (24 h, Brachydanio rerio, Semi-static system)
acetone (67-64-1)	
LC50 fish 1	5540 mg/l (EU Method C.1, 96 h, Salmo gairdneri, Static system, Fresh water, Experimental value, Nominal concentration)
EC50 96h algae [mg/l] (1)	> 7000 mg/l (Selenastrum capricornutum, Static system, Fresh water, Experimental value, Nominal concentration)
BCF fish 1	0.69 (Pisces)
BCF other aquatic organisms 1	3 (BCFWIN, Calculated value)
Log Pow	-0.24 (Test data)
methyl acetate (79-20-9)	
LC50 fish 1	250 - 350 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Brachydanio rerio, Static system, Fresh water, Experimental value, GLP)
EC50 Daphnia 1	1026.7 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, GLP)
EC50 72h algae [mg/l] 1	> 120 mg/l (OECD 201: Alga, Growth Inhibition Test, Scenedesmus subspicatus, Static system, Fresh water, Experimental value, GLP)
BCF fish 1	< 1 (Pisces, Literature study)
Log Pow	0.37 (Calculated, KOWWIN, 25 °C)
Log Koc	0.18 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value, GLP)
cyclohexane (110-82-7)	
LC50 fish 1	4.53 mg/l (Equivalent or similar to OECD 203, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value, Measured concentration)
EC50 Daphnia 1	0.9 mg/l (Equivalent or similar to OECD 202, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Locomotor effect)
ErC50 (algae)	9.317 mg/l (Equivalent or similar to OECD 201, 72 h, Pseudokirchneriella subcapitata, Experimental value, GLP)
BCF fish 1	167 (Pimephales promelas, QSAR)
Log Pow	3.44 (Experimental value, Other, 25 °C)
Log Koc	2.89 (log Koc, Other, QSAR)
12.2. Persistence and degradability	
ethyl methyl ketone (78-93-3)	
Persistence and degradability	Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	2.03 g O ₂ /g substance
Chemical oxygen demand (COD)	2.31 g O ₂ /g substance
ThOD	2.44 g O ₂ /g substance
titanium(IV) oxide (13463-67-7)	
Persistence and degradability	Biodegradability: not applicable.
Biochemical oxygen demand (BOD)	Not applicable (inorganic)
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)
carbon black (1333-86-4)	
Persistence and degradability	Biodegradability in soil: not applicable. Biodegradability: not applicable.
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable
talca (14807-96-6)	
Persistence and degradability	Biodegradability: not applicable.

REVvive by RSG High Build Primer- Gray

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

talca (14807-96-6)	
Biochemical oxygen demand (BOD)	Not applicable
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable
BOD (% of ThOD)	Not applicable
acetone (67-64-1)	
Persistence and degradability	Biodegradable in the soil. Biodegradable in the soil under anaerobic conditions. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	1.43 g O ₂ /g substance
Chemical oxygen demand (COD)	1.92 g O ₂ /g substance
ThOD	2.2 g O ₂ /g substance
BOD (% of ThOD)	0.872 (20 day(s), Literature study)
methyl acetate (79-20-9)	
Persistence and degradability	Readily biodegradable in water. Inherently biodegradable.
cyclohexane (110-82-7)	
Persistence and degradability	Non degradable in the soil. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	0.22 g O ₂ /g substance
ThOD	3.425 g O ₂ /g substance
12.3. Bioaccumulative potential	
ethyl methyl ketone (78-93-3)	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
Log Pow	0.3 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 40 °C)
Log Koc	1.53 (log Koc, Calculated value)
titanium(IV) oxide (13463-67-7)	
Bioaccumulative potential	Not bioaccumulative.
carbon black (1333-86-4)	
Bioaccumulative potential	Not bioaccumulative.
acetone (67-64-1)	
Bioaccumulative potential	Not bioaccumulative.
BCF fish 1	0.69 (Pisces)
BCF other aquatic organisms 1	3 (BCFWIN, Calculated value)
Log Pow	-0.24 (Test data)
methyl acetate (79-20-9)	
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
BCF fish 1	< 1 (Pisces, Literature study)
Log Pow	0.37 (Calculated, KOWWIN, 25 °C)
Log Koc	0.18 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value, GLP)
cyclohexane (110-82-7)	
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
BCF fish 1	167 (Pimephales promelas, QSAR)
Log Pow	3.44 (Experimental value, Other, 25 °C)
Log Koc	2.89 (log Koc, Other, QSAR)
12.4. Mobility in soil	
ethyl methyl ketone (78-93-3)	
Surface tension	0.024 N/m (20 °C)
Ecology - soil	Highly mobile in soil. Slightly harmful to plants.
Log Koc	1.53 (log Koc, Calculated value)
Log Pow	0.3 (Experimental value, OECD 117: Partition Coefficient (n-octanol/water), HPLC method, 40 °C)
titanium(IV) oxide (13463-67-7)	
Ecology - soil	Low potential for mobility in soil.

REVvive by RSG High Build Primer- Gray

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

carbon black (1333-86-4)	
Ecology - soil	Adsorbs into the soil. Not toxic to plants. Not toxic to animals.
acetone (67-64-1)	
Surface tension	0.0237 N/m
Ecology - soil	No (test)data on mobility of the substance available.
Log Pow	-0.24 (Test data)
methyl acetate (79-20-9)	
Surface tension	0.024 N/m (20 °C)
Ecology - soil	Highly mobile in soil.
Log Koc	0.18 (log Koc, OECD 121: Estimation of the Adsorption Coefficient (Koc) on Soil and on Sewage Sludge using High Performance Liquid Chromatography (HPLC), Experimental value, GLP)
Log Pow	0.37 (Calculated, KOWWIN, 25 °C)
cyclohexane (110-82-7)	
Surface tension	0.025 N/m (20 °C)
Ecology - soil	Low potential for adsorption in soil.
Log Koc	2.89 (log Koc, Other, QSAR)
Log Pow	3.44 (Experimental value, Other, 25 °C)

12.5. Other adverse effects

Ozone : Not classified

SECTION 13: Disposal considerations

13.1. Disposal methods

Regional legislation (waste) : Disposal must be done according to official regulations.
Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

14.1. Basic shipping description

In accordance with TDG

Transportation of Dangerous Goods

UN-No. (TDG) : UN1950
TDG Primary Hazard Classes : 2.1 - Class 2.1 - Flammable Gas.
Transport document description : UN1950 AEROSOLS (flammable), 2.1
Proper Shipping Name (Transportation of Dangerous Goods) : AEROSOLS
flammable

Hazard labels (TDG) : 2.1 - Flammable gases



TDG Special Provisions : 80 - Despite section 1.17 of Part 1, Coming into Force, Repeal, Interpretation, General Provisions and Special Cases, a person must not offer for transport or transport these dangerous goods unless they are in a means of containment that is in compliance with section 5.11 of Part 5, Means of Containment, except that the requirement for aerosol containers to be tightly packed in a wood, fibreboard or plastic box does not apply to a user or purchaser who transports no more than six aerosol containers. For a similar rule respecting aerosol containers, see subparagraph 1.15(1)(a)(i) of Part 1, Coming into Force, Repeal, Interpretation, General Provisions and Special Cases. SOR/2012-245
107 - (1)These Regulations, except for Part 1 (Coming into Force, Repeal, Interpretation, General Provisions and Special Cases) and Part 2, (Classification), do not apply to the handling, offering for transport or transporting of UN1950, AEROSOLS, and UN2037, GAS CARTRIDGES, that contain dangerous goods included in Class 2.1 or Class 2.2 and that are transported on a road vehicle, a railway vehicle or a ship on a domestic voyage, if the aerosols or gas cartridges have a capacity less than or equal to 50 mL. (2)Subsection (1) does not apply to self-defence spray. SOR/2014-306

Explosive Limit and Limited Quantity Index : 1 L
Excepted quantities (TDG) : E0

REVvive by RSG High Build Primer- Gray

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

Passenger Carrying Road Vehicle or Passenger : 75 L
Carrying Railway Vehicle Index

14.2. Transport information/DOT

Department of Transport

DOT NA no. : UN1950
UN-No.(DOT) : 1950
Transport document description : UN1950 Aerosols (flammable, (each not exceeding 1 L capacity)), 2.1
Proper Shipping Name (DOT) : Aerosols
flammable, (each not exceeding 1 L capacity)
Contains Statement Field Selection (DOT) :
Class (DOT) : 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115
Division (DOT) : 2.1
Hazard labels (DOT) : 2.1 - Flammable gas



Dangerous for the environment : No
DOT Special Provisions (49 CFR 172.102) : N82 - See 173.306 of this subchapter for classification criteria for flammable aerosols.
DOT Packaging Exceptions (49 CFR 173.xxx) : 306
DOT Packaging Non Bulk (49 CFR 173.xxx) : None
DOT Packaging Bulk (49 CFR 173.xxx) : None
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 75 kg
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 150 kg
DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.
DOT Vessel Stowage Other : 25 - Shade from radiant heat, 87 - Stow "separated from" Class 1 (explosives) except Division 14, 126 - Segregation same as for Class 9, miscellaneous hazardous materials
Other information : No supplementary information available.

14.3. Air and sea transport

IMDG

UN-No. (IMDG) : 1950
Proper Shipping Name (IMDG) : AEROSOLS
Transport document description (IMDG) : UN 1950 AEROSOLS, 2.1
Class (IMDG) : 2 - Gases

IATA

UN-No. (IATA) : 1950
Proper Shipping Name (IATA) : Aerosols, flammable
Transport document description (IATA) : UN 1950 Aerosols, flammable, 2.1
Class (IATA) : 2

SECTION 15: Regulatory information

15.1. National regulations

ethyl methyl ketone (78-93-3)

Listed on the Canadian DSL (Domestic Substances List)

titanium(IV) oxide (13463-67-7)

Listed on the Canadian DSL (Domestic Substances List)

carbon black (1333-86-4)

Listed on the Canadian DSL (Domestic Substances List)

talc (14807-96-6)

Listed on the Canadian DSL (Domestic Substances List)

acetone (67-64-1)

Listed on the Canadian DSL (Domestic Substances List)

REVvive by RSG High Build Primer- Gray

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

methyl acetate (79-20-9)

Listed on the Canadian DSL (Domestic Substances List)

cyclohexane (110-82-7)

Listed on the Canadian DSL (Domestic Substances List)

15.2. International regulations

ethyl methyl ketone (78-93-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

titanium(IV) oxide (13463-67-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

carbon black (1333-86-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

talc (14807-96-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

acetone (67-64-1)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

methyl acetate (79-20-9)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

cyclohexane (110-82-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

SECTION 16: Other information

SDS Major/Minor : None
Date of issue : 04-17-2018
Revision date : 08-21-2018
Supersedes : 06-27-2018

Full text of H-phrases:

H222	Extremely flammable aerosol
H225	Highly flammable liquid and vapor
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness
H351	Suspected of causing cancer
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

SDS Canada

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product