

TECHNICAL DATA SHEET

www.refinishsolutionsgroup.com

PART NUMBER REVvive by RSG - Matte Trim Black

666233**91014**

PACKAGE SIZE

Aerosol, 15.2 fl. oz. / Net Wt. 11 oz.

6/case

DESCRIPTION

Restores original Matte Black appearance to body panels, under hood, chassis and wheels. Excellent pigment density, essentially single coat coverage. Apply direct to TPO, EDPM, and polypropylene without an adhesion promotor.

APPLICATION

SUBSTRATES: Can be applied to OEM-painted surfaces, lightly abraded E-Coat, TPO, EDPM, and polypropylene.

SURFACE PREPARATION: For best results, ensure the surface is thoroughly cleaned, degreased, dried and dust free. Sand primed surfaces wet or dry with 400-600 grit sandpaper, degrease and dry.

MIXING: Shake the aerosol can for at least 2 minutes before use.

COATS: 1 - 2 coats at a distance of approx. 6 - 10 inches from the surface gives a build thickness of 15 μ / 0.6 MIL.

THEORETICAL COVERAGE: 48 ft²/unit (theoretical coverage per unit assuming 100% transfer efficiency and giving the dry film thickness between indicated values.)

TECHNICAL DATA

FLASH OFF: 3 - 5 minutes between coats

DRYING TIME: Dust-free @ 68 °F: 20 - 30 minutes

VOC INFORMATION: Maximum Incremental Reactivity (MIR): 1.70 (Automotive Bumper and Trim Product)

STORAGE INFORMATION

SHELF LIFE: 2 years from manufacture subject to good storage conditions.

Aerosol cans should be stored for two hours at room temperature before use. For long term storage, keep in a dry, well-ventilated area and away from direct sunlight and frost. To maximize the lifespan of your aerosol, always invert the can and spray upside down for a few seconds after each use to clear the nozzle. If the nozzle becomes blocked, remove it from the can and soak it in gentle thinners.

RECOMMENDED STORAGE TEMPERATURE: 41 °F - 77 °F

RECOMMENDED APPLICATION TEMPERATURE: 68 °F

PRECAUTIONS

For use only by professional use only. Before use, read and follow all TDS, label and SDS precautions.



