



REVvive by RSG Coatings are ideal for restoring the original appearance in a cleaner, durable, corrosion-free solution that can be used on almost any surface.



DTM

Substrates:

Can be applied to prepared OEM-painted surfaces, Aluminum, bare steel, galvanized, SMC, fiberglass, and polyester body filler.

E-Coat

- Super durable coating provides outstanding corrosion protection
- Used as DTM primer or as a single coating to match the original OEM appearance
- Compatible with most basecoats
- Excellent adhesion over bare metal and paints and primers

PART #	SIZE	COLOR	CASE QUANTITY
666233 91015	12.6 oz	BLACK	6
666233 91016	12.7 oz	GRAY	6
666233 91017	12.8 oz	OLIVE GREEN	6
666233 91018	12.7 oz	LIGHT GREEN	6
666233 91019	12.9 oz	TAN	6
666233 91025	12.4 oz	WHITE	6
666233 91026	11.9 oz	OLIVE BROWN	6
666233 91027	11.9 oz	DARK GREEN	6
666233 91028	11.9 oz	FIELD DRAB	6
		-	



Dry Guide Coat

- Identifies surface defects when sanding fillers or primers
- Convenient aerosol application provides no waste and clean-up
- Dries instantly
- Does not clog abrasives
- Use when dry or wet sanding

PART #	SIZE	COLOR	CASE QUANTITY
666233 91008	10.9 oz	Black	6



Trim Black

- Restores trim back to original condition
- No adhesion promoter required
- Excellent coverage
- Maintains flexibility

PART #	SIZE	COLOR	CASE QUANTITY
666233 91013	10.9 oz	Satin Black	6
666233 91014	11 oz	Matte Black	6

Substrates:

Can be applied to OEM-painted surfaces, lightly abraded E-Coat, TPO, EDPM, and polypropylene.

Substrates:

Can be applied to prepared OEM-painted surfaces, fiberglass, and polyester body filler.

Rocker Panel Texture Coat

- A textured, durable coating to protect against stone chips, salt, damp and rust
- Includes two nozzles to recreate a variety of OEM textures
- Apply directly to sanded bare metal. For use on aluminum or galvanized, REVvive BY RSG Acid Etch Primer is recommended
- High Build formulation covers seams and weld areas

PART #	SIZE	COLOR	CASE QUANTITY
666233 91011	13.2 oz	GRAY	6
666233 91012	12.8 oz	BLACK	6



Substrates:

OEM-painted surfaces, SMC, fiberglass, lightly abraded E-Coat, polyester body fillers, properly prepared bumper covers, prepared metal surfaces. It is not recommended to use REVvive by RSG Rocker Panel Texture Coat on thermoplastics.

For optimal results Direct-to-Metal, apply after sanding with 180-240 grit sandpaper, 1-2 light even coats of Acid Etch Primer aerosol and allow 30 minutes drying time before applying.



Premium Rubberized Undercoating

Fast drying, paintable rubberized undercoating protects against stone chips and abrasion

- Non-sag, high rubber content coating with excellent build
- Texture matches OEM appearance
- Suited for wheel wells, trunks, lower body panels and underbodies
- Assists with sound deadening





Substrates:

Bare metal or primed steel and aluminum (coated metal)

Primers

REVvive by RSG presents a full line of Primers with exceptional adhesion and corrosion protection in an easy-to-sand, fast drying solution for all repairs.

Weld-Thru Primer

- Excellent adhesion
- High concentration of zinc or copper for greater corrosion protection
- Superior conductivity while Resistance Spot, MIG and TIG welding
- Fast drying for maximum efficiency

PART #	SIZE	COLOR	CASE QUANTIT
Zinc Weld-Thru Primer			
666233 91000	12.5 oz	Gray	6
Copper Weld Thru Primer			
666233 91001	12.5 oz	Copper	6

Substrates:

Can be applied direct to metal, galvanized steel and aluminum.

High Build Primer

- Fills uneven surfaces prior to topcoating
- Ideal for spot repairs
- Includes 2 nozzles flat fan and round for versatility in film build
- Easy to sand



Substrates:

Can be applied directly to metal, prepared OEM painted surfaces, aluminum, galvanized steel, SMC, fiberglass, lightly abraded e-Coat, polyester body fillers, GRP.

Universal Primer

 Direct adhesion to both metal and flexible plastics

WELD-T

- Fast drying and easy to sand- ideal for small rub through areas and localized repairs
- No adhesion promoter or etch primer required
- Can be top-coated with most water or solvent based paints

PART #	SIZE	COLOR	CASE QUANTITY
666233 91003	11.2 oz	Gray	6



Substrates:

Can be applied to prepared OEMpainted surfaces, Aluminum, galvanized steel, directly on to metal, SMC, Fiberglass, lightly abraded E-Coat, TPO, EDPM, polypropylene.

Acid Etch Primer

NIVERSAL PRIMER

APPRET UNIVERSEL

RIMADOR UNIVERSAL

9100

DE CUIVRE PO RE WELD-THRI

WELD-T

 One step etch and prime formula prevents corrosion and promotes paint adhesion

HIGH BUILD PRIMER

MPRIMADOR DE ALTO ESPESOR

MORET TRÈS BATISSES APPRÈT INCRUSTAL

DE TRES HAUTE QUALITE

E FORDO DE ALTAS CALBER

- For use priming bare metal surfaces
- Ideal for rub-throughs
- No sanding required- can be directly topcoated

PART #	SIZE	COLOR	CASE QUANTITY
666233 91010	12.9 oz	Gray	6



Substrates:

Can be applied to fully cured paint, Aluminum, galvanized & zinccoated steel, bare steel, polyester body fillers, GRP.



Spray Gun Paint Remover

- · Quickly dissolves cured paint residue
- Unique nozzle design creates a seal, giving a blast of cleaning solvent
- Use on waterborne or solvent-based paints

cup adapte	n all gravity-feed ers			POUR PISTOLET VAPORISATION VAPORISATION VAPORISATION VALOPITO A ROCKING		
PART #		COLOR	CASE QUANTITY	THE PISTOLA MOCHANI		
666233 91024	15 oz (Opaque	6	San Streeter		
	ostrates: ect to metal, spray e		rosol spray tips			
METP						
				_	1	
					3	46



Aerosol Selector Chart

PART #	DESCRIPTION	SIZE (OZ)	COLOR	SHAKE TIME (MINUTES)	COATS (@ 10")	FLASH TIME (MIN. BETWEEN COATS)	COVERAGE (SQ FT/UNIT)	DRY TIME (MINUTES)	SANDING (DRY/WET)	DRY BUILD (MIL)	MIR
Primers	DESCRIPTION	(UZ)	CULUN	(IVIIIVUTES)	(@ 10)	(IVIIIN. BETWEEN GUATS)	(SQ FI/UNIT)	(IVIIIVUTES)	(DRI/WEI)	(IVIIL)	IVIIN
666233 91000	Zinc Weld-Thru	12.5	Zinc	2	1-2	5-10	53.8	10-20	180-220/180-220	0.39	WTP: 1.00
666233 91001	Copper Weld-Thru	12.5	Copper	2	1-2	5-10	53.8	10-20	180-220/180-220	0.39	WTP: 1.00
666233 91003	Universal	11.2	Gray	2	1-2	3-5	48.4	15-20	400-600/600-800	0.59	ABP: 0.95
666233 91007	High Build	12	Gray	2	1-2	5-10	21.5	60	400-600/600-800	1.77	ABP: 0.95
666233 91010	Acid Etch Primer	12.9	Gray	2	1-2	3-5	48.4	10-20	400-600/600-800	0.59	ABP: 0.95
Coatings											
666233 91008	Dry Guide Coat	10.9	Black	2	1	_	_	Immediately	As Needed	_	FPP: 0.80
666233 91013	Satin Trim Black	10.9	Black	2	1-2	3-5	48.4	20-30	_	0.59	ABT: 1.70
666233 91014	Matte Trim Black	11	Black	2	1-2	3-5	48.4	20-30	_	0.59	ABT: 1.70
666233 91015	e-Coat	12.6	Black	2	1-2	10	59	20-30	_	0.60	ABP: 0.95
666233 91016	e-Coat	12.7	Gray	2	1-2	10	59	20-30	_	0.60	ABP: 0.95
666233 91017	e-Coat	12.8	Olive Green	2	1-2	10	59	20-30	_	0.60	ABP: 0.95
666233 91018	e-Coat	12.7	Light Green	2	1-2	10	59	20-30	_	0.60	ABP: 0.95
666233 91019	e-Coat	12.9	Tan	2	1-2	10	59	20-30	_	0.60	ABP: 0.95
666233 91025	e-Coat	12.4	White	2	1-2	10	59	20-30	_	0.60	ABP: 0.95
666233 91026	e-Coat	11.9	Olive Brown	2	1-2	10	59	20-30	_	0.60	ABP: 0.95
666233 91027	e-Coat	11.9	Dark Green	2	1-2	10	59	20-30	_	0.60	ABP: 0.95
666233 91028	e-Coat	11.9	Field Drab	2	1-2	10	59	20-30	_	0.60	ABP: 0.95
666233 91011	Rocker Panel Texture Coat	13.2	Gray	2	1-2	10-15	43	180-240	_	1.97	ABP: 0.95
666233 91012	Rocker Panel Texture Coat	12.8	Black	2	1-2	10-15	43	180-240	_	1.97	ABP: 0.95
666233 91029	Premium Rubberized Undercoating	17.7	Black	2	2-3	5-10	15 sq.ft.	60-120	-	1.5 to 2.0	-
Cleaners											
666233 91009	Surface Degreaser	9.9	Clear	2	1	_	_	Immediately		_	Exempt
666233 91024	Spray Gun Paint Remover	15	Opaque	1	1	_	_	Immediately		_	Exempt
Cavity Wax											
666233 91022	Cavity Wax	13.75	Amber	1	1-2 at 12"	_	60-80 sq.ft.	Immediately	_	_	0.587
666233 91023	Applicator Wand	30"	Black	_	_	_	-	_	_	_	_

Many substrates need to be properly prepared before application for proper adhesion. Please refer to the corresponding TDS before beginning any repair.

Proven Corrosion Protection

REVvive by RSG E-Coat outperforms the leading competitor in an ASTM standard salt spray test.





REVvive by RSG Cavity Wax is an OEM-approved coating for internal body panels, structural components, and new replacement parts to protect against corrosion.

Cavity Wax

OEM approved corrosion protection for cavities and inner body panels


- Excellent crevice penetration
- Dries firm to touch with a slight tack
- Convenient aerosol can eliminates the need for spray equipment

PART #	SIZE	CASE QUANTITY
666233 91022	13.75 oz	12

Cavity Wax Applicator Wand

- Flexible design makes reaching difficult areas easy
- 360° tip designed for outstanding coverage
- Reduces mess

PART #		CASE QUANTITY	
666233 91023		1	







POUR CAVITÉS

PARA CAVIDADES

Take RSG for a Test Drive

Refinish Solutions Group has complete confidence in our superior performing refinishing products that we invite you to put us to the test. It's an effortless way for you to be the judge. There's nothing to lose, but a lot to gain by participating in a RSG test Drive.

Contact us today to set up your test drive https://rsg-na.com/testdrive





















www.refinishsolutionsgroup.com | 1 (800) 456-8444 | Email: rsg@saint-gobain.com

FORM #8757 REV. 07/20

© Saint-Gobain July 2020.

Carborundum, Norton, Solar Gard, REVvive, and "Refinish Solutions Group" are trademarks of Saint-Gobain Abrasives. All other trademarks are the property of their respective owners. Vehicle image provided courtesy of Ford Motor Company.