

# STEALTH 7000B/7030B

A023\_0918

## STEALTH unit



### Features & Benefits

- Great final polishing filter and control unit
- Quick disconnect clamp ring design
- 0.01 micron at 99.99998% efficiency
- Spin-on/spin-off element
- Equipped with brass petcock manual drain
- Comes with high flow regulator/gauge
  - 1/4" On STEALTH 7000
  - 3/8" On STEALTH 7030
- 0-160 PSI gauge with glass lens
- Cleaner compressed air with no oil to your applications
- Simple design requires no tools for maintenance
- Easy service of elements
- Extremely long element life
- 99.99998% effective at oil removal

### Specifications

- Replacement Element: 3C-060
- Max. Air Pressure: 200 PSIG
- Max. Operating Temp: 125° F
- Max. Flow: 60 SCFM @ 100 PSI
- 1/2" NPT inlet,  
1/4" Outlet: 7000, 3/8": 7030
- 1/2" Ball Valve: BV-051

### Applications

- After Filter for Refrigerated Dryer
- After Filter for Desiccant Dryer
- Final Paint Air Filter and Control Unit

CA PROPOSITION 65 WARNING



**WARNING:** Cancer and Reproductive Harm  
[www.P65Warnings.ca.gov/product](http://www.P65Warnings.ca.gov/product)



(800) 521-9200



[www.driair.com](http://www.driair.com) | [www.rti-pbe.com](http://www.rti-pbe.com)



@RTiPBE



@rti\_pbe



Removes: ● ●

1.0 micron • 60 SCFM • Brass Manual Petcock Drain



1/4"

**STEALTH 6900B**  
**STEALTH 6950B**  
**STEALTH 6952B**

No Regulator  
Regulator w/ Gauge  
Regulator w/ Gauge, (2) 1/4" Outlets

3/8"

**STEALTH 3050B**  
**STEALTH 3052B**

Regulator w/ Gauge  
Regulator w/ Gauge, (2) 3/8" Outlets

Replacement Element: 6950-1

Removes: ● ● ●

1.0 micron • 60 SCFM • Brass Manual Petcock Drain



1/4"

**STEALTH 6910B**  
**STEALTH 6960B**  
**STEALTH 6962B**

No Regulator  
Regulator w/ Gauge  
Regulator w/ Gauge, (2) 1/4" Outlets

3/8"

**STEALTH 3060B**  
**STEALTH 3062B**

Regulator w/ Gauge  
Regulator w/ Gauge, (2) 3/8" Outlets

Replacement Element: 6960-1

Removes: ● ●

0.01 micron • 60 SCFM • Brass Manual Petcock Drain



1/4"

**STEALTH 7000B**  
**STEALTH 7800B**

Regulator w/ Gauge  
No Regulator

1/2"

**STEALTH 1000B**  
**STEALTH 1500B**

Regulator w/ Gauge  
Regulator w/ Gauge and manifold

3/8"

**STEALTH 7030B**

Regulator w/ Gauge

Replacement Element: 3C-060

Removes: ● ● ●

0.01 micron • 60 SCFM • 1st Stage: Automatic Float Drain  
2nd Stage: Brass Manual Petcock Drain



3/8"

**STEALTH 6060B**

Regulator w/ Gauge

1st Stage Replacement Element: 6960-1  
2nd Stage Replacement Element: 3C-060

Note: All Stealth units feature 1/2" NPT Inlet, Max Pressure: 200 PSI, Max Temp: 125°F | Removal Key: ● Water ● Dirt ● Oil

CA PROPOSITION 65 WARNING



**WARNING:** Cancer and  
Reproductive Harm  
[www.P65Warnings.ca.gov/product](http://www.P65Warnings.ca.gov/product)



(800) 521-9200



[www.driair.com](http://www.driair.com) | [www.rti-pbe.com](http://www.rti-pbe.com)



@RTiPBE



@rti\_pbe

