

EH4000-3R

The Best Dry You Can Buy!™



30

Our products are

Made in the USA.

FEATURES

- Superior Clean, Dry Air
- -40°F Dew Point
- Equipped with Auto Drain (1st Stage)
- Quick Disconnect Clamp Ring Design
- Spin-on/Spin-off Elements
- High Flow $\frac{3}{8}$ " Regulator & Gauge
- $\frac{1}{2}$ " Shut off Valve on Inlet
- True Air Stream Moisture Indicator
- High-Efficiency, Low-Cost Product

BENEFITS

- Featuring a $\frac{3}{8}$ " Outlet per Paint MFR's specs
- "Inverse Flow™" Filtration with $3\frac{1}{2}$ " Filter Depth
- Activated Carbon 1st Stage for Oil Removal
- Desiccant 2nd Stage for Dew Point Suppression
- Non-corrosive Aluminum Bowls & Zemag Heads

APPLICATIONS

- Paint Booths
- Lacquer Spraying

SPECIFICATIONS

- Replacement element:
4P-060 & DE401
- Maximum air pressure: 150 PSIG
- Maximum operating temp: 125°F
- Maximum flow to 25 SCFM



Reading Technologies, Inc.
Advanced Air System Technology™

1031F MacArthur Road Reading, PA 19605
1 800-521-9200 Fax 610 372-1984
Website <http://www.driair.com>