Version number 12 Printing date 11/15/2018 Reviewed on 11/15/2018

1 Identification

- · Product identifier
- · Trade name: MCO11-MCO14 Mix Clear
- · Article number: MCO11, MCO14
- · Application of the substance / the mixture Coating
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier: SEM Products Inc.

1685 Overview Drive Rock Hill, SC 29730

803 207 8225

· Information department:

cust\_care@semproducts.com: SEM Products,Inc. 1685 Overview Dr. Rock Hill, SC 29730: phone 1-800-831-1122, M - TH 7am - 4pm EDT

· Emergency telephone number: CHEMTREC 1-800-424-9300

### 2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer.

Repr. 2 H361 Suspected of damaging fertility or the unborn child.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms







GHS02

GHS07

GHS08

- · Signal word Danger
- · Hazard-determining components of labeling:
- 4-methylpentan-2-one
- n-butyl acetate

(Contd. on page 2)

Printing date 11/15/2018 Version number 12 Reviewed on 11/15/2018

Trade name: MCO11-MCO14 Mix Clear

(Contd. of page 1)

bis(1,2,2,6,6-Pentamethyl-4-piperidinyl) sebacate

#### · Hazard statements

H225 Highly flammable liquid and vapor.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

H361 Suspected of damaging fertility or the unborn child.

H336 May cause drowsiness or dizziness.

#### · Precautionary statements

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat/sparks/open flames/hot surfaces No smoking.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools. P242

P243 Take precautionary measures against static discharge. P261 Avoid breathing dust/fume/gas/mist/vapors/spray P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. P280

P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/

shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P312 Call a poison center/doctor if you feel unwell.

P321 Specific treatment (see on this label).

P362+P364 Take off contaminated clothing and wash it before reuse. P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

*In case of fire: Use for extinction: CO2, powder or water spray.* P370+P378 P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

#### · Classification system:

#### · NFPA ratings (scale 0 - 4)



Health = 1Fire = 3Reactivity = 0

#### · HMIS-ratings (scale 0 - 4)



- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.

(Contd. on page 3)

SEM

Printing date 11/15/2018 Version number 12 Reviewed on 11/15/2018

Trade name: MCO11-MCO14 Mix Clear

· vPvB: Not applicable.

(Contd. of page 2)

### 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description:

*Mixture: consisting of the following components.* 

Weight percentages

· Dangerous components:		
123-86-4	n-butyl acetate	30-40%
1330-20-7	xylene	13-30%
110-43-0	heptan-2-one	10-13%
108-10-1	4-methylpentan-2-one	<i>≥</i> 7-<10%
108-88-3	toluene	≥0.1-≤1%
41556-26-7	bis(1,2,2,6,6-Pentamethyl-4-piperidinyl) sebacate	≥0.1-<1%

### 4 First-aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

## 5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

### 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions: Do not allow to enter sewers/ surface or ground water.

(Contd. on page 4)

SEM

Printing date 11/15/2018 Version number 12 Reviewed on 11/15/2018

Trade name: MCO11-MCO14 Mix Clear

(Contd. of page 3)

#### · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

#### · Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

#### · Protective Action Criteria for Chemicals

<i>PAC-1</i> :		
123-86-4	n-butyl acetate	5 ppm
1330-20-7	xylene	130 ррг
110-43-0	heptan-2-one	150 ррг
108-10-1	4-methylpentan-2-one	75 ppm
108-88-3	toluene	67 ppm
<i>PAC-2:</i>		
123-86-4	n-butyl acetate	200 ppm
1330-20-7	xylene	920* pp
110-43-0	heptan-2-one	670 ppm
108-10-1	4-methylpentan-2-one	500 ppm
108-88-3	toluene	560 ppm
<i>PAC-3:</i>		•
123-86-4	n-butyl acetate	3000* pp.
1330-20-7	xylene	2500* pp
110-43-0	heptan-2-one	4000* pp
108-10-1	4-methylpentan-2-one	3000* pp.
108-88-3	toluene	3700* pp.

## 7 Handling and storage

- · Handling:
- · Precautions for safe handling

No special measures required.

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

#### · Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

(Contd. on page 5)

SEM

Printing date 11/15/2018 Version number 12 Reviewed on 11/15/2018

Trade name: MCO11-MCO14 Mix Clear

(Contd. of page 4)

Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) No further relevant information available.

## 8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

110 0,00	nts time, the remaining constituent has no known exposure timus.	
123-8	3-86-4 n-butyl acetate	
PEL	L Long-term value: 710 mg/m³, 150 ppm	
REL	L Short-term value: 950 mg/m³, 200 ppm	
	Long-term value: 710 mg/m³, 150 ppm	
TLV	Short-term value: 712 mg/m³, 150 ppm	
	Long-term value: 238 mg/m³, 50 ppm	
	30-20-7 xylene	
PEL	L Long-term value: 435 mg/m³, 100 ppm	
REL	L Short-term value: 655 mg/m³, 150 ppm	
	Long-term value: 435 mg/m³, 100 ppm	
TLV	Short-term value: 651 mg/m³, 150 ppm	
	Long-term value: 434 mg/m³, 100 ppm BEI	
110		
	)-43-0 heptan-2-one	
	Long-term value: 465 mg/m³, 100 ppm	
	Long-term value: 465 mg/m³, 100 ppm	
	V Long-term value: 233 mg/m³, 50 ppm	
108-1	3-10-1 4-methylpentan-2-one	
PEL	L Long-term value: 410 mg/m³, 100 ppm	
REL	L Short-term value: 300 mg/m³, 75 ppm	
	Long-term value: 205 mg/m³, 50 ppm	
TLV	Short-term value: 307 mg/m³, 75 ppm	
	Long-term value: 82 mg/m³, 20 ppm	
100	BEI	
	3-88-3 toluene	
PEL	L Long-term value: 200 ppm Ceiling limit value: 300; 500* ppm	
	*10-min peak per 8-hr shift	
DEI	L Short-term value: 560 mg/m³, 150 ppm	
KEL	Long-term value: 375 mg/m³, 100 ppm	
TLV	V Long-term value: 75 mg/m³, 20 ppm	
111	BEI	
		(Contd. on pag

USA

SEM

Printing date 11/15/2018 Version number 12 Reviewed on 11/15/2018

Trade name: MCO11-MCO14 Mix Clear

(Contd. of page 5)

#### · Ingredients with biological limit values:

#### 1330-20-7 xylene

BEI 1.5 g/g creatinine

Medium: urine Time: end of shift

Parameter: Methylhippuric acids

### 108-10-1 4-methylpentan-2-one

#### BEI 1 mg/L

Medium: urine Time: end of shift Parameter: MIBK

#### 108-88-3 toluene

#### BEI 0.02 mg/L

Medium: blood

Time: prior to last shift of workweek

Parameter: Toluene

0.03 mg/L
Medium: urine
Time: end of shift
Parameter: Toluene

0.3 mg/g creatinine Medium: urine Time: end of shift

Parameter: o-Cresol with hydrolysis (background)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

#### · Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

#### · Protection of hands:

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

(Contd. on page 7)

SEM

Printing date 11/15/2018 Version number 12 Reviewed on 11/15/2018

Trade name: MCO11-MCO14 Mix Clear

(Contd. of page 6)

### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

$\alpha$ $\mathbf{D}$			•	- 7			
UPM	vereal	ana	chomi	cal	nra	กกษา	os
	voucuu		chemi	cui	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		
	,						

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Liquid

*Color:* According to product specification

Odor: Characteristic
 Odor threshold: Not determined.
 pH-value: Not determined.

· Change in condition

Melting point/Melting range: Undetermined.
Boiling point/Boiling range: 114-117 °C

· Flash point: 14 °C

· Flammability (solid, gaseous): Not applicable.

• Ignition temperature: 370 °C

· Decomposition temperature: Not determined.

• Auto igniting: Product is not selfigniting.

• Danger of explosion: In use, may form flammable/explosive vapour-air mixture.

· Explosion limits:

 Lower:
 1 Vol %

 Upper:
 7.5 Vol %

· Vapor pressure at 20 °C: 10.7 hPa

Density at 20 °C: 0.92989 g/cm³
 Relative density Not determined.
 Vapor density Not determined.
 Evaporation rate Not determined.

· Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

(Contd. on page 8)

- USA

SEM

Printing date 11/15/2018 Version number 12 Reviewed on 11/15/2018

Trade name: MCO11-MCO14 Mix Clear

(Contd. of page 7) · Viscosity: Dynamic: Not determined. Kinematic: Not determined. · Solvent content: 67.6 % Organic solvents: 67.56 % **VOC** content: 628.2 g/l / 5.24 lb/gal Solids content: 32.4 % · Other information No further relevant information available.

## 10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

### 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50 values that are relevant for classification:		
1330-20	1330-20-7 xylene	
Oral	LD50	4,300 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)

- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: No irritating effect.
- · Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

· IARC (Int	ernational Agency for Research on Cancer)	
1330-20-7	xylene	3
108-10-1	4-methylpentan-2-one	2B
108-88-3	toluene	3
NTP (Nat	ional Toxicology Program)	
None of th	e ingredients is listed.	
		(Contd. on page 9

- LISA

SEM

Printing date 11/15/2018 Version number 12 Reviewed on 11/15/2018

Trade name: MCO11-MCO14 Mix Clear

(Contd. of page 8)

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

## 12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- $\cdot \textit{Bioaccumulative potential No further relevant information available}.$
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

## 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- **Recommendation:** Disposal must be made according to official regulations.

## **14 Transport information**

· UN-Number

· DOT, ADR, IMDG, IATA UN1263

· UN proper shipping name

 $\cdot$  **DOT** Pain

• ADR 1263 Paint, special provision 640D

· IMDG, IATA PAINT

- · Transport hazard class(es)
- $\cdot DOT$



· Class 3 Flammable liquids

(Contd. on page 10)

SEM

Printing date 11/15/2018 Version number 12 Reviewed on 11/15/2018

Trade name: MCO11-MCO14 Mix Clear

	(Contd. of page
· Label	3
· ADR, IMDG, IATA	
· Class	3 Flammable liquids
· Lahel	3
2000	
· Packing group · DOT, ADR, IMDG, IATA	II
	П
Environmental hazards:	N.
· Marine pollutant:	No
· Special precautions for user	Warning: Flammable liquids
· EMS Number:	<i>F-E</i> , <u><i>S-E</i></u>
· Stowage Category	В
· Transport in bulk according to Annex	II of
MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
$\cdot DOT$	
· Quantity limitations	On passenger aircraft/rail: 5 L
<b>2</b>	On cargo aircraft only: 60 L
· ADR	<u>*</u> <u>*</u>
· Excepted quantities (EQ)	Code: E2
Excepted quantities (EQ)	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
· <i>IMDG</i>	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml

## 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredient is listed.

· Section 313 (Specific toxic chemical listings):

1330-20-7 xylene

108-10-1 4-methylpentan-2-one

108-88-3 toluene

(Contd. on page 11)

USA

SEM

Printing date 11/15/2018 Version number 12

Reviewed on 11/15/2018

Trade name: MCO11-MCO14 Mix Clear

(Contd. of page 10) · TSCA (Toxic Substances Control Act): All ingredients are listed. · Proposition 65 · Chemicals known to cause cancer: 108-10-1 4-methylpentan-2-one · Chemicals known to cause reproductive toxicity for females: None of the ingredients is listed. · Chemicals known to cause reproductive toxicity for males: None of the ingredients is listed. · Chemicals known to cause developmental toxicity: 108-10-1 4-methylpentan-2-one 108-88-3 toluene · Cancerogenity categories · EPA (Environmental Protection Agency) 1330-20-7 xylene 108-10-1 4-methylpentan-2-one Ι 108-88-3 toluene II· TLV (Threshold Limit Value established by ACGIH) 1330-20-7 xylene A4108-88-3 toluene A4· NIOSH-Ca (National Institute for Occupational Safety and Health) None of the ingredients is listed.

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms







GHS02 GHS07 GHS08

- · Signal word Danger
- · Hazard-determining components of labeling:

4-methylpentan-2-one

n-butyl acetate

*bis*(1,2,2,6,6-*Pentamethyl-4-piperidinyl*) *sebacate* 

· Hazard statements

H225 Highly flammable liquid and vapor.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

H361 Suspected of damaging fertility or the unborn child.

H336 May cause drowsiness or dizziness.

· Precautionary statements

*P201 Obtain special instructions before use.* 

P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

(Contd. on page 12)

SEM

Printing date 11/15/2018 Version number 12 Reviewed on 11/15/2018

Trade name: MCO11-MCO14 Mix Clear

	(Contd. of page 11)	
P240	Ground/bond container and receiving equipment.	
P241	Use explosion-proof electrical/ventilating/lighting/equipment.	
P242	Use only non-sparking tools.	
P243	Take precautionary measures against static discharge.	
P261	Avoid breathing dust/fume/gas/mist/vapors/spray	
P264	Wash thoroughly after handling.	
P271	Use only outdoors or in a well-ventilated area.	
P272	Contaminated work clothing must not be allowed out of the workplace.	
P280	Wear protective gloves/protective clothing/eye protection/face protection.	
P303+P361+P	353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/	
	shower.	
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.	
P308+P313	IF exposed or concerned: Get medical advice/attention.	
P312	Call a poison center/doctor if you feel unwell.	
P321	Specific treatment (see on this label).	
P362+P364	Take off contaminated clothing and wash it before reuse.	
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.	
P363	Wash contaminated clothing before reuse.	
P370+P378	In case of fire: Use for extinction: CO2, powder or water spray.	
P403+P233	Store in a well-ventilated place. Keep container tightly closed.	
P403+P235	Store in a well-ventilated place. Keep cool.	
P405	Store locked up.	
P501	Dispose of contents/container in accordance with local/regional/national/international	
	regulations.	
Chemical safet	y assessment: A Chemical Safety Assessment has not been carried out.	
	· · · · · · · · · · · · · · · · · · ·	

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact: Rita Joiner (rjoiner@semproducts.com)
- Date of preparation / last revision 11/15/2018 / 11
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

(Contd. on page 13)

SEM

Printing date 11/15/2018

Version number 12

Reviewed on 11/15/2018

Trade name: MCO11-MCO14 Mix Clear

PEL: Permissible Exposure Limit
REL: Recommended Exposure Limit

BEI: Recommended Exposure Limit
BEI: Biological Exposure Limit
Flam. Liq. 2: Flammable liquids – Category 2
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Skin Sens. 1: Skin sensitisation – Category 1

Carc. 2: Carcinogenicity – Category 2 Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

\* Data compared to the previous version altered.

(Contd. of page 12)

ISA -