



SUPER BLUE DRESS WELL™ Conditioning Coating

Directions:

INTERIOR AND EXTERIOR:

- 1. Wipe on vinyl, plastic and rubber surfaces.
- 2. Allow to air dry or wipe dry with a clean cloth.

TIRES:

- 1. Apply product on sponge or applicator pad.
- 2. Wipe on tire with sponge or pad.
- 3. Allow product to thoroughly dry before moving vehicle.

NOTE: Do not apply to seat bottoms, steering wheel or foot pedals. This product can cause these surfaces to be slippery. Not recommended for engines.

Uses:

- Exterior and Interior
- Vinyl
- Conditions and Restores Vinyl Tops
- Plastic
- Rubber Surfaces

Packaging:

#20931 - 1 Gallon #20935C - 5 Gallon Cube #209355 - 55 Gallon

Specify when ordering available V.O.C. compliant formula.

For complete product specifications, review the product MSDS/SDS at wellworthproducts.com.

Storage:

Do not store in temperatures above 120°F (50°C). Avoid sparks and open flames. Keep container closed when not in use. Do not allow product to freeze.

First Aid Measures:

- EYE CONTACT: Flush eyes with cool water for at least 15 minutes or flush with a buffered eye wash solution. If irritation persists, get medical attention.
- SKIN CONTACT: Wash with soap and water. Remove clothing, wash before reuse.
- INHALATION: Remove to fresh air and insure breathing.
- INGESTION: If swallowed do not induce vomiting, seek medical attention.

ChemTrec (USA) 800-424-9300

HMIS HAZARD RATING

0-Least A-Goggles
1-Slight B-Goggles, Gloves
2-Moderate C-Goggles, Gloves
3-High Protective Wear
4-Extreme

Protection B

NOTICE TO PURCHASER: Well•Worth Products, Inc. provides no warranty of any kind with respect to the product, whether express or implied including without limitation, the implied warranty of merchantability or fitness for any intended use or purpose; shall not be liable under any circumstances for any loss, damage, liability, injury or expense directly or indirectly resulting from, arising or related to the use or application of product; shall not be liable for consequential or incidental damages or loss of profits; and its liability shall be limited to replacement of the product. ALWAYS CONSULT MSDS for further details on precautions for safe handling and use.