

OTC MEANS PULLERS

Trusted pullers with a lifetime warranty to separate rusted, frozen or seized components

GRIP-O-MATIC PULLERS



1020 2-JAW AND 1021 3-JAW 1-TON PULLERS

- 2-1/8" max reach
- 3-1/4" spread
- 5/16"-24 x 3-7/8" forcing screw
- 9/64" thick 1/4" wide jaw



1022 2-JAW AND 1023 3-JAW 2-TON PULLERS WITH REVERSIBLE JAWS

- 3-1/4" max reach
- 4" max spread for 1022;
4-3/4" max spread for 1023
- 3/8"-24 x 4-7/8" forcing screw
- Jaw thickness: 3/16" upper, 1/8" lower
- Jaw width: 1/4" upper, 1/2" lower



1024 2-JAW AND 1026 2/3-JAW 5-TON PULLERS WITH REVERSIBLE JAWS

- 3-1/4" max reach
- 6" max spread for 1024;
7" max spread for 1026
- 9/16"-20 x 6-15/16" forcing screw
- Jaw thickness: 5/16" upper, 1/4" lower
- Jaw width: 3/8" upper, 3/4" lower



1025 2-JAW AND 1027 2/3-JAW 5-TON LONG PULLERS WITH REVERSIBLE JAWS

- 5-1/2" max reach
- 6" max spread for 1025;
7" max reach for 1027
- 9/16"-20 x 6-15/16" forcing screw
- Jaw thickness: 5/16" upper, 1/4" lower
- Jaw width: 3/8" upper, 3/4" lower



1035 2-JAW AND 1037 2/3-JAW 7-TON PULLERS WITH REVERSIBLE JAWS

- 5" max reach
- 9" max spread on 1035;
10-1/2" max spread on 1037
- 11/16"-18 x 9" forcing screw
- Jaw thickness: 5/16" upper, 11/32" lower
- Jaw width: 1" upper, 1" lower



1036 2-JAW AND 1038 2/3-JAW 7-TON LONG PULLERS

- 8-3/4" max reach
- 9-1/2" max spread on 1036;
11" max spread on 1038
- 11/16"-19 x 9" forcing screw
- Jaw thickness: 11/32"
- Jaw width: 1"

