

LOCK NUT SOCKETS

For removing & installing rounded or hex nuts. All w/ 1/2" drive.

No.	Size
4180	2-1/2" Round
4182	2-3/4" Round
4184	2-3/8" Hex
4186	2-9/16" Round
4188	2-3/8" Round
4190	55mm Hex
4192	2-1/2" Hex



5016 PORSCHE CENTER LOCK NUT SOCKET - 991 & 997

Removes & installs center-lock wheel nuts on Porsche 911 Carrera 997 and 991 performance models. A torque wrench or torque multiplier tool is necessary for proper use.

Compare to Factory Tool: 99136106900.



5415 HD LUG NUT INDICATOR REMOVAL TOOL

Easily removes difficult to remove loose wheel nut indicators off of wheel lugs on HD trucks. Deep reach for easy access with limited clearances.



NEW!

1720 BMW FRONT WHEEL HUB BEARING TOOL

For BMWs w/ stub axle. Guides wheel hub & bearing assembly on & presses bearing into place on E28, E36, E46, E53, E60, E61, E67, E83, E85, E86, E90, E91, E92. M30X1.5 Threads.

Compare to Factory Tool #83300491905.



AXLE NUT SOCKETS

For removing & installing front hub/axle nuts. All w/ 1/2" drive*.

No.	Size	Point
4995	24mm	12
A417	27mm	6
A418	33mm	6
A419	38mm	6
A420	30mm	6
A421	30mm	12
A422	32mm	6
A423	32mm	12
A424	34mm	6
A425	36mm	6
A426	39mm	12
A427	24mm	6
A428	29mm	6



No.	Size	Point
A429	35mm	6
A431	34mm	12
A432	36mm	12
A433	46mm	6
4145	43mm	6
4146	46mm	12 *(3/4" drive)

4219 BENZ FRONT AXLE NUT SOCKET - E24 TORX®

Fits special conical style lug bolts. Impact grade w/ 1/2" square drive. Services 4MATIC models including new C-Class (204, E-Class (212) & S-Class (221).



4026 DODGE WHEEL HUB REMOVAL TOOL

Removes stuck front hubs on 2500 (3/4 ton) and 3500 (1 ton) Dodge P/U's (Late 1990+). Place against hub bolt & turn power steering against tool. Faster and safer than sledge hammer. Solid steel cylinder w/ 3/4" hex opening. OAL: 4-3/4" (12cm).



1200 INNER BEARING RACE PULLER

For precision removal of inner bearing races from wheel hub. Ideal for Transmission Shops & Truck Repair. Includes: Puller, Collet Chuck (48-52mm) for Ford Transit, T330, Collet Chuck (52-56mm) For VW/Audi, Spindle, Reaction Handle, Clamp Nut, Wrench & Pressure Pieces. In blowmold case.



WHEEL BEARING LOCKNUT SOCKETS

Varying lug designs fit the locknuts on many vehicles. All 1/2" drive, (1724 - 3/4" drive).

No.	Applications
1083	Ford Transit 2014+
1724	Toyota Sequoia, Tundra & 4Runner (*3/4" Drive)
3828	Dodge 292AA (11.5") Rear Hub (#2029500030)
4135	Ford F150 & Bronco w/ Dana 44 outer lock nut
4140	Toyota 4WD w/ lockout hubs
4150	Ford, GM, & Dodge 1/2 ton w/ manual hubs
4155	Ford & GM Heavy-Duty 3/4 & 1 ton 4WD
4160	Ford w/ manual hubs, Dana 44 front axle, & Dodge w/ Dana auto hubs

No.	Applications
4165	Ford F-series HD Dana 50 IFS & 60 front axle, 28 front axle, & GM HD 3/4 & 1 ton
4166	Ford F-Series Super Duty w/ 10-1/2" rear axle
4168	GM/Chevy 2 & 4WD w/ 10-1/2 - 11-1/2" ring gears
4170	Isuzu, Honda & Jeep J20 pick-ups w/ Dana 60
4175	Ford F-Series Dana 80 rear axle
4177	Chevy & GMC 5,200 & 7,200 lb axles (*3/4" Drive)
5045	Dodge RAM 1500-4500. Compare to Factory Tool: 8954A

