

Air Filters

Contamination Elimination



Model F88 Air Filter

Model F88 Air Filter is highly effective at removing water, oil & contamination. It protects air cylinders and air tools and features a reusable edge-type filter element.

PN	Description
8130	Air filter, 75 cfm
U32719	Replacement filter element

- 5 micron filtration
- Air Inlet Size: 1/2 in NPT
- Air Outlet Size: 3/8 in NPT and 1/4 in NPT plugged
- Max. Operating Pressure: 160 psi (11.0 bar)
- Filter Capacity: 75 cfm
- Instruction Manual: PN 310603
- Reference p. 57



Model F88M Mechanic's Air Filter

Model F88M Mechanic's Air Filter is designed for the mechanic who wants to protect their investment in air tools. This unit is portable and easily mounts anywhere. It is designed for use with quick couplers.

PN	Description
8135	Air filter with quick connect, 75 cfm
U32719	Replacement filter element

- 5 micron filtration
- Air Inlet Size: 1/4 in NPT
- Air Outlet Size: 1/4 in NPT and 1/4 in NPT plugged
- Max. Operating Pressure: 160 psi (11.0 bar)
- Filter Capacity: 75 cfm
- Instruction Manual: PN 310603
- Reference p. 57



Model 606 Air Filter

The Model 606 Air Filter is most effective at removing water, oil & contamination. Its features include a large, reusable, edge-type filter element.

PN	Description
U06710	Air filter, 120 cfm
19930	Replacement filter element

- 5 micron filtration
- Air Inlet Size: 1/4 in NPT
- Air Outlet Size: 1/4 in NPT and 1/4 in NPT plugged
- Max. Operating Pressure: 160 psi (11.0 bar)
- Filter Capacity: 120 cfm
- Instruction Manual: PN 310601
- Reference p. 59

Air Control Units

Protection for Air Cylinders & Air Tools



880A Air Control Unit

Highly effective at removing water, oil and contamination to protect air cylinders and air tools. Contains 18C-3R Regulator with a 160 lb inverted gauge and air cock. Regulated outlet and filtered main line outlet included.

PN

Description

6950	Air Control Unit, 75 cfm
U32719	Replacement filter element

- 5 micron filtration
- Air Inlet Size: 1/2 in NPT (f)
- Air Outlet Size: 3/8 in NPT (f) and 1/4 in NPT (f) plugged
- Max. Operating Pressure: 200 psi (13.6 bar)
- Filter Capacity: 75 cfm
- Regulator Capacity: 50 cfm
- Instruction Manual: PN 310603
- Reference p. 58



606A Air Control Unit

Effective at removing water, oil and contamination to protect air cylinders and air tools. Contains 18C-3R Regulator with a 160 lb inverted gauge and air cock. Regulated outlet and filtered main line outlet included.

PN

Description

U06720	Air Control Unit, 120 cfm
19930	Replacement filter element

- 5 micron filtration
- Air Inlet Size: 1/2 in NPT
- Air Outlet Size: 1/4 in NPT
- Max. Operating Pressure: 200 psi (13.6 bar)
- Filter Capacity: 120 cfm
- Regulator Capacity: 50 cfm
- Instruction Manual: PN 310601
- Reference p. 60



606B Air Control Unit

Effective at removing water, oil and contamination to protect air cylinders and air tools. Contains 18C-3R Regulator with a 160 lb inverted gauge and air cock. Regulated outlet and filtered main line outlet with 200 lb gauge included.

PN

Description

6730	Air Control Unit, 120 cfm
19930	Replacement filter element

- 5 micron filtration
- Air Inlet Size: 1/2 in NPT
- Air Outlet Size: 1/4 in NPT
- Max. Operating Pressure: 200 psi (13.6 bar)
- Filter Capacity: 120 cfm
- Regulator Capacity: 50 cfm
- Instruction Manual: PN 310601
- Reference p. 60



606C Air Control Unit

Effective at removing water, oil and contamination to protect air cylinders and air tools. Contains two 18C-3R Regulators with a 160 lb inverted gauge and air cock. Two regulated outlets and a filtered main line outlet with 200 lb gauge included.

PN

Description

6740	Model 606C Air Control Unit
19930	Replacement Filter Element

- 5 micron filtration
- Air Inlet Size: 1/2 in NPT
- Air Outlet Size: 1/4 in NPT
- Max. Operating Pressure: 160 psi (13.6 bar)
- Filter Capacity: 120 cfm
- Regulator Capacity: 50 cfm
- Instruction Manual: PN 310601
- Reference p. 60

REFERENCE

REPLACEMENT PARTS DRAWINGS INDEX

F88 Air Filter Part No. 8130

