

MAX Comfort. MAX Performance.

In keeping with the tradition of Ingersoll Rand MAX tools, the 118MAX and 122MAX vibration-reduced air hammers deliver the MAX Comfort, MAX Power, and MAX Productivity needed to accomplish your most challenging material preparation jobs.



Quick-change retainer
Provides fast chisel changeovers
(Included with tool)

- MAX Comfort

Anti-vibration feature reduces tool vibration by over 30% when compared to standard air hammers in its class
- MAX Power

15% increase in impact force over standard air hammer product offering
- MAX Productivity

Quick-change retainer allows for faster chisel changeovers, so you can get the job done

Model	Shank Opening in (mm)	Blows Per Minute bpm	Bore Diameter in (mm)	Stroke Length in (mm)	Tool Weight w/o Retainer wlb (kg)	Tool Length w/o Retainer in (mm)	Average Air Consumption cfm (L/min)	Air Consumption @ Load cfm (L/min)	Vibration (m/s ²)	Sound Pressure / Power dBA	Air Inlet NPTF in	Min Hose Size in (mm)
MAX SERIES												
118MAX	0.401" (10.2)	2500	0.75" (19)	3.5" (89)	4.6 (2.1)	10.5" (266)	2.9 (82.9)	11.6 (332.6)	5.7	94.7 / 105.7	1/4"	3/8" (10)
122MAX	0.401" (10.2)	3500	0.75" (19)	2.63" (67)	4.0 (1.8)	8.6" (218)	2.9 (82.9)	11.6 (332.6)	7.5	94.7 / 105.7	1/4"	3/8" (10)

Performance figures are at 90 psi



ingersollrandproducts.com/airhammers

Kit includes vibe-reduced air hammer, quick-change retainer, 5-piece chisel set and case.

118MAX & 122MAX