

Product Safety Information

Intended Use:

These Tire Buffers are designed for tough patchwork and roughing up jobs on tires.

For additional information refer to Product Safety Information Manual Form 04584991.
Manuals can be downloaded from ingersollrandproducts.com.

Product Specifications

Model	Chuck Capacity	Free Speed	Rated Horse Power
327	3/8"	22000	1/2
327-EU	3/8"	22000	1/2
327LS	3/8" Hex. Quick Change	3000	1/2
327LS With Exhaust Hose	3/8" Hex. Quick Change	3000	1/2

Model	Sound Level dB (A) (ISO15744)		Vibration m/s ² (ISO 28927)	
	† Pressure (L _p)	‡ Power (L _w)	Level	*K
327	87.9	98.9	4.6	1.1
327-EU	87.9	98.9	4.6	1.1
327LS	92.0	103.0	< 2.5	---
327LS With Exhaust Hose	77.4	88.4	< 2.5	---

† K_{PA} = 3dB measurement uncertainty

* K = Vibration measurement uncertainty

‡ K_{WA} = 3dB measurement uncertainty



WARNING

Sound and vibration values were measured in compliance with internationally recognized test standards. The exposure to the user in a specific tool application may vary from these results. Therefore, on site measurements should be used to determine the hazard level in that specific application.