

Model 81726



Assemblies for standard hydraulic fittings

Model	Whip hose		Coupler	Thread size NPT (m)	Maximum pressure Working	
	–	in. mm			psi	bar
81725	5818	18 457	5845	1/8	4 500	310
81726	5812	12 305	5845	1/8	4 500	310
81795*	5812	12 305	5845	1/8	4 500	310

* Includes model 81980 locking sleeve

Model 81795



Model 3029



Assemblies for button-head couplers with swivel

Model	Whip hose		Coupler	Thread size NPT (m)	Maximum pressure Working	
	–	in. mm			psi	bar
3029	5812	12 305	80933/large	1/8	4 000	276
3034	5812	12 305	81458/standard	1/8	4 000	276
3055	5861	36 914	81458/standard	1/8	4 000	276
3056	5861	36 914	80933/large	1/8	4 000	276

Model 3034



Model 5858



Flexible and rigid extension adapter

Model 5858

Maximum working pressure 5 000 psi (345 bar). Allows operator to switch from flexible to rigid extension with one hand. Overall length 13 in. (330 mm). 1/8 in. NPT (m). For use on hand guns or air operated grease control valves.

WARNING!

Whip hose models 3029, 3034, 5812, 5818, 5861, 81725, 81726, 81795

Install as shown

