

**98211-A ACCU-CHARGE III CERTIFIED REFRIGERANT SCALE (OIML & CE Approved, Legal for Trade)****CE OIML****FUNCTIONS:****CHARGE PROGRAMMING:**

Allows user to program desired quantities. Before charge is complete, an alarm will sound allowing user ample time to turn off refrigerant supply.

**PAUSE/CHARGE:**

(Using the 98230 charging solenoid module)

**TANK CAPACITY PROGRAMMING:**

Allows user to know the amount of refrigerant that is left in the tank at any time.

**REPEAT:**

Allows user to charge previously stored amount.

**SPECIFICATIONS:**

- Complies with European (OIML) standards
- Capacity: 110 lbs (50 kg)
- Accuracy:  $\pm 50$  g
- Resolution: 0.05 kg
- 3 hours auto off function
- Operating temperature: 32 to 120°F (0 to 49°C)
- Battery life: approximately 40 hours
- 9 x 9" (22 x 22 cm) platform

**98230 CHARGING SOLENOID MODULE**

**The 98230 charging solenoid module turns the 98210-A ACCU-CHARGE II & 98211-A ACCU-CHARGE III into automatic programmable scales!**

This module allows the user to control the exact amount of refrigerant transferring to and from the A/C system. The compact design is battery powered (9V), lightweight, portable and works with all types of refrigerant. 98230 includes a short hose for tank connection, USB cord and 1/4"FL - 1/2" ACME adapters.

**98250 ELECTRONIC TANK HEATER BLANKET**

The Mastercool refrigerant tank heater blanket speeds up recharging time.

- Assures total discharge of refrigerant from 30 lb and 50 lb tanks. Heats tanks to 125°F resulting in maximum pressure of 185 psi for R134a and 170 psi for R12
- Quick working 300W heater element
- An excellent complement to all Mastercool refrigerant scales



**Mastercool<sup>®</sup>**  
"World Class Quality"