



AIRCRAFT® Paint Remover

GAR343, QAR343
EAR322

Gallon, Quart Liquid
18oz Aerosol



- Starts Working in 5 Minutes (aerosol in 15 minutes)
- Lifts Multiple Layers
- Removes acrylics, epoxies, enamels, lacquers, polyurethanes, and most other automotive finishes
- Clings well to vertical surfaces
- Water Rinsable

FINISH REMOVAL TIPS

1. KLEAN-STRIP® AIRCRAFT® Paint Remover begins to work in as little as 5 minutes. Once applied, allow time for the remover to do the work. Let stand until finish is completely blistered or liquefied. The time will vary from 5 to 45 minutes for most finishes.
2. Scratching or abrading the finish will often speed up the stripping action.
3. **Always apply a generous amount of remover. Thickly daubing remover onto the surface, rather than brushing, provides better coverage. Thin coats can dry too quickly for the remover to work effectively.**
4. On particularly tough finishes, and to minimize evaporation, secure a 2 – 3 mil polyethylene film over wet remover. For best results, let the remover stand up to two hours, and if necessary, repeat with a second application.
5. If stripper dries on the surface, scrape loosened portions and reapply as needed.
6. Mask seams and trim openings to prevent bleed-back stripping of new finish.

*Not intended for use on aircraft.





AIRCRAFT® Paint Remover

	GAR343/QAR343	EAR322
Appearance	Thick, orange to brown opaque paste with strong ammonia odor	Yellow to orange clinging liquid
Vapor Density	Heavier Than Air	
Percent Volatile	95% by weight	98% by weight
Flash Point	No Flash to Boiling	N/A
CPSC Flammability Classification	Not a Flammable or Combustible Liquid	Flammable
Boiling Range	105°F to 300°F	N/A
Max VOC	11.1%	Less than 50%
Storage	Store in a cool place. Prolonged exposure to temps in excess of 90°F may cause can to leak or swell. Do not reuse container. Once opened, remover should be used within 6 months or disposed of properly to avoid can deterioration.	Replace overcap on container after each use. Contents under pressure. Do not puncture, incinerate or store above 120°F. Exposure to heat or prolonged exposure to sun can cause bursting.
Density	9.8 lb/gal	10.5 lb/gal
Shelf Life	2 years from date of manufacture, in an unopened container	
DOT	UN1760, Corrosive Liquid, N.O.S., 8, PGI (Ammonium Hydroxide, Methylene Chloride)	UN1950, AEROSOLS, flammable, 2.1, Limited Quantity
HAPS	Methylene Chloride, Methanol, Xylene, Ethyl Benzene	Methylene Chloride, Methanol
Coverage	25 – 50 sq. ft. per can	10 – 15 sq. ft. per can
VOC Category	Paint Removers or Strippers	

ORDERING INFORMATION

Product	Size	Pack	Lbs	Cube Ft.	Width	Depth	Height	UPC Code	Pallet Qty
QAR343	QT	6	17	.347	7 10/16	9 11/16	8 2/16	030192343159	125 cases
GAR343	GL	2	22	.404	7 1/16	8 14/16	11 2/16	030192343258	104 cases
EAR322	18oz	4	6	.194	5 11/16	5 11/16	10 6/16	030192322994	168 cases

©2009 W.M. Barr & Co., Inc.
P.O. Box 1879
Memphis, TN 38101
800.238.2672
www.bulldogsticks.com
www.kleanstripauto.com

